NET CAMERA M3216-LVE DOME/02372-001 AXIS

Gamintojas: **AXIS** · Modelis: **02372-001** · EAN: **7331021076556** · Prekės kodas: **923885**



969,90 €

Kaina su PVM

Be PVM: **801,57 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt






Aprašymas

This cost-effective fixed focal dome offers Lightfinder, Forensic WDR, and OptimizedIR, and ensures excellent image quality under any light conditions. Built on ARTPEC-8, it includes a deep learning processing unit enabling powerful analytics based on deep learning on the edge. Plus, it delivers valuable metadata facilitating fast, easy, and efficient forensic search capabilities. And AXIS Object Analytics offers detection and classification of humans, vehicles, and types of vehicles—all tailored to your specific needs. Featuring audio and I/O connectivity, you can integrate for instance a microphone to extend the value of your system. Furthermore, built-in cybersecurity features safeguard your system.

- Analytics with deep learning; Audio and I/O connectivity; Built-in cybersecurity features; Excellent image quality in 4 MP; Lightfinder, Forensic WDR, OptimizedIR

Summary: Axis M3216-LVE. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Dome. Minimum illumination: 0.16 lx, Angle of rotation: 190°, Lens viewing angle, horizontal: 102°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Fixed focal length: 2.9 mm, Closest focusing distance: 1 m | Vendor Homepage: https://www.axis.com/products/axis-m3216-lve | Form factor: Dome | Mounting type: Ceiling/wall | Product colour: White | Housing material: Plastic/Polycarbonate (PC) | International Protection (IP) code: IP66 | IK code: IK10 | Fog proof: Yes | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor & outdoor | PTZ control: Yes | PTZ modes: Digital PTZ | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Minimum illumination: 0.16 | Angle of rotation: 190 | Lens viewing angle, horizontal: 102 | Lens viewing angle, vertical: 73 | Tilt angle range: -10 - 80 | Pan range: 0 - 190 | Camera shutter speed: 1/50000 - 1/5 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Zoom capability: Yes | Minimum aperture number: 2 | Closest focusing distance: 1 | Fixed focal length: 2.9 | Night vision: Yes | LED type: IR | Maximum resolution: 2688 x 1512 | Video compression formats: H.264/H.265 | Frame rate: 30 | Video streaming: Yes | Privacy masking: Yes | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.1x | Supported network protocols: IPv4, IPv6 USGv6,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

ICMPv4/ICMPv6, HTTP, HTTPSa, HTTP/2, TLSa, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTCP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, ARP, SOCKS, | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash)/MicroSDHC/MicroSDXC | Flash memory: 8192 | Internal memory: 1024 | Ethernet LAN (RJ-45) ports: 1 | Microphone in: Yes | HTTPS encryption: Yes | Security algorithms: EAP-TLS/HTTPS | Power source type: PoE | Power consumption (Power over Ethernet (PoE)): 4.8 | Operating temperature (T-T): -40 - 50 | Storage temperature (T-T): -40 - 65 | Operating relative humidity (H-H): 10 - 100 | Storage relative humidity (H-H): 5 - 95 | Height: 102 | Diameter: 149 | Weight: 791 | Number of cameras: 1 | Unit Calculated Weight: 1.09 | Product Net Weight: 0.791 | Unit Calculated Volume: 0.00602 | Units per Shipping Box: 1 | Unit Width: 20 | Shipping Box Height: 14 | Unit Depth: 21.5 | Unit Height: 14 | Name: NET CAMERA M3216-LVE DOME/02372-001 AXIS | Model: M3216-LVE

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	22,00cm × 20,00cm × 14,00cm