HP ScanJet Pro 3600 f1 Flatbed scanner 1200 x 1200 DPI A4 White

Gamintojas: **HP INC** · Modelis: **20G06A** · EAN: **5715063395011** · Prekės kodas: **924774**



555,90 €

Kaina su PVM

Be PVM: **459,42 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt


Pagrindinės savybės


- ✓ ADF; CIS scanning technology; Flatbed
- ✓ Up to 600 dpi (color and mono, ADF); Up to 1200 dpi (color and mono, flatbed)
- ✓ Paper (banner, inkjet, photo, plain), envelopes, labels, cards (greeting, index)
- ✓ 6 lights (Shortcut, Duplex, Error); 5 button (Power, Scan, Duplex, Shortcut Select, Cancel)
- ✓ 13.31 watts (Active - Scanning), 5.31 watts (Ready), 1.23 watts (Sleep), 0.07 (Auto-Off), 0.07 (Manual-Off)
- ✓ Recommended daily duty cycle: 3000 pages (ADF)
- ✓ Scan front-panel function : Save as PDF, Save as JPEG, Scan to E-mail, Send to Cloud and Scan to USB. HP Scan in Win OS, HP Easy Scan/ICA in Mac OS and third parties applications via TWAIN.













Aprašymas

Enhance productivity with reliable and fast, two-sided scanning, a 60 page ADF, and one-button shortcuts. Boost productivity for professional scanning tasks with the fast, compact, and reliable HP ScanJet Pro, designed for scanning up-to 3,000 pages daily. Automate workflows with one-click shortcuts and fast, two-sided scanning from the auto document feeder.

Techninė specifikacija

Scanning	
Maximum scan size	216 x 297 mm
Optical scanning resolution	1200 x 1200 DPI
Duplex scanning	Yes
Colour scanning	Yes
Greyscale levels	256
ADF scan speed (b/w, A4)	30 ppm
ADF scan speed (greyscale, A4)	30 ppm
ADF scan speed (colour, A4)	30 ppm
Design	
Scanner type	Flatbed scanner
Built-in display	No
Product colour	White
Control type	Buttons
Performance	
Sensor type	CIS
Daily duty cycle (max)	3000 pages
Scan file formats	BMP, CSV, DOC, DOCX, JPEG, PDF, PNG, RTF, TIFF, TXT, XLS, XLSX
Scan to	USB
Scan drivers	ICA, TWAIN
Internal memory	256 MB
Built-in processor	Yes
Processor frequency	666 MHz
HP segment	Home, Home office, Business
Input capacity	
Auto document feeder (ADF) input capacity	60 sheets
Paper handling	
Maximum ISO A-series paper size	A4
Scanning media types supported	Card stock, Envelopes, Labels, Photo paper, Plain paper

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

ISO A-series sizes (A0...A9)	A4, A5, A6
ISO B-series sizes (B0...B9)	B5
Auto Document Feeder (ADF) media weight	49 - 120 g/m²
Maximum scan area (ADF)	216 x 3100 mm
Minimum scan area (ADF)	89 x 148 mm

Ports & interfaces

USB port	Yes
USB version	3.2 Gen 1 (3.1 Gen 1)

Power

Power supply type	AC
Power consumption (typical)	13.31 W
Power consumption (standby)	5.31 W
Power consumption (off)	0.07 W
Power consumption (PowerSave)	0.07 W
Sleep mode	Yes
Input voltage	100 - 240 V
Power consumption (sleep)	1.23 W

Weight & dimensions

Width	491.5 mm
Depth	325.4 mm
Height	133.3 mm
Weight	5.4 kg

Packaging data

Package width	600 mm
Package depth	245 mm
Package height	499 mm
Package weight	7.3 kg

Packaging content

Cables included	USB, AC
Bundled software	HP Scan Software, HP Scanner Device Driver, HP WIA scan driver, HP TWAIN scan driver, HP Scanner Tools Utility, HP Easy Scan for MacOS

Sustainability

Sustainability certificates	ENERGY STAR, EPEAT, EPEAT Silver
Total carbon footprint (kg of CO2e)	82
Sustainability compliance	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

System requirements	
Minimum system requirements	Microsoft Windows (11, 10, 8.1, 7 : 32-bit and 64-bit, 2008 R2, 2012 R2, 2016, 2019); 2 GB available hard disk space, Internet connection, Microsoft Internet Explorer or any browser
Compatible operating systems	Windows 11; Windows 10; Windows 8; Windows 8.1; Windows 7; Windows Server; macOS 10.14 Mojave; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Linux
Windows operating systems supported	Windows 7, Windows 8, Windows 8.1, Windows 10, Windows 11
Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, MacOS
Server operating systems supported	Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Operational conditions	
Operating temperature (T-T)	10 - 35 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	15 - 80%
Storage relative humidity (H-H)	0 - 90%
Certificates	
Electromagnetic compatibility	Class B Emissions; CISPR 32:2015 (International); European Union EMC Directive 2004/108/EC, EN 55032:2015 (CE mark); China GB9254-2008 (CCC); Taiwan CNS13438:2006 (BSMI); USA CFR47 Part 15, Subpart B (FCC); ICES-003:2020 Issue 7 (Canada); Australia C-tick (includes New Zealand); KN 22 and Korea KCC; EAC EMC Certificate; Ukraine EMC approval; EN 61000-3-2:2014 (harmonics); EN 61000-3-3:2013 (flicker); Immunity 505035:2017
Other features	
Recommended system requirements	Microsoft Windows (11, 10, 8.1, 7; 32-bit and 64-bit, 2008 R2, 2012 R2, 2016, 2019); 2 GB available hard disk space; Internet connection; Microsoft Internet Explorer or any browser. macOS Mojave 10.14; macOS Catalina 10.15 and macOS Big Sur 11.x; Internet required.
Other operating systems supported	Linux
Media types supported	Paper (banner, inkjet, photo, plain), envelopes, labels, cards (greeting, index)
Image formats supported	JPEG, PNG, TIFF
Maximum scan resolution	1200 x 1200 DPI
Compliance certificates	CECP
Certification	Class B Emissions; CISPR 32:2015 (International); European Union EMC Directive 2004/108/EC, EN 55032:2015 (CE mark); China GB9254-2008 (CCC); Taiwan CNS13438:2006 (BSMI); USA CFR47 Part 15, Subpart B (FCC); ICES-003:2020 Issue 7 (Canada); Australia C-tick (includes New Zealand); KN 22 and Korea KCC; EAC EMC Certificate; Ukraine EMC approval; EN 61000-3-2:2014 (harmonics); EN 61000-3-3:2013 (flicker); Immunity 505035:2017
Non-operating relative humidity (non-condensing)	0 - 90%

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Recommended humidity operating range	30 - 70%
Recommended operating temperature range (T-T)	17.5 - 25 °C
UNSPSC-code	43211711
Box contents	HP ScanJet Pro 3600 f1 Scanner; Install Guide; Supporting flyers; Cushions; USB cable; Power adapter; Power cords

Logistics data

Products per pallet	32 pc(s)
Country of origin	China, Taiwan
Layers per pallet	4 pc(s)
Master (outer) cases per pallet layer	8 pc(s)
Harmonized System (HS) code	8471608000

Matmenys ir svoris

Svoris	6,90kg

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- CE ženklinimas
- Vaizdo įrašas objects.icecat.biz/objects/94591524_74747283.mp4

Gamintojo ir saugos informacija

GAMINTOJAS

HP Inc
Page Mill Road 1501, CA 94304 Palo Alto, California, US
hp.com

ATSAKINGAS ASMUO ES

HP Printing and Computing Solutions S.L.U.
Calle Jose Echegaray 18, 28232 Las Rozas (Madrid), ES
hp.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- CE ženklinimas