

D-Link 52-Port PoE Gigabit Smart Managed Switch including 4 x 100/1000Mbps Combo Ports

Gamintojas: **D-LINK** · Modelis: **DGS-1210-52MP** · EAN: **790069409592** · Prekės kodas: **925773**



751,89 €

Kaina su PVM

Be PVM: **621,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 48 x 1000Base-T 802.3af/802.3at PoE
- ✓ 370W PoE budget
- ✓ 4 x Combo



Aprašymas

Smart Managed with a Plus

With increased PoE output, advanced Layer 2 management features, and Layer 3 static routing , D-Link's DGS-1210 Smart+ Managed Gigabit Switches provide a cost-efficient and flexible solution for expanding any business network.

Advanced Layer 2 Management with Layer 3 Static Routing

The DGS-1210 Smart+ family has advanced network management options, accessible via Compact CLI or the Web-based UI, that equip your business with network capabilities such as VLANs, multiple spanning tree protocol (MSTP), link aggregation (LACP), static routing, dual software images, and dual configuration files.

With powerful security features like IGMP snooping, access control lists, port security, and the unique D-Link Safeguard Engine that protects your network against malicious denial-of-service attacks from broadcast, multicast and unicast flooding, the DGS-1210 Smart+ family is a versatile solution for access-edge network environments.

Fibre Uplinks

Use fibre uplinks to connect across longer distances, like factory lines and university campuses, using lightweight, secure, and energy-efficient fibre optic cabling that's immune to interference and which has access to higher throughput to protect the future demands of your business network.

PoE and PoE+, with budgets up to 370W

The DGS-1210 Smart+ Series includes a range of high power budget PoE-enabled switches for businesses looking to power larger deployments of VoIP phones, wireless access points or network cameras.

This product is compatible with Nuclias Connect

Nuclias Connect is our free remote network management software designed with network scalability, privacy and customisation in mind. It can be used either as an on-premises software management platform, or as a cloud solution.

Free Network Design and Management Software

D-Link's free Network Assistant (DNA) displays all connected devices and speeds up the first time configuration. The free D-View 7 Network Management System comes with a license for 25 nodes and 2 probes and full access to the management tools. Optional upgrade licenses allow you to broaden your network and analysis.

Smart Energy-Saving Design

D-Link Green technology enables the DGS-1210 Smart+ series to save power without any sacrifices. The majority of the family utilises a fanless design, otherwise they feature a smart fan that powers on above a certain temperature. All come with advanced silicon technology which saves up to 73% of energy compared to a normal switch.

Surveillance Mode

Select Surveillance Mode in the Web UI to take advantage of easy-to-use surveillance features which enable you to manage your surveillance network effortlessly. It automatically detects your security devices and segments them into a dedicated Auto Surveillance VLAN to handle video surveillance traffic securely and efficiently.

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes

MIB support	Y
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Combo SFP ports quantity	4
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
Spanning tree protocol	Yes
Head-of-line (HOL) blocking	Yes
Auto-negotiation	Yes
VLAN support	Yes
Number of VLANs	256
Data transmission	
MAC address table	16000 entries
Switching capacity	104 Gbit/s
Forwarding rate	77.4 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	10000
Packet buffer memory	12 MB
Security	
DHCP features	DHCP server, DHCP client
Access Control List (ACL)	Yes
IGMP snooping	Yes

MAC address filtering	Yes
Loop protection	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Stackable	Yes
Form factor	1U
Product colour	Black
LED indicators	Yes
Performance	
Memory type	DDR3-SDRAM
Internal memory	256 MB
Flash memory	32 MB
Noise level	52.4 dB
Mean time between failures (MTBF)	236667 h
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	478.9 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	-5 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Heat dissipation	1634.01 BTU/h
Weight & dimensions	
Width	440 mm
Depth	430 mm
Height	44 mm

Weight 6.26 kg

Matmenys ir svoris

Svoris 8,90kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
[dlink.com](https://www.dlink.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- › [Atitikties deklaracija](#)