

Viewsonic LS832WU data projector Ultra short throw projector 5000 ANSI lumens WUXGA (1920x1200) White

Gamintojas: **VIEWSONIC** · Modelis: **LS832WU** · EAN: **766907021912** · Prekės kodas: **926726**



4 079,90 €

Kaina su PVM

Be PVM: **3 371,82 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 0.25 ultra short throw for space-saving installation
- ✓ 2nd generation Laser Phosphor technology with up to a 30,000-hour lifespan
- ✓ 5,000 ANSI Lumens offering bright images in any environment
- ✓ Up to 170" ultra-large screen with lower cost-per-inch
- ✓ H/V keystone and 4 corner adjustment for enhanced installation flexibility
- ✓ Comprehensive LAN control providing efficient device management





Aprašymas

The LS832WU is part of ViewSonic's Luminous Superior series, a lamp-free high brightness projector lineup designed for both commercial and educational spaces. This advanced 5,000 ANSI Lumens WUXGA ultra short throw laser projector is a go-to digital signage solution for public and commercial applications, such as museums, storefronts, shopping malls, and airports. The LS832WU's 0.25 ultra short throw ratio allows for a 100" screen from only 28 cm away, and the screen size can be further expanded up to 170", offering a lower cost-per-inch compared to other types of commercial displays. Adopting the 2nd generation Laser Phosphor technology, it produces consistent high brightness for up to 30,000 hours lifespan. With H/V keystone and 4 corner image adjustment, the LS832WU also offers flexible installation options. Complete with comprehensive LAN control, it enables centralized management of multiple devices and is compatible with Crestron, AMX, Extron, and PJ Link AV control systems.

No Shadows, No Blinding Lights

Designed to provide installation flexibility even in reduced spaces, the LS832WU's 0.25 ultra short throw ratio enables a 100" screen projection from only 28 cm away, offering immersive visuals without shadow casting or blinding lights for all commercial and public display applications.

Ultra-large Screen with Lower Cost-per-inch

This easy-to-install projector allows for an image size of up to 170", offering a lower cost-per-inch compared to other types of commercial displays.

Bright, Durable, Eco-friendly

The LS832WU uses 2nd generation laser phosphor technology, offering up to a 30,000 hours lifespan, improved brightness, better heat resistance and instant power on/off in a more compact format. The projector's eco-friendly, lamp-free design eliminates toxic mercury lightbulbs and the hassle of frequent lamp replacement, ensuring consistent image quality during extended commercial display applications.

Bright Images in All Lighting Conditions

The LS832WU's 5,000 ANSI Lumens and 3,000,000:1 contrast ratio ensure bright and vibrant visuals in all light conditions, even under ambient lighting, making it perfectly suited for digital display applications in public and commercial spaces such as in museums, airports, or shopping malls.

Get Perfectly-shaped Images Effortlessly

Horizontal and Vertical Keystone correction along with 4 corner adjustment features eliminate crooked or distorted images for a perfectly proportioned picture every time.

Easy and Cost-effective Installation

The LS832WU is 41% lighter in weight and 47% smaller in size compared to its predecessor, greatly reducing the cost of transportation and increasing the ease of installation.

Centralized Device Management

The LS832WU is compatible with Crestron, AMX, PJ Link, and Extron systems, allowing for centralized device management for better operational efficiency.

Non-stop 24/7 Operation

With an advanced cooling design, it enables 24/7 operation without degradation of quality or performance, making the projector ideal for applications that require continuous projection.

Enhanced Dust Resistance

Maintain crystal-clear image quality and product longevity with an advanced IP5X sealed design that prevents dust from entering and affecting internal components.

Present the Best with Vibrant Colors

Impress any audience with ViewSonic's exclusive color technology, elevating your presentation with a true-to-life color experience.

Seamless Display from External Devices

Prevent display formatting issues with dual HDMI 2.0b/HDCP 2.2 ports and support for 4K UHD and HDR/HLG content from external devices. Enjoy total peace of mind knowing that your content will be displayed error-free.

A Simpler Way to Update Projector Software

Skip trips to the service center by keeping software up to date easily via USB cable connection with your laptop.

Power Wireless HDMI Dongle

The LS832WU's built-in 5V/1.5A USB output can conveniently deliver power to a Wireless HDMI Dongle, eliminating the need for separate power adapters when streaming multimedia content.

Techninė specifikacija

Projector	
Projector brightness	5000 ANSI lumens
Projector native resolution	WUXGA (1920x1200)
Contrast ratio (typical)	3000000:1
Screen size compatibility	2032 - 4318 mm (80 - 170")
Number of colours	1.07 billion colours
Keystone correction, horizontal	10°
Keystone correction, vertical	10°
Horizontal synchronization (min)	15 kHz
Horizontal synchronization (max)	91 kHz
Light source	
Light source type	Laser
Service life of light source	20000 h
Service life of light source (economic mode)	30000 h

Lens system

Focal length range	3.7 mm
Zoom capability	Yes
Zoom type	Fixed
Throw ratio	0.253
Offset	133%

Ports & interfaces

VGA (D-Sub) ports quantity	1
HDMI ports quantity	2
Audio (L/R) in	1
Serial interface type	RS-232
HDMI version	2.2/1.4
USB 2.0 ports quantity	1
USB 2.0 Type-A ports quantity	1
USB 2.0 Type-B ports quantity	1
Microphone in	Yes

Network

Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1

Features

Noise level	34 dB
Noise level (economic mode)	28 dB

Multimedia

Built-in speaker(s)	Yes
RMS rated power	10 W
Number of built-in speakers	1

Design

Product type	Ultra short throw projector
Market positioning	Portable
Product colour	White

Display

Built-in display	No
------------------	----

Power

Power source	AC
--------------	----

Power consumption (typical)	328 W
Power consumption (standby)	0.5 W
AC input voltage	100-240 V
AC input frequency	50-60 Hz
Operational conditions	
Operating temperature (T-T)	5 - 40 °C
Weight & dimensions	
Weight	7 kg
Width	382 mm
Depth	318 mm
Height	132 mm
Package width	518 mm
Package depth	420 mm
Package height	313 mm
Package weight	10 kg
Packaging content	
Remote control included	Yes
Logistics data	
Pallet gross length	94 cm
Pallet gross width	114 cm
Pallet gross height	2.08 m
Products per master (outer) case	1 pc(s)
Harmonized System (HS) code	8528620000

Gamintojo ir saugos informacija

GAMINTOJAS

Viewsonic

ATSAKINGAS ASMUO ES

ViewSonic Technology GMBH

Fürst-Leopold-Platz 1, 46284 Dorsten, DE

[viewsonic.com](https://www.viewsonic.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt