TP-Link Omada MC212CS-2 network media converter 1000 Mbit/s 1550 nm Single-mode Black

Gamintojas: **TP-LINK** · Modelis: **MC212CS-2** · EAN: **1210002601115** · Prekės kodas: **926748**



26,90 €

Kaina su PVM

Be PVM: **22,23 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1× 10/100/1000Mbps Auto-Negotiation RJ45 port supports Auto-MDI/MDIX
- ✓ Auto-negotiation of Half-Duplex/Full-Duplex transfer mode
- ✓ Adopts WDM technology, transmitting and receiving data on one single fiber
- ✓ Extends fiber distance up to 2 km



Aprašymas

MC212CS-2 is a gigabit media converter, providing a gigabit RJ-45 port and a gigabit SC fiber port, which can convert between electrical and optical signals. And long-distance data transmission through optical fiber can be applied to commercial scenarios such as park security monitoring and wireless networking.

Techninė specifikacija

Network	
Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Duplex system	Full, Half
Performance	
Maximum transfer distance	2000 m
Wavelength	1550 nm
Wavelength-division multiplexing (WDM)	Yes
Fiber mode structure	Single-mode
Features	
Internal	No
LED indicators	Activity, Link, Power
Product colour	Black
Ports & interfaces	
Fiber optic connector	SC/UPC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Input voltage	9 V
Input current	0.6 A
Weight & dimensions	
Width	94.5 mm
Depth	73 mm
Height	27 mm
Operational conditions	
Operating temperature (T-T)	-5 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Packaging content	
AC adapter included	Yes
Quick installation guide	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Matmenys ir svoris	
Matmenys (I × P × A)	7,00cm × 21,00cm × 17,00cm
Svoris	0,37kg

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH
Niederkasseler Lohweg 175, 40547 Düsseldorf, DE
tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt