

Vertiv Liebert GXT5 Lithium-Ion Online UPS 1000 VA/1000 W 230 V Rack/Tower

Gamintojas: **VERTIV** · Modelis: **GXT5-1000IRT2UXLN** · EAN: **4061471435285** · Prekės kodas: **926966**



1 771,90 €

Kaina su PVM

Be PVM: **1 464,38 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Lithium-Ion UPS batteries last up to 3x longer than traditional VRLA batteries; with 5-year warranty on UPS and batteries
- ✓ Offers lowest total cost of ownership (TCO) with fewer or no battery replacements over its lifetime
- ✓ Environmentally friendly UPS reduces battery disposal and recycling with lower replacement rates
- ✓ The 1 kVA UPS offers longer runtime and faster recharge time
- ✓ Add 1U external battery cabinet units to power the UPS for scalable runtime



Aprašymas

The Vertiv Liebert GXT5 Lithium-Ion UPS protects critical IT applications against outages and various power disturbances. This online UPS offers the highest level of power conditioning and battery backup in server rooms, network closets, and other edge or distributed IT locations. Lithium LFB batteries require fewer battery replacements and last up to 3x as long as traditional VRLA batteries reducing maintenance, labor, and replacement costs (resulting in the lowest TCO). Internal batteries offer industry-leading runtime (up to 14 minutes at full load (varies by model)) to protect critical equipment during an unexpected power loss. They offer better performance at higher temperatures, supports up to 10 times more discharge cycles, and delivers faster recharge times compared to VRLA batteries. Hot-swappable, user-replaceable batteries may increase the useable life of the UPS by allowing you to easily replace the batteries, if needed, without disrupting power to connected equipment.

Techninė specifikacija

Features

UPS topology Double-conversion (Online)

Output power capacity 1 kVA

Output power 1000 W

Waveform Pure sine

Input operation voltage (min) 115 V

Input operation voltage (max) 280 V

Input frequency 40 - 70 Hz

Output operation voltage (min) 200 V

Output operation voltage (max) 240 V

Efficiency (On-line mode) 93%

Power factor 0.99

Audible alarm(s) Yes

Ports & interfaces

AC outlet types C13 coupler

Power plug C14 coupler

AC outlets quantity 8 AC outlet(s)

USB port Yes

Serial interface Yes

Battery

Typical
backup time
at full load

12 min

Typical
backup time
at half load

26.5 min

Design

Form factor

Tower

Product
colour

Black

Rack
capacity

2U

Display type

LCD

LED
indicators

Yes

Operational conditions

Operating
temperature
(T-T)

0 - 40 °C

Storage
temperature
(T-T)

-20 - 60 °C

Operating
relative
humidity (H-
H)

0 - 95%

Certificates

Compliance
certificates

REACH, RoHS

Certification

UL1778,<SP>4th<SP>Ed.
FCC<SP>Part<SP>15<SP>Class<SP>A
ANSI<SP>C62.41<SP>Cat.<SP>B
ISTA<SP>1A

Packaging content

Cables
included

USB cable

Manual

Yes

Quick
installation
guide

Yes

Sustainability

Sustainability
certificates

ENERGY STAR

Weight & dimensions

Width	430 mm
-------	--------

Depth	446 mm
-------	--------

Height	85 mm
--------	-------

Weight	15 kg
--------	-------

Packaging data

Package width	570 mm
---------------	--------

Package depth	597 mm
---------------	--------

Package height	242 mm
----------------	--------

Package weight	21 kg
----------------	-------

Logistics data

Country of origin	China
-------------------	-------

Other features

Packaging content	GXT5LI UPS, USB Cable, Quick Install Guide (QIG), 4-Post Rack 2U Rail Kit, Tower Base Kit
-------------------	---

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Vertiv

ATSAKINGAS ASMUO ES

Vertiv GmbH

August-Everding-Str 25, 81671 München, DE
[vertiv.com](https://www.vertiv.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt