

APC BX750MI nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 0,75 kVA 410 W 4 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **BX750MI** · EAN: **731304410799** · Prekės kodas: **927044**



110,90 €

Kaina su PVM

Be PVM: **91,65 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 0,75 kVA 410 W
- ✓ Signalų forma: Sinusas
- ✓ 4 AC išvestis(ys / čių)
- ✓ Rūgštinis akumulatorius (VRLA)
- ✓ Kompaktiškos Juoda



Aprašymas

Security through emergency power

An APC Back-UPS has a built-in battery that ensures that all connected equipment, such as a PC and NAS, but also your WIFI internet (router + modem) continues to function if the power goes out. In addition, this APC emergency power supply can also automatically shut down a NAS or PC in time via the USB connection. Useful when the APC ups is almost empty. This prevents downtime, damage to equipment, and loss of data.

Safety and convenience

In addition, this secure APC Back-UPS protects by are surge protected outputs that protect valuable equipment against peak voltage caused by lightning strikes, for example. Thanks to the 1Gb Network Dataline Surge Protection, the UPS also protects your Ethernet data line (internet cable) and the equipment connected to it against "backdoor" peak voltage, all without sacrificing internet speed. It is also extra quiet due to the fanless design.

Battery life

You can easily read the expected battery life in the runtime graph, which you can find between the product images. You can easily see how long the UPS supplies emergency power at a certain load.

Extend the lifespan

The internal battery cartridge (RBC17) can be replaced. This way you can easily and cheaply extend the lifespan of the APC Back-UPS BX750MI.

Warranty extension

The factory warranty of the BX750MI is 2 years and can be upgraded to 5 years with the APC service pack (WBEXTWAR3YR-SP-01A).

Insurance

Despite the high risk of lightning strikes and surges, APC has full confidence in its products and offers this APC Back-UPS:

- Equipment protection policy of 50,000 euros

Save on operational costs

The UPS is equipped with AVR, which extends battery life and maximizes runtime by correcting low and high voltages without discharging the battery. Furthermore, the emergency power supply has 4 battery+surge protected outputs. PowerChute Serial Shutdown software and a USB cable are also included.

Automatic Voltage Regulation (AVR)

Automatically steps up low voltage and steps down high voltage to levels that are suitable for your equipment.

Dataline surge protection

Provides protection of connected equipment from power surges on the data lines.

PowerChute Serial Edition

This software supports numerous operating systems and processors.

USB connection

Use your PC to access additional power protection and management features for your UPS via a USB Port.

Audible alarms

Provides notification of changing utility power and UPS power conditions

LED status display

Quickly understand unit and power status with visual indicators.

Intelligent battery management

Maximizes battery performance, life, and reliability through intelligent, precision charging.

Automatic self-test

Periodic battery self-test ensures early detection of a battery that needs to be replaced.

Battery failure notification

Provides early-warning fault analysis on batteries enabling timely preventive maintenance

Surge only outlets

Protect secondary electronics from surges and spikes without reducing battery power used to run primary electronics during an outage.

Battery and surge protected outlets

Back up and protect your hardware and data during power outages, surges and spikes.

Safety-agency approved

Ensures the product has been tested and approved to work safely with the connected service provider equipment and within the specified environment.

Battery-protected and surge-only outlets

Reserves power capacity and run time for connected equipment that require UPS battery back-up while providing surge only protection for less critical equipment

Techninė specifikacija

Savybės	
UPS topologija	„Line-Interactive“
Išvesties galia (VA)	0,75 kVA
Išvesties galia	410 W
Signalų forma	Sinusas
Išvesties eksploatacinė įtampa (min.)	140 V
Išvesties eksploatacinė įtampa (maks.)	300 V
Įėjimo dažnis	50/60 Hz
Išvesties darbinė įtampa (min.)	230 V
Išvesties darbinė įtampa (maks.)	230 V
Išvesties dažnis	50/60 Hz
Išvesties dažnių reguliavimas	0.5 Hz

Išvesties įtampos reguliavimas	10%
Automatinis įtampos reguliavimas (AVR)	Taip
Viršįtampio energijos įvertinimas	273 J
Reakcijos laikas	6 ms
Įvesties galios koeficientas	0,63
Garso lygis	40 dB
Apsauga nuo viršįtampių	Taip
Garsiniai perspėjimo signalai	Taip
Garsinio pavojaus signalo režimai	Senkančio akumuliatoriaus signalas
Ryšys	
AC išėjimo tipai	C13 šakotuvai
Maitinimo laido kištukas	C14 šakotuvai
Lizų kiekis	4 AC išvestis(ys / čių)
USB prievadas	Taip
USB 2.0 portų kiekis	1
USB prievado tipas	B tipo USB
Ethernet LAN (RJ-45) portų kiekis	2
„SmartSlot“	Ne
„SmartConnect“ prievadas	Ne
Baterija	
Baterijos technologija	Rūgštinis akumuliatorius (VRLA)
Tipiško laikino maitinimo trukmė pilna apkrova	1 min
Tipiško laikino maitinimo trukmė pusei apkrovimo	8,5 min
Baterijos veikimo trukmė (maks.)	2 metai
Baterijos įkrovimo laikas	6 h
Konstrukcija	
Forma	Kompaktiškos
Produkto spalva	Juoda
Kabelio ilgis	1,2 m
LED indikatoriai	Taip
Tarptautinės apsaugos (IP) kodas	IP20
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-15 - 40 °C

Darbo santykinės drėgmės diapazonas	0 - 95%
Darbinis aukštis	0 - 3000 m
Sertifikatai	
Atitikties sertifikatai	RoHS
Sertifikavimas	CB Meet EN62040-1 / CE / IEC-62040-1 / IEC-62040-2
Pakuotės turinys	
Pridėti kabeliai	Įvesties maitinimo laidas
Pridedama valdymo kortelė	Ne
Instrukcija	Taip
Svoris ir matmenys	
Plotis	120 mm
Ilgis	355 mm
Aukštis	160 mm
Svoris	5,4 kg
Pakuotės duomenys	
Pakuotės plotis	197 mm
Pakuotės gylis	430 mm
Pakuotės aukštis	250 mm
Paketo svoris	5,9 kg
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85078000
Matmenys ir svoris	
Matmenys (I × P × A)	43,00cm × 25,00cm × 20,00cm

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas
- › Vaizdo įrašas [youtube.com/watch?v=JoErEwjle3g](https://www.youtube.com/watch?v=JoErEwjle3g)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR

[se.com](https://www.se.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt