

TP-Link Omada AC1750 Wireless MU-MIMO Gigabit Ceiling Mount Access Point

Gamintojas: **TP-LINK** · Modelis: **EAP265 HD** · EAN: **6935364030728** · Prekės kodas: **928411**



198,90 €

Kaina su PVM

Be PVM: **164,38 €**

Sandėlyje





Prekė internetu

Nusenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Fast Dual-Band Wi-Fi: Simultaneous 450 Mbps on 2.4 GHz and 1300 Mbps on 5 GHz totals 1750 Mbps Wi-Fi speeds.†
- ✓ High-Density Connectivity: MU-MIMO, Load Balance, and professional antennas improve capacity in high-density environments to connect more devices simultaneously
- ✓ Integrated into Omada SDN: Zero-Touch Provisioning (ZTP)‡, Centralized Cloud Management, and Intelligent Monitoring
- ✓ Centralized Management: Cloud access and Omada app for ultra convenience and easy management
- ✓ Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.§
- ✓ PoE Support: Support both standard 802.3af/at and Passive PoE (PoE adapter included) for flexible installations
- ✓ Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi/ Voucher, etc.) and abundant wireless security technologies



Aprašymas

Advanced Performance in High-Density Environments

AC1750 Wireless MU-MIMO Gigabit Ceiling Mount Access Point

AC1750 Dual-Band Speed

1300 Mbps on 5 GHz Band + 450 Mbps on 2.4 GHz Band†

High-Density Connectivity

MU-MIMO + Professional Antennas

Centralised Cloud Management

SDN Solutions Integration for a Highly Efficient Network

Seamless Roaming

Supports 802.11k/v for Signal Auto Transition

Software Defined Networking (SDN) with Cloud Access

Omada's Software Defined Networking (SDN) platform integrates network devices, including access points, switches, and gateways, providing 100% centralised cloud management. Omada creates a highly scalable network—all controlled from a single interface. Seamless wireless and wired connections are provided, ideal for use in hospitality, education, retail, offices, and more.

Techninė specifikacija

Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	1300 Mbit/s
Maximum data transfer rate (2.4 GHz)	450 Mbit/s
Maximum data transfer rate (5 GHz)	1300 Mbit/s
Ethernet LAN data rates	10,100,1000 Mbit/s
Frequency band	2.4 - 5 GHz
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at
Number of users	500 user(s)
Automatic channel selection	Yes
Automatic channel scanning	Yes
MIMO	Yes
MIMO type	Multi User MIMO
Wi-Fi Multimedia (WMM)/(WME)	Yes
VLAN support	Yes
Rate limiting	Yes
Wireless isolation	Yes

Band steering	Yes
Quality of Service (QoS) support	Yes
Transmitting power (CE)	20/23 dBm
Transmitting power (FCC)	24 dBm
Security	
Security algorithms	64-bit WEP, 128-bit WEP, 152-bit WEP, HTTPS, SNMP, SNMPv2, SSH, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK
MAC address filtering	Yes
Service Set Identifier (SSID) features	Multiple SSIDs
Number of SSID supported	16
Management features	
Web-based management	Yes
Syslog	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	0
WAN connection	Ethernet (RJ-45)
Power	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Active PoE, Passive PoE
DC voltage range	12 V
Design	
Placement	Ceiling, Wall
Product colour	White
Reset button	Yes
LED indicators	Yes
Antenna	
Antenna type	Internal
Antenna direction type	Omni-directional
Antenna gain level (max)	4 dBi
Performance	
Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Linux
Certificates	
Certification	CE, FCC, RoHS

Weight & dimensions

Width	205.5 mm
Depth	181.5 mm
Height	37.1 mm

Packaging content

Quantity per pack	1 pc(s)
Mounting kit	Yes
Quick start guide	Yes

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)
- > [Vaizdo įrašas 1](#) [objects.icecat.biz/objects/80471059_18005060.mp4](#)
- > [Vaizdo įrašas 2](#) [youtube.com/watch?v=i917RDjFtr4](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE
[tp-link.com](#)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
[info@shopro.lt](#)