

D-Link DAP-E3620OU wireless access point 3600 Mbit/s White Power over Ethernet (PoE)

Gamintojas: **D-LINK** · Modelis: **DAP-E3620OU** · EAN: **790069482298** · Prekės kodas: **928480**



273,90 €

Kaina su PVM

Be PVM: **226,36 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ High-speed BE3600 dual-band Wi-Fi 7 connectivity
- ✓ OFDMA + MU-MIMO boosts multi-user efficiency
- ✓ 2.5GbE uplink eliminates wired bottlenecks
- ✓ Single-cable PoE+ deployment for faster installation
- ✓ Optimized RF design for stable outdoor coverage
- ✓ Enterprise-grade WPA3 security protection
- ✓ Traffic segmentation via SSID-to-VLAN mapping
- ✓ Rugged weather-resistant for harsh environments
- ✓ Centralized management through Nuclias Unity
- ✓ Easy management via Nuclias HW/SW controllers



Aprašymas

Wi-Fi 7 Technology

Dual-band Wi-Fi 7 (802.11be), BE3600 class (2x2 + 2x2), delivering lower latency and higher efficiency for multi-user traffic

Rugged Outdoor Design

IP67-rated weatherproof design for reliable outdoor deployment and built for harsh environments with reduced maintenance

Customizable Captive Portal

Per-SSID captive portal support enables branded guest access, promotions, and flexible login workflow

VLAN per SSID

Each SSID to a dedicated VLAN for traffic segmentation, enabling simple separation of networks through policy-based control

Protection and Mounting

Flexible mounting options combined with durable protection ensure reliable installation and long-term performance

Centralized Management

Centralized management through Nuclias Unity or Nuclias hardware/software controllers (DNH-1000, DNC-5000)

Faster Wireless, Better Business Experiences

- Experience next-generation dual-band Wi-Fi 7 (BE3600 class) built for modern business networks, delivering faster speeds, lower latency, and more reliable connectivity.
- With up to 5 GHz up to 2882 Mbps and 2.4 GHz up to 688 Mbps, businesses gain high-capacity performance for productivity, collaboration, and everyday wireless connectivity.
- Advanced 4K-QAM improves throughput and device capacity, while Multi-Link Operation (MLO) enhances responsiveness and reliability in busy environments.
- Designed for resort garden, school campus, public square and outdoor application,
- it provides stable, scalable wireless performance for staff, guests, and connected
- devices-helping improve productivity, user experience, and operational efficiency.

Outdoor Wi-Fi 7 That Braves the Elements

Engineered for harsh environments, the DAP-E3620OU delivers blazing Wi-Fi 7 (BE3600) speeds inside a fully weatherproof chassis built for year-round reliability. Its IP67-rated enclosure and wide temperature tolerance keep connections stable through pouring rain, scorching heat, and freezing cold. With a 2.5GbE PoE uplink, you can place it anywhere without worrying about power outlets—perfect for campuses, factories, public plazas, and outdoor dining areas.

Easy Installation & High-Speed Deployment

The DAP-E3620OU features a single-cable 2.5GbE and PoE+ connection, delivering both power and high-speed data through one Ethernet cable. This simplifies installation, reduces cabling complexity, and enables more flexible device placement in outdoor environments where power access may be limited.

With high-speed 2.5GbE backhaul support, the wired network can fully support Wi-Fi 7 performance without bottlenecks, ensuring smooth connectivity for bandwidth-intensive applications and wireless deployments.

Simplified Centralized Network Management

- The DAP-E3620OU integrates seamlessly with D-Link Nuclias Unity and Nuclias hardware and software controllers, including the DNH-1000 and DNC-5000, to streamline Wi-Fi management for growing business networks.
- Through an intuitive dashboard, IT teams can quickly provision access points, enforce SSID and VLAN policies, deploy firmware updates, and monitor network health across sites. Centralized visibility and configuration simplify deployment, accelerate troubleshooting, and reduce routine maintenance, making it easy to scale from small installations to enterprise environments with consistent performance and security.

Techninė specifikacija

Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	3600 Mbit/s
Maximum data transfer rate (2.4 GHz)	688 Mbit/s
Maximum data transfer rate (5 GHz)	2882 Mbit/s
Ethernet LAN data rates	1000,2500 Mbit/s
Frequency band	2.4/5 GHz
Networking standards	IEEE 802.11be, IEEE 802.11ax, IEEE 802.3at, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz
MIMO	Yes
MIMO type	Multi User MIMO
Wireless isolation	Yes
Band steering	Yes
Security	
Security algorithms	WPA, WPA2, WPA3, AES, AES-CCMP, WEP, 802.1x RADIUS, SNMP
MAC address filtering	Yes
Service Set Identifier (SSID) features	SSID broadcast, Multiple SSIDs
Remote Authentication Dial-In User Service (RADIUS)	Yes
Management features	
Web-based management	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	0
Power	

Power over Ethernet (PoE)	Yes
Power consumption (max)	17.04 W
Design	
Placement	Pole, Wall
Product colour	White
Reset button	No
LED indicators	Power, Link, Status, WLAN
Antenna	
Antenna type	Internal
Antennas quantity	4
Antenna gain level (max)	6 dBi
Weight & dimensions	
Width	181 mm
Depth	88 mm
Height	304 mm
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	-30 - 55 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 95%
Matmenys ir svoris	
Svoris	1,00kg

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt