

Allied Telesis AT-GS980M/52-50 Managed Gigabit Ethernet (10/100/1000) Grey

Gamintojas: **ALLIED TELESIS** · Modelis: **AT-GS980M/52-50** · EAN: **767035212388** · Prekės kodas: **928775**



2 300,90 €

Kaina su PVM

Be PVM: **1 901,57 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ AlliedWare Plus™ operating system
- ✓ Autonomous Management Framework™ (AMF) edge node
- ✓ Active Fiber Monitoring
- ✓ Ethernet Protection Switched Ring (EPSR™)
- ✓ Static Routing and RIP
- ✓ DHCP snooping
- ✓ IEEE 802.1x/MAC/Web authentication support
- ✓ Loop Protection
- ✓ Eco-friendly
- ✓ Web-based Graphical User Interface (GUI)

Aprašymas

The Allied Telesis CentreCOM GS980M/52 managed switch features 48 x 10/100/1000T copper ports and 4 x 100/1000X SFP uplinks. A comprehensive feature-set, and built in security, make it ideal for high-density user and device connectivity at the network edge.

Overview

Allied Telesis GS980M Series switches provide an excellent access solution for today's networks, supporting Gigabit to the desktop for maximum performance. Deploying the GS980M as an AMF edge node when an AMF Master switch is available in the network, helps reduce network running costs by automating and simplifying many day-to-day administration tasks. 48 Gigabit ports and 4 SFP uplinks enable high-density and secure connectivity at the network edge, and the PoE+ model can supply up to 30 Watts to powered end-points.

Techninė specifikacija

Management features

Switch type	Managed
Quality of Service (QoS) support	Yes
Web-based management	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes
MIB support	SNMP MIB
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	4
Installed SFP+ modules quantity	0
Fiber optic connector	SFP
Network	
Networking standards	IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	Yes
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Port mirroring	Yes
Full duplex	Yes
IP routing	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Spanning tree protocol	Yes
VLAN support	Yes
Virtual LAN features	Port-based VLAN, Private VLAN, Protocol-based VLAN, Tagged VLAN, Voice VLAN
Number of VLANs	4094
Optical fiber	
Fiber ethernet cabling technology	100BASE-X, 1000BASE-X
Switching optical modules type	100 Gigabit Ethernet
Data transmission	
MAC address table	16000 entries
Switching capacity	104 Gbit/s
Forwarding rate	77.4 Mpps
Latency (10-100 Mbps)	5.5 µs

Latency (1 Gbps)	2.6 µs
Static route	Yes
Jumbo frames support	Yes
Jumbo frames	10000
Packet buffer memory	1.5 MB
Security	
DHCP features	DHCP client, DHCP snooping
Access Control List (ACL)	Yes
IGMP snooping	Yes
Security algorithms	3DES, AES, MD5, PEAP, RSA, SHA-1, SHA-2, SSH, SSH-2, SSL/TLS, TTLS
MAC address filtering	Yes
SSH/SSL support	Yes
Loop protection	Yes
BPDU filtering/protection	Yes
Authentication	MAC-based authentication, Port-based authentication, Web-based authentication
Password protection	Yes
Authentication type	AAA, IEEE 802.1x, Network Access Control (NAC), RADIUS
Multicast features	
Multicast support	Yes
Protocols	
Management protocols	SNMP
Routing protocols	RIP, RIP-2
Design	
Rack mounting	Yes
Product colour	Grey
LED indicators	Yes
Wall mountable	Yes
Electromagnetic compatibility	EN55024
Performance	
Memory type	DDR-SDRAM
Internal memory	256 MB
Flash memory	64 MB
Noise level	39 dB
Power	

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	1.0 A
Power consumption (typical)	47 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-25 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 4000 m
Heat dissipation	160 BTU/h
Weight & dimensions	
Width	441 mm
Depth	323 mm
Height	44 mm
Weight	4.5 kg
Packaging data	
Package width	575 mm
Package depth	445 mm
Package height	150 mm
Package weight	6.4 kg
Certificates	
Certification	UL60950-1, CAN/CSA-C22.2 No. 60950-1-03, EN60950-1, EN60825-1, AS/NZS 60950.1 UL, cUL, UL-EU RoHS
Logistics data	
Harmonized System (HS) code	8517.62.0050

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas](#) youtube.com/watch?v=3wu5AR2grTI

Gamintojo ir saugos informacija

GAMINTOJAS

Allied Telesis

ATSAKINGAS ASMUO ES

Allied Telesis International B.V.Karl-Hammerschmidt-Straße 34, 85609 Aschheim-
Dornach, DEalliedtelesis.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt