

APC BE650G2-IT uninterruptible power supply (UPS) Standby (Offline) 0.65 kVA 400 W

Gamintojas: **APC** · Modelis: **BE650G2-IT** · EAN: **731304347224** · Prekės kodas: **928795**

194,89 €

Kaina su PVM

Be PVM: **161,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Standby (Offline)
- ✓ 0.65 kVA 400 W
- ✓ Waveform: Sine
- ✓ Compact Black

Aprašymas

Adjustable voltage sensitivity

Provides the ability to adapt the UPS for optimal performance in specific power environments or generator applications.

Audible alarms

Provides notification of changing utility power and UPS power conditions

Automatic self-test

Periodic battery self-test ensures early detection of a battery that needs to be replaced.

Battery failure notification

Provides early-warning fault analysis on batteries enabling timely preventive maintenance

Building Wiring Fault Indicator

This LED informs users of potentially dangerous wiring problems in the wall circuit.

Cold-start capable

Provides temporary battery power when the utility power is out.

Dataline surge protection

Provides protection of connected equipment from power surges on the data lines.

Disconnected battery notification

Warns when a battery is not available to provide backup power.

Hot-swappable batteries

Ensures clean, uninterrupted power to protected equipment while batteries are being replaced

Safety-agency approved

Ensures the product has been tested and approved to work safely with the connected service provider equipment and within the specified environment.

Simple battery replacement

Increases UPS availability by allowing quick, easy battery replacement.

USB connection

Use your PC to access additional power protection and management features for your UPS via a USB Port.

User-replaceable batteries

Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR)

Techninė specifikacija

Features	
UPS topology	Standby (Offline)
Output power capacity	0.65 kVA
Output power	400 W
Waveform	Sine
Input frequency	47/63 Hz
Output operation voltage (min)	220 V
Output frequency	47/63 Hz
Maximum current	6 A
Surge energy rating	310 J
Efficiency	80%

Noise level	45 dB
Surge protection	Yes
Surge protection features	Digital Subscriber Line (DSL)
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	Type F
USB port	Yes
Ethernet LAN (RJ-45) ports	1
Cabling technology	10/100Base-T
Battery	
Battery life (max)	5 year(s)
Battery recharge time	16 h
Hot-swap battery	Yes
Automatic battery test	Yes
Cold start	Yes
Design	
Form factor	Compact
Product colour	Black
Cable length	1.83 m
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 95%
Non-operating altitude	0 - 4500 m
Certificates	
Compliance certificates	RoHS
Certification	CE, EAC
Packaging content	
Manual	Yes
Weight & dimensions	
Width	130 mm

Depth	365 mm
Height	120 mm
Weight	4 kg
Packaging data	
Package width	186 mm
Package depth	441 mm
Package height	190 mm
Package weight	4.5 kg
Logistics data	
Harmonized System (HS) code	85078000

Gamintojo ir saugos informacija

GAMINTOJAS
Schneider Electric SE
rue Joseph Monier 35, 92500 Reuil Malmaison, FR
[se.com](https://www.se.com)

PLATINTOJAS
MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt