Zyxel GS1900-10HP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Gamintojas: **ZYXEL** · Modelis: **GS1900-10HP-EU0101F** · EAN: **4718937587810** · Prekės kodas: **929125**



192,90 €

Kaina su PVM

Be PVM: **159,42 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2 Web-based management SNMP, RMON, ICMP, Syslog
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 8 Console port: RJ-45
- ✓ 10BASE-T, 100BASE-T, 1000BASE-T
- ✓ MAC address table: 8000 entries Switching capacity: 20 Gbit/s
- ✓ 1U
- ✓ Power over Ethernet (PoE)











Aprašymas

Simple, Fast and Smart Managed Switches for Small Business Connectivity

The ZyXEL GS1900 Series of 8/10/16/24/48-port GbE Smart Managed Switch with Gigabit speed and essential managing functions bring your business network more flexibility and connectivity. The 1900 Series consists of nine (9) models—the GS1900-8, GS1900-8HP, GS1900-10HP, GS1900-16, GS1900-24E, GS1900-24, GS1900-24HP, GS1900-48 and GS1900-48HP. Providing GbE switches with power-saving functions, fanless design and full IPv6 support ensure your network to be ready for future expansions. In addition, the PoE models GS1900-8HP/10HP/24HP/48HP Gigabit switch complies with the IEEE 802.3at Power over Ethernet (PoE) Plus standard. The complete GS1900 Series has been designed with useful features and advanced performances that empower your networks with speed and security as well as silent operation in your office environments.

Versatility and flexibility for different needs

The complete ZyXEL GS1900 Series has an essential portfolio of 8/10/16/24/48-port compact desktop and rackmount size with GbE connectivity. All models support multiple deployment methods to fulfill the needs for small offices and meeting room environments such as wall-, under table- or desktop-mounting and rackmount options*1. It’s now quick and effortless to enjoy the high-speed business network applications without a hitch. Additionally, the GS1900-10HP/24/24HP/48/48HP is equipped with 2 extra SFP slots to provide 100M and GbE speeds for long-distance deployments.

The GS1900-8HP/10HP/24HP/48HP features IEEE 802.3at PoE Plus with up to 30 W powers per port to flexibly extend network deployment, especially for high-power devices such as Wi-Fi APs, IP cams and IP phones. The 802.3at PoE Plus capability makes the switch ideal for connecting numerous powered devices to form a flawless business network.

ZyXEL ONE Network experience

Aiming for relieving our customers from repetitive operations of deploying andmanaging a network, ZyXEL ONE Network is designed to simplify the configuration, management, and troubleshooting, allowing our customers to focus on the business priorities. ZyXEL ONE Network presents an easy-to-use tool, ZyXEL ONE Network Utility (ZON Utility), to realize speed network setup. ZyXEL Smart Connect** allows ZyXEL networking equipment to be aware and recognize each other and further facilitating the network maintenance via one-click remote functions such as factory reset or power cycling. ZyXEL ONE Network redefines the network integration across multiple networking products from switch to Wi-Fi AP and to Gateway.

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
System event log	Yes
MIB support	RFC 1213, RFC 2819, RFC 1215, RFC 1493
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP module slots quantity	2
Console port	RJ-45

Network	
Networking standards	IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Data transmission	
MAC address table	8000 entries
Switching capacity	20 Gbit/s
Throughput	14.88 Mpps
Jumbo frames	9000
Security	
IGMP snooping	Yes
Security algorithms	802.1x RADIUS, SSL/TLS
Protocols	
Management protocols	SNMP, RMON, ICMP, Syslog
Design	
Rack mounting	No
Form factor	1U
Product colour	Black
LED indicators	Yes
Wall mountable	Yes
Safety	LVD EN60950-1, BSMI CNS14336-1, CB IEC60950-1
Performance	
Buffer size	525 KB
Mean time between failures (MTBF)	801.113 h
Power	
Input current	1.7 A
Input voltage	54 V
Power consumption (typical)	96.2 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Total Power over Ethernet (PoE) budget	77 W
Operational conditions	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%
Heat dissipation	65.472 BTU/h
Weight & dimensions	
Width	250 mm
Depth	104 mm
Height	27 mm
Weight	720 g
Packaging data	
Package width	302 mm
Package depth	227 mm
Package height	64 mm
Package weight	1.53 kg
Certificates	
Certification	CE, FCC, C-Tick, BSMI CNS13438
Logistics data	
Harmonized System (HS) code	85176990

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

Zyxel Networks Corporation
Industry East RD. IX, Hsinchu Science Park 2,
30076 Hsinchu, TW
zyxel.com

ATSAKINGAS ASMUO ES

Zyxel Networks A/S
Adenauerstraße 20/A3, 52146 Würselen, DE
zyxel.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt