

Vertiv Liebert GXT5 uninterruptible power supply (UPS) Double-conversion (Online) 1 kVA 1000 W 8 AC outlet(s)

Gamintojas: **VERTIV** · Modelis: **GXT5-1000IRT2UXLE** · EAN: **767041027174** · Prekės kodas: **929133**



1 603,90 €

Kaina su PVM

Be PVM: **1 325,54 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Reliable, easy-to-manage power protection and battery backup with 1000VA (1000W) capacity
- ✓ Highest power factor available on standard input connections
- ✓ Four individual programmable output receptacle for device control and management for optimum battery usage
- ✓ Its user-friendly interface includes color graphic display with gravity sensing feature
- ✓ 2019 ENERGY STAR 2.0 certified and has higher operating efficiency in standard and eco-mode



Aprašymas

The Vertiv Liebert GXT5 UPS 1000VA/1000W, is a 2U UPS solution for ensuring the health and availability of IT infrastructure. With online, double conversion technology, the UPS protects critical equipment against outages and every type of power disturbance without drawing on battery power,

extending battery life and minimizing replacements. This can support a wide range of power environment including 200/208/220/230/240V user configurable AC power and has scalable runtime options with matching external battery cabinets to offer extra time during an outage to support critical equipment and activity. It includes hot-swappable batteries and all hardware for installing it as a tower or in an equipment rack. This single-phase UPS is ENERGY STAR 2.0 certified and offers leading normal mode power efficiency and Eco-mode for ultimate efficiency levels. It has a two-year factory warranty. It offers premium power protection for critical infrastructure in centralized and edge applications.

Techninė specifikacija

Features	
UPS topology	Double-conversion (Online)
Output power capacity	1 kVA
Output power	1000 W
Waveform	Pure sine
Input operation voltage (min)	115 V
Input operation voltage (max)	288 V
Input frequency	40 - 70 Hz
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output voltage regulation	3%
Number of input phases	1
Number of output phases	1
Efficiency	95%
Efficiency (On-line mode)	95%
Efficiency (ECO mode)	98%
Input power factor	0.99
Emergency Power Off (EPO)	Yes
Noise level	58 dB
Power protection features	Overload
Audible alarm(s)	Yes
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes
Serial interface type	RS-232, RS-485
Serial ports quantity	1
Emergency Power Off (EPO) connector	Yes
Battery	

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	9 VAh
Battery voltage	12 V
Typical backup time at full load	6 min
Typical backup time at half load	15 min
Battery recharge time	3 h
Hot-swap battery	Yes

Design

Form factor	Rackmount/Tower
Product colour	Black
Display type	LCD
International Protection (IP) code	IP20

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 40 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m

Certificates

Compliance certificates	RoHS
Certification	IEC/EN/AS 62040-2 2nd Ed (Cat 2 - 6); FCC 15 A CISPR22 A(RFI)

Safety regulation & standards

Safety	IEC62040-1:2008, GS; UL1778, c-UL
--------	-----------------------------------

Sustainability

Sustainability certificates	ENERGY STAR
-----------------------------	-------------

Weight & dimensions

Width	430 mm
Depth	630 mm
Height	217 mm
Weight	21 kg

Packaging data

Package width	517 mm
Package depth	262 mm
Package height	617 mm

Package weight	21.4 kg
----------------	---------

Logistics data

Harmonized System (HS) code	85078000
-----------------------------	----------

Other features

Battery type	VRLA
--------------	------

Output connections	IEC320 C13
--------------------	------------

Input connection type	C14
-----------------------	-----

Nominal output voltage	230 V
------------------------	-------

Nominal input voltage	230 V
-----------------------	-------

Overload protection	Yes
---------------------	-----

Bypass	Yes
--------	-----

Non-operating relative humidity (non-condensing)	0 - 95%
--	---------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Saugos duomenų lapas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Vertiv

ATSAKINGAS ASMUO ES

Vertiv GmbH

August-Everding-Str 25, 81671 München, DE
[vertiv.com](https://www.vertiv.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- › [Saugos duomenų lapas](#)