

TP-Link AX1800 Whole Home Mesh WiFi System

Gamintojas: **TP-LINK** · Modelis: **HX220(1-PACK)** · EAN: **4897098684665** · Prekės kodas: **929195**



95,90 €

Kaina su PVM

Be PVM: **79,26 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dual Band WiFi 6: Speeds up to 1800 Mbps—1201 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.†
- ✓ Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger WiFi signal
- ✓ One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.*
- ✓ Enhanced Security: WPA3 encryption, Multi-SSID, and Parental Controls provide personalized and safer online experience.**
- ✓ EasyMesh Compatible: Provides whole home WiFi coverage with standard mesh technology
- ✓ Easy Setup and Use: Set up your mesh WiFi in minutes with powerful Aginet app
- ✓ Remote Management: TAUC cloud management, TR-181, TR-111, and TR-143 are supported



Aprašymas

Fast. Stable. Everywhere.

AX1800 Whole Home Mesh WiFi System

Advanced Mesh Powered by WiFi 6

Armed with WiFi 6 technology, HX220 provides faster speeds up to 1.8 Gbps for buffer-free 8K/4K streaming and gaming even with all smart home, mobile, and other electronic devices connected.

Extensive WiFi Coverage

Beamforming technology and high-performance antennas combine to adapt WiFi coverage to perfectly fit home and concentrate signal strength towards every device.

Whole Home Coverage

Empowered by EasyMesh technology, HX220 provides a strong WiFi signal in every corner of your home. Wireless connections and optional Ethernet backhaul work together to link each unit, providing even faster network speeds and truly seamless coverage. Want more coverage? Simply add another HX220 whenever you want.

Seamless Roaming with One WiFi Name

All units work together to form one unified network. Your mobile device will automatically connect to the fastest unit when you move through your home, creating a truly seamless WiFi experience.

Stable Connections, No More Buffering

Enhanced by WiFi 6, featuring with OFDMA and MU-MIMO technology**, HX220 allows you to connect over 250+ devices. Enjoy a more efficient network that loads faster without dragging down performance.

2-in-1 Router and Access Point

Flexible and multifunctional, HX220 includes a variety of features to serve as a router or access point. Choose the mode for actual network demands and experience maximum wireless flexibility.

More Ethernet Ports for More Options

Each unit has 3 Gigabit Ethernet ports for fast and reliable wired connections. Supports wired Ethernet Backhaul for more stable speeds.

Easy to Set Up and Use

You can set up your device in minutes, whether you prefer the powerful Aginet app or the intuitive web interface. The Aginet app allows you to manage network settings from your smart phone or tablet.

Support TR-069 Remote Management

ISPs can remotely configure and manage the devices via ACS (Auto-Configuration Server). High-level operations are also supported thanks to compatibility with TR-181, TR-111, and TR-143 protocols.

Aginet Solution: End-to-End Management System for ISPs

The Aginet solution offers ISPs powerful and flexible platforms to manage multiple devices for connected homes, such as dynamic service provisioning, zero-touch firmware upgrading, and remote troubleshooting and mesh WiFi diagnostics.

Techninė specifikacija

Design

Product colour	White
Product type	Mesh router
LED indicators	Yes
Reset button	Yes
Wireless LAN features	
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard	Wi-Fi 6 (802.11ax)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
WLAN data transfer rate (first band)	574 Mbit/s
WLAN data transfer rate (second band)	1201 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g
Security algorithms	WMM, WPA, WPA2, WPA3
Features	
Quality of Service (QoS) support	Yes
Port forwarding	Yes
Firewall security	SPI Firewall
Transmitting power (CE)	20 - 23 dBm
Transmitting power (FCC)	30 dBm
Mobile operating systems supported	Android 4.4, iOS 9.0
Parental control	Yes
SSID Broadcast	Yes
Supported WAN type	Dynamic IP, Static IP, PPPoE
Ports & interfaces	
Ethernet LAN (RJ-45) ports	3
Ethernet WAN	Yes
Power	
AC input voltage	12 V
AC adapter input current	1 A
Certificates	
Compliance certificates	CE
Certification	CE, FCC
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 60 °C

Operating relative humidity (H-H)	10 - 90%
-----------------------------------	----------

Storage relative humidity (H-H)	5 - 90%
---------------------------------	---------

Weight & dimensions

Width	100 mm
-------	--------

Depth	100 mm
-------	--------

Height	89.5 mm
--------	---------

Packaging content

Number of products included	1 pc(s)
-----------------------------	---------

AC adapter included	Yes
---------------------	-----

Number of units included	1 pc(s)
--------------------------	---------

Ethernet cable	Yes
----------------	-----

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Greitos pradžios vadovas](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE[tp-link.com](https://www.tp-link.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt