

Conceptronic ZEUS52ES1K 1000VA 900W Online Tower UPS, Schuko

Gamintojas: **CONCEPTRONIC** · Modelis: **ZEUS52ES1K** · EAN: **4015867238172** · Prekės kodas: **929606**



467,89 €

Kaina su PVM

Be PVM: **386,69 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Output Power Factor 0.9
- ✓ ECO Mode for Energy-Saving
- ✓ Generator Compatible
- ✓ Provides HID compatible USB connection
- ✓ Emergency Power Off (EPO) Port
- ✓ THDi≤5%



Aprašymas

Introducing the Conceptronic Online Tower UPS—the premier power backup solution for your home or office. Featuring an output power factor of 0.9, this UPS delivers superior efficiency and performance. Its ECO Mode enhances energy savings, while compatibility with generators ensures uninterrupted power during extended outages.

The Conceptronic Online Tower UPS comes with HID USB communication for seamless device connectivity and enhanced control and monitoring. For added safety during emergencies, it includes an Emergency Power Off (EPO) port for swift shutdowns in critical situations.

With its sleek, modern tower design, the Conceptronic Online Tower UPS integrates effortlessly into any environment, providing reliable power backup when you need it most.

Techninė specifikacija

Features	
UPS topology	Double-conversion (Online)
Output power capacity	1 kVA
Output power	900 W
Waveform	Sine
Input operation voltage (min)	220 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Maximum current	10 A
Efficiency (ECO mode)	95%
Input power factor	0.99
Output power factor	0.9
Crest factor	3:1
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Input current Total Harmonic Distortion (THD)	5%
Power protection features	Overload, Short circuit
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	Type F
AC outlets quantity	3 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
RS-232 ports	1
Emergency Power Off (EPO) connector	Yes
Battery	
Battery capacity	9 Ah
Battery voltage	12 V
Battery recharge time	4 h

Cold start	Yes
Battery capacity	108 Wh
Design	
Form factor	Tower
Product colour	Black
Cooling type	Active
Built-in fan	Yes
Display type	LCD
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Cables included	Input power cable, RS-232, USB cable
Quick installation guide	Yes
Weight & dimensions	
Width	140 mm
Depth	327 mm
Height	191 mm
Weight	10.1 kg
Packaging data	
Package type	Box
Logistics data	
Pallet gross length	100 cm
Pallet gross width	120 cm
Pallet gross height	126 cm
Harmonized System (HS) code	8504406090
Master (outer) case width	217 mm
Master (outer) case length	440 mm
Master (outer) case height	277 mm
Master (outer) case gross weight	10.5 kg
Products per master (outer) case	1 pc(s)
Country of origin	China

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Digital Data Communications GmbH

Im Defdahl 10 F, D-44141 Dortmund, DE

digital-data.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

- › [Atitikties deklaracija](#)