

LevelOne OSW-1061 network switch Managed L2 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) Black

Gamintojas: **LEVELONE** · Modelis: **OSW-1061** · EAN: **4015867236444** · Prekės kodas: **929787**



589,90 €

Kaina su PVM

Be PVM: **487,52 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8- Port 10/100/1000 Ethernet PoE + Gigabit SFP+ slots x 2
- ✓ 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- ✓ IEEE 802.3af/at PoE compliant to simplify deployment and installation
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ Web-based Management
- ✓ 6KV surge protection, 6KV contact / 8KV air ESD protection
- ✓ Weatherproof IP55-rated Box housing
- ✓ PoE Budget Max 185 W
- ✓ Included 4 x SC fiber tray



Aprašymas

The OSW-1061 is a L2 Managed PoE Industrial Switch with 8 ports of Gigabit RJ45 PoE and 2 ports of Gigabit SFP. This switch is offering full suite of L2 management features, better PoE functionality with 185W PoE power budget and usability.

The OSW-1061 switch is designed to withstand outdoor or harsh environments, and can be mounted on a wall, pole, or cabinet to fit your space and layout.

Techninė specifikacija

Management features		
Switch type		Managed
Switch layer		L2
Quality of Service (QoS) support		Yes
Web-based management		Yes
Traffic classification		Yes
System event log		Yes
Ports & interfaces		
Basic switching RJ-45 Ethernet ports quantity		8
Basic switching RJ-45 Ethernet ports type		2.5G Ethernet (100/1000/2500)
Installed SFP modules quantity		0
2.5G Ethernet (copper) ports quantity		8
SFP+ module slots quantity		2
Power connector		DC-in jack
Network		
Networking standards		IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1ad, IEEE 802.1ag, IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3ah, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support		No
Copper ethernet cabling technology		10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-X
Port mirroring		Yes
Full duplex		Yes
Policy-based routing		Yes
Half duplex		Yes
Flow control support		Yes
Broadcast storm control		Yes
Auto MDI/MDI-X		Yes
Spanning tree protocol		Yes
Ethernet LAN data rates		1000 Mbit/s
Auto-negotiation		Yes
VLAN support		Yes
Data transmission		
MAC address table		8000 entries
Switching capacity		20 Gbit/s

Forwarding rate	14.88 Mpps
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	12 MB
Security	
DHCP features	DHCP snooping
MAC address filtering	Yes
BPDU filtering/protection	Yes
Password protection	Yes
Multicast features	
Multicast support	Yes
Protocols	
IP Source Guard (IPSG)	Yes
Design	
Rack mounting	No
Stackable	No
Product colour	Black
LED indicators	Link, Power
International Protection (IP) code	IP55
Performance	
Internal memory	1 MB
Flash memory	120 MB
Fanless	No
Mean time between failures (MTBF)	4000000 h
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	200 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Total Power over Ethernet (PoE) budget	185 W

Operational conditions

Operating temperature (T-T)	-20 - 65 °C
Storage temperature (T-T)	-40 - 75 °C
Operating relative humidity (H-H)	0 - 90%

Weight & dimensions

Width	280 mm
Depth	200 mm
Height	250 mm
Weight	8 kg

Packaging content

Quick start guide	Yes
Manual	Yes

Packaging data

Package type	Box
--------------	-----

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC)
-------------------------	---

Matmenys ir svoris

Svoris	7,13kg
--------	--------

Dokumentai ir vaizdo įrašai[› Gaminio lankstinukas](#)**Gamintojo ir saugos informacija**

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbHIm Defdahl 10 F, 44141 Dortmund, DE
level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt