

Allied Telesis AT-2914SX/LC-001 network card Internal Fiber 1000 Mbit/s

Gamintojas: **ALLIED TELESIS** · Modelis: **AT-2914SX/LC-901** · EAN: **767035210629** · Prekės kodas: **931020**



320,90 €

Kaina su PVM

Be PVM: **265,21 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Jumbo frames up to 9.6KB
- ✓ Smart Load Balancing (SLB) and failover
- ✓ Link aggregation (IEEE 802.3ad)
- ✓ Generic trunking (FEC/GEC) / IEEE 802.3ad-draft static
- ✓ UEFI network boot
- ✓ Low-profile and standard height brackets included

Aprašymas

High reliability

The Allied Telesis 2914 Series Gigabit interface includes a comprehensive Microsoft Windows utility which performs detailed tests, diagnostics and analysis.

Advanced manageability

Priority queuing allows users to set up the network based on their individual

needs. A comprehensive diagnostics and configuration software suite provides system administrators and engineers with a powerful tool to analyze the adapter card and check specific data.

Wake-on-LAN (WoL)

WoL allows users to remotely power on or wake up an otherwise unavailable computer from a remote location. WoL is a versatile technique that allows computers to be deactivated when not required. When WoL is enabled, the computer maintains power to the network adapter, and continues to process network packets. When a valid WoL packet is detected the network adapter powers on or resumes the computer. Effective use of WoL

allows system administrators or users to turn computers on remotely, for patch management remote support and remote access. WoL has the potential to greatly increase the use of low-power modes and energy-saving techniques.

Techninė specifikacija

Ports & interfaces	
Connectivity technology	Wired
Host interface	PCI Express
Interface	Fiber
Fiber ports quantity	2
Fiber optic connector	LC
Network	
Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.2, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3x, IEEE 802.3z
Fiber ethernet cabling technology	1000BASE-X
Security algorithms	SNMP
Wake-on-LAN ready	Yes
Jumbo frames support	Yes
Auto-negotiation	Yes
Jumbo frames	9.6
Quality of Service (QoS) support	Yes
Load balancing system	Yes
Design	
Internal	Yes
Product colour	Green, Metallic
Certification	UL, FCC/EN55022 Class A, TUV, EN55024, CE, C-TICK, VCCI
Power	
Power consumption (typical)	1.5 W
System requirements	
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows Vista
Server operating systems supported	Windows Server 2008 R2, Windows Server 2008 R2 x64, Windows Server 2012 R2 x64, Windows Server 2012 x64
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-25 - 70 °C

Operating relative humidity (H-H) -25 - 70%

Weight & dimensions

Width 88 mm

Height 69 mm

Weight 68 g

Technical details

Compliance certificates RoHS

Other features

Flow control support Yes

Matmenys ir svoris

Matmenys (I × P × A) 23,00cm × 18,00cm × 2,00cm

Svoris 0,10kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Allied Telesis

ATSAKINGAS ASMUO ES

Allied Telesis International B.V.

Karl-Hammerschmidt-Straße 34, 85609 Aschheim-
Dornach, DE

alliedtelesis.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt