

Lenovo 01CV830 network card Internal Fiber 16000 Mbit/s

Gamintojas: **LENOVO** · Modelis: **01CV830** · EAN: **889488417339** · Prekės kodas: **931911**



365,90 €

Kaina su PVM

Be PVM: **302,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ PCIe 3.0 Fiber
- ✓ 16000 Mbit/s
- ✓ Internal Component for: Server

Aprašymas

The Emulex 16 Gb (Generation 6) Fibre Channel (FC) host bus adapters (HBAs) are an ideal solution for all Lenovo System x servers requiring high-speed data transfer in storage connectivity for virtualized environments, data backup, and mission-critical applications. They are designed to meet the needs of modern networked storage systems that utilize high performance and low latency solid state storage drives for caching and persistent storage as well as hard disk drive arrays.

The Emulex 16 Gb Gen 6 FC HBAs feature ExpressLane™, which prioritizes mission-critical traffic in congested networks ensuring maximum application performance on flash storage arrays. They also seamlessly support Brocade ClearLink™ diagnostics through Emulex OneCommand® Manager, ensuring the reliability and management of storage network when connected to Brocade Gen 5 FC SAN fabrics.

Techninė specifikacija

Ports & interfaces	
Connectivity technology	Wired
Host interface	PCIe
Interface	Fiber
Fiber ports quantity	1
Fiber optic connector	FC, SFP+

PCI version	3
Network	
Maximum data transfer rate	16000 Mbit/s
Full duplex	Yes
Web-based management	Yes
Maximum operating distance	150 m
Design	
Internal	Yes
Component for	Server
Product colour	Black, Green, Silver
Rack mounting	Yes
Rack capacity	2U
Hot-swap	Yes
Hot-Plug support	Yes
LED indicators	Yes
Mean time between failures (MTBF)	10000000 h
Certification	AS/NZS CISPR22:2009+A1, Class A Australian EMC Framework (RCM) cUR recognized to CSA 22.2, No. 60950-1-07 EN55022:2010, Class A EN55024:2010 EN55032:2012 EU (CE Mark) FCC Rules, Part 15, Class A Industry Canada, ICES-003, Class A Japan VCCI, Class A Korea MSIP, Class A RoHS Compliant (Directive 2011/65/EU) TUV certified to EN60950-1+A11+A1+A12+A2 Taiwan BSMI, Class A UL recognized to UL60950-1 2nd Edition
Compatible products	System x3500 M5 Type 5464 System x3550 M5 Type 5463 System x3550 M5 Type 8869 System x3650 M5 Type 5462 System x3650 M5 Type 8871 System x3750 M4 Type 8753 System x3850 X6 Type 6241 (E7 v2, E7 v3, and E7 v4) System x3950 X6 Type 6241 (E7 v2, E7 v3, and E7 v4) NeXtScale nx360 M5 Type 5465 (E5-2600 v3 and E5-2600 v4)
System requirements	
Linux operating systems supported	RedHat EL Linux 6.0, RedHat EL Linux 7.0, SuSE Linux 11, SuSE Linux 12.0
Other operating systems supported	VMware vSphere ESXi
Server operating systems supported	Windows Server 2012, Windows Server 2012 R2
Operational conditions	
Operating temperature (T-T)	0 - 55 °C
Storage temperature (T-T)	-20 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Weight & dimensions	
Depth	168 mm

Height	69 mm
--------	-------

Packaging data

Low-profile bracket	Yes
Quantity per pack	1 pc(s)
Package type	Box

Packaging content

Mounting brackets included	Yes
----------------------------	-----

Technical details

Compliance certificates	RoHS
-------------------------	------

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------

Other features

PCI-SIG* SR-IOV Capable	Yes
-------------------------	-----

Dokumentai ir vaizdo įrašai

- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas](#) youtube.com/watch?v=AGGhW_kl4BM

Gamintojo ir saugos informacija

GAMINTOJAS

Lenovo Group Limited

Courtyard Xibeiwang East Road Building 2, No.10,
100094 Beijing, CN
lenovo.com

ATSAKINGAS ASMUO ES

Lenovo France SAS

Rue des Deux Gares 20, 92500 Rueil-Malmaison,
FR
lenovo.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt