

TP-Link TL-WA3001 wireless access point 2402 Mbit/s Black Power over Ethernet (PoE)

Gamintojas: **TP-LINK** · Modelis: **TL-WA3001** · EAN: **4897098688021** · Prekės kodas: **935064**



138,90 €

Kaina su PVM

Be PVM: **114,79 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Gigabit WiFi 6 Speed for 4K Streaming – 3000 Mbps Dual Band WiFi for faster browsing, streaming and downloading, all at the same time
- ✓ Flexible Deployment – Supports Passive PoE to carry electrical power and data simultaneously
- ✓ Multiple Modes – Supports Access Point, Range Extender, Multi-SSID, and Client modes to meet any network needs
- ✓ Boosted Coverage – Four fixed antennas equipped with Beamforming technology extend and concentrate the Wi-Fi signals
- ✓ Captive Portal – Offers a designed portal page for heightened security and marketing



Aprašymas

The Next Generation of Wi-Fi is Upon Us

Wi-Fi 6 (802.11ax) could turn out to be the most significant advancement in Wi-Fi development, delivering a huge boost in speed and total capacity. Mainstream adoption of Wi-Fi 6 is inching ever closer with more and more AX clients available. It's the right time to upgrade your router to the newest generation of Wi-Fi!

Lightning-Fast AX3000 Dual Band Wi-Fi

Upgrade your home or office network with the latest-generation of dual band 802.11ax access point, which offers combined speeds of up to 3000Mbps and is perfectly suited to serve multiple devices at the same time. The 5GHz band is ideal for Ultra-HD streaming video and online gaming, while the 2.4GHz band is there for all of your everyday Internet needs, like sending email and browsing the Internet.

Gigabit-Class Wired Performance

The gigabit Ethernet port makes full use of gigabit-class bandwidth provided by a local ISP to ensure reliable network connections. It also provides an ultra-fast connection for wired devices such as PCs, IPTVs, and game consoles, etc.

Boosted Wi-Fi Coverage

Four external antennas equipped with Beamforming technology concentrate Wi-Fi signals towards your devices to extend reliable Wi-Fi to every corner of your home or office—even over long distances.

Deploy Anywhere with Just One Cable

Power over Ethernet (PoE) allows your Ethernet cable to carry electrical power and data simultaneously, making deployment effortless and flexible. An elegant appearance and simple mounting design make it easy to attach the Access Point to any wall or desktop, blending in perfectly with most interior decoration.

Captive Portal Marketing

Captive Portal provides a secure guest network and offers unique marketing opportunities, especially for small businesses like cafes or salons. Utilize a flexibly designed portal page—requiring customers to view an advertisement or accept a set of terms for internet access—to improve brand awareness or deliver marketing messages.

Multi-Mode 4 in 1

Multiple operation modes are supported to give you full flexibility to tailor the Access Point to fit your network's needs.

Techninė specifikacija

Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	2402 Mbit/s
Maximum data transfer rate (2.4 GHz)	574 Mbit/s
Maximum data transfer rate (5 GHz)	2402 Mbit/s
Frequency band	2.4 - 5 GHz
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Wi-Fi Multimedia (WMM)/(WME)	Yes
Quality of Service (QoS) support	Yes

Security

Security algorithms	SNMP, WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3
Service Set Identifier (SSID) features	Multiple SSIDs

Protocols

DHCP server	Yes
DHCP client	Yes
Supported protocols	IPv4, IPv6

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes

Power

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
DC voltage range	48 V
Input current	0.375 A

Design

Placement	Table
Product colour	Black
On/off switch	Yes
Reset button	Yes
WPS push button	Yes

Antenna

Antenna type	External
Antennas quantity	4

Certificates

Compliance certificates	Federal Communications Commission (FCC), RoHS
-------------------------	---

Weight & dimensions

Width	240 mm
Depth	165 mm
Height	43.6 mm

Packaging content

Quantity per pack	1 pc(s)
AC adapter included	Yes
PoE adapter included	Yes

Cables included	LAN (RJ-45)
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Sustainability	
Sustainability compliance	Yes

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE

tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt