TP-Link 10/100Mbps Single-Mode Media Converter

Gamintojas: **TP-LINK** · Modelis: **MC110CS** · EAN: **6935364030407** · Prekės kodas: **935255**



38,90 €

Kaina su PVM

Be PVM: **32,15 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Complies with 802.3u 10/100Base-TX, 100Base-FX standards
- ✓ Link Fault Passthrough and Far End Fault minimize the loss caused by link failure timely
- ✓ Provides switch configuration of Half-Duplex / Full-Duplex transfer mode for FX port
- ✓ Extends fiber distance up to 20km

Aprašymas

What This Product Does

The MC110CS is a media converter designed to convert 100BASE-FX fiber to 100Base-TX copper media or vice versa. Designed under IEEE 802.3u 10/100Base-TX and 100Base-FX standards, the MC110CS is designed for use with single-mode fiber cable utilizing the SC-Type connector. The MC110CS supports longwave (LX) laser specification at a full wire speed forwarding rate. It works at 1310nm on both transmitting and receiving data.

Other features of this module include the ability to be used as a stand alone device (no chassis required) or with TP-LINK´s 19´´ system chassis, Auto MDI/MDI-X for TX port, Auto negotiation of duplex mode on TX port and front panel status LEDs. The MC110CS will transmit at extended fiber optic distances utilizing single-mode fiber up to 20 kilometers.

Techninė specifikacija

Network	
Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Gigabit Ethernet

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Ethernet LAN data rates	1000 Mbit/s
Fiber ethernet cabling technology	100BASE-FX
Auto MDI/MDI-X	Yes
Cabling technology	UTP 3, 4, 5e, 5
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Performance	
Maximum transfer distance	20000 m
Wavelength	1310 nm
Features	
Internal	No
LED indicators	Power, Speed
Product colour	Black
Compliance industry standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Power consumption (max)	1.52 W
Weight & dimensions	
Width	94.5 mm
Depth	73 mm
Height	27 mm
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Packaging data	
Package width	165 mm
Package depth	204 mm
Package height	65 mm
Package weight	380 g

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Certificates	
Certification	FCC, CE
Other features	
Dimensions (WxDxH)	94.5 x 73 x 27 mm
Full duplex	Yes
I/O ports	1x 100M SC 1x 100M RJ45
Matmenys ir svoris	
Matmenys (I × P × A)	17,00cm × 21,00cm × 7,00cm
Svoris	0,30kg

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH
Niederkasseler Lohweg 175, 40547 Düsseldorf, DE
tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt