

Lindy 150m Cat.6 HDMI 4K60 & Type C HDBaseT UK Wall Plate KVM Extender - Transmitter (38387)

Gamintojas: **LINDY** · Modelis: **38387** · EAN: **4002888383875** · Prekės kodas: **935459**



439,90 €

Kaina su PVM

Be PVM: **363,55 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Sends HDMI or Type C signals up to 150m over Cat.6 network cable via HDBaseT technology with Long Reach mode
- ✓ Supports HDMI 18G resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- ✓ Supports USB 2.0, Audio, RS-232, bi-directional IR and PoC (Power over Cable)
- ✓ UK standard 1-gang wall plate (86x86mm)



Aprašymas

The Lindy Cat.6 HDBaseT HDMI 4K60 & Type C Wall Plate Transmitter is one part of a high performance, reliable solution for extending AV and data signals over long distances via Cat.6 network cable.

By combining this Transmitter unit with a compatible HDBaseT Receiver such as Lindy No. 38389, this solution ensures reliable transmission up to 150m.

The following distance and resolution combinations are possible when using high quality Cat.6 or above U/UTP or F/UTP cable:

Standard Mode (STD)

90m: 3840x2160@60Hz 4:4:4 8bit / 4:2:2 12bit

Long Reach Mode (LRM)

150m: 3840x2160@30Hz 4:4:4 8bit / 4:2:2 12bit

Supporting resolutions up to 4K Ultra HD, video can be viewed in stunning clarity, while additional support for HDR (High Dynamic Range) allows content to be displayed with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut. This provides a reliable solution for creating eye-catching digital signage in retail, immersive displays at events or engaging setups in larger conference rooms or lectures halls.

Pushing the Source button on the front panel allow the user to switch between Type C or HDMI (with USB) inputs in order to control a source such as a PC from a compatible HDBaseT KVM Receiver. Auto switch feature is also supported.

PoC (Power over Cable) functionality with On/Off switch provides additional flexibility. This allows power to be supplied alongside data through Cat.6 network cable in a point to point connection between the transmitter and receiver, meaning only a single power supply is required at one side of the installation.

Featuring bi-directional IR ports at both sides of the setup, the source equipment can be easily controlled from the display side, and the display can also be controlled from the HDMI source side. This extension system allows for complete and simple control for the user providing also RS-232 port via terminal block on the rear side of the wall plate.

HDBaset is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance.

Please Note: the quoted lengths and resolutions are possible with a direct connection between Transmitter and Receiver using good quality Cat.6 or above cable. Using a different cable type, introducing couplers or patch panels may result in a reduction of possible distances.

Techninė specifikacija

Features	
Type	Transmitter
Connectivity technology	Wired
Maximum transfer distance	150 m
Cable types supported	Cat6
Maximum digital resolution	3840 x 2160 pixels
Maximum refresh rate	60 Hz
Colour depth	8 bit
Material	Metal, Plastic
LED indicators	Yes
Certification	CE, UKCA, FCC, RoHS, REACH, California Proposition 65

Transmitter

Transmitter video port type	HDMI
RJ-45 ports quantity (transmitter)	1

Receiver

Receiver local video port type	HDMI
RJ-45 ports quantity (receiver)	1

Ports & interfaces

USB port type	USB Type-C
HDMI version	2
RS-232 ports	1

Power

AC input voltage	24 V
Input current	1 A

Packaging data

Package width	152 mm
Package depth	95 mm
Package height	133 mm
Package weight	540 g

Packaging content

Manual	Yes
--------	-----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	20 - 90%

Other features

HDCP	Yes
HDCP version	2.2
Extended display identification data (EDID)	Yes
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA

Technical details

Dimensions (WxDxH)	86 x 38.05 x 86 mm
Maximum resolution	3840 x 2160 pixels
Weight	390 g

Logistics data

Quantity per pack1 pc(s)

Sustainability

Sustainability complianceYes

Matmenys ir svoris

Svoris0,54kg

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › CE ženklavimas

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB
lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH

Markircher Str. 22, 68229 Mannheim, DE
lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- › CE ženklavimas