iiyama ProLite TF2234MC-B1AGB computer monitor 54.6 cm (21.5") 1920 x 1080 pixels Full HD LED Touchscreen Multi-user Black

Gamintojas: **IIYAMA** · Modelis: **TF2234MC-B1AGB** · EAN: **4948570113774** · Prekės kodas: **935484**

325,90 €

Kaina su PVM

Be PVM: **269,34 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 54.6 cm (21.5") Black
- ✓ Screen shape: Flat
- ✓ Response time: 8 ms
- ✓ 1920 x 1080 pixels Full HD Panel type: IPS

Aprašymas

ProLite TF2234MC uses P-Cap Technology, built into an eye catching bezel with edge-to-edge glass. Featuring IPS LCD Screen technology, it offers exceptional colour performance and wide viewing angles. The higher brightness ensures crispy and clear image, even in bright environment. In addition to the superb image quality, the screen comes with an IP54 Rating, making it dust and water resistant, and with a rugged bezel making it suitable for demanding environments. The Anti Glare coating helps to avoid issues with reflections and external light sources affecting colour reproduction, contrast and sharpness. ProLite TF2234MC is the ideal screen for the kiosk integrators and a solution for Interactive Digital Signage, Instore Retail and Interactive Presentations.

Techninė specifikacija

Display	
Display diagonal	54.6 cm (21.5")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	8 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.78 million colours
LED backlight	Yes
Backlight type	LED
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness	300 cd/m²
Supported graphics resolutions	1920 x 1080 (HD 1080)
Supported video modes	1080p
Aspect ratio	16:9
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.247 x 0.247 mm
Horizontal scan range	31.5 - 82.3 kHz
Vertical scan range	56 - 75 Hz

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Display diagonal (metric)	55 cm
Separate H/V sync	Yes
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Multimedia	
Built-in camera	No
Design	
Product colour	Black
Glass thickness	7 mm
Ports & interfaces	
Number of upstream ports	1
VGA (D-Sub) ports quantity	1
DVI port	Yes
DVI-D ports quantity	1
HDMI ports quantity	0
DisplayPorts quantity	0
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Number of OSD languages	7
Plug and Play	Yes
LED indicators	Yes
Power	
Power consumption (typical)	27 W
AC input voltage	100-240 V
AC input frequency	50 - 60 Hz
Power supply type	DC

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (without stand)	517.5 mm
Depth (without stand)	46 mm
Height (without stand)	313.5 mm
Weight (without stand)	4.4 kg
Packaging content	
Cables included	AC, DVI, USB, VGA
Quick start guide	Yes
Other features	
International Protection (IP) code	IP65
Display viewable area (HxV)	268.1 x 476.6 mm
Power management	Yes
Certification	CE, TÜV-Bauart, cULus, CU, VCCI
Supplied AC adapter type	AC
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Svoris	8,18kg

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International
Wijkermeerstraat 8, 2131 HA Hoofddorp, NL
iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.