Lanview RSL42U81BL rack cabinet 42U Freestanding rack Black

Gamintojas: **LANVIEW** · Modelis: **RSL42U81BL** · EAN: **5420016846587** · Prekės kodas: **935598**



1 545,90 €

Kaina su PVM

Be PVM: **1 277,60 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Perforated Door
- ✓ 4 way fan included
- ✓ RAL9005
- ✓ Vertical Cable management included
- ✓ Castors and Leveling feet included
- ✓ Cage nuts can be bought separate



Aprašymas

Product Dimensions: 800 x 1000 x 2053mm

Free standing rack cabinets offers the most ideal solutions at the offices and system rooms in the areas of cabling and server installations. The cabinets created in a highly strong and robust structure are unrivalled in their class.
With the specially designed structure, the cabinets can be assembled and disassembled easily. Simple tools will be enough to assemble the whole cabinet. The front door with spring loaded hinge system provides ease at the installation and use as it’s changeable on the desired direction of opening, removable and installable without the need of any tool.
The standard rear door model is solid metal door. It is easy to remove especially during relocation, installation and maintenance of the cabinet and system inside. The easily removable rear doors have the barrel locking mechanism.
The 3U high brushed cable entries on the bottom and top of the back of the cabinet are provided as the standard configuration of the cabinets. These cable entries enable the cable management on top, back and bottom of the cabinet. As the roof is located 10mm above the top of the cabinet,

it not only enables passive ventilation without the assembly of a fan module, but also provides resistance against water and dust.

Cabling Managing Made Easier

The cabinets are designed to enable the integration of vertical cable manager module structurally.

Thus, a bigger cable mass can be managed with these cable managers.The bottom chassis has a wide cable entry. The rubber edged sliding cable entry module directs the mass cables. After the cables are directed inside the cabinet, the sliding part is closed and fixed. The rubber edges are closed without any damage to the cables and the dust proof structure is provided on the maximum level available. Thanks to the Tire-Up structured side bracket provided, it’s extra advantageous to direct the cables upwards and downwards and to fix them in the exact position.

Secured Door

The front door modules with horizontally split doors consist of decorative metal frame on both left and right. The front doors with full size, break-resistant, tempered, anti-static 4mm smoke colored glass are lockable by the handle-locking mechanism.

The other sides are strengthened with U and Y shaped lockable and interlock able special metal bars. The rear door is solid metal and is easy to remove especially during relocation, installation and maintenance of the cabinet and system inside.

The easily removable rear doors have the barrel-locking mechanism.

Easy Secure Access from All Sides

The cabinets have the maximum strength with the side brackets and extra cube omega support points.

The side panel of the cabinets are easily removable and have a barrel-locking system. The 42U and 46U high cabinets have vertically split side panels and it enables easy removal of the panels during installation and maintenance or when there is not enough space available.

Techninė specifikacija

Features	
Rack capacity	42U
Type	Freestanding rack
Maximum weight capacity	2000 kg
Product colour	Black
Material	Steel
Frame type	Closed
Back door construction	Perforated
Front door construction	Perforated
Removable back door	Yes
Removable side panels	No
Key lock	Yes
Back door key lock	Yes
Front door key lock	Yes
Side panel key lock	Yes
Rack rails	Yes
Adjustable mounting rails	Yes
Adjustable feet	Yes
Cooling type	Active
Number of fans	4 fan(s)
Soundproof	No

Cable management	Yes
Castor wheels	Yes
Assembly required	No
International Protection (IP) code	IP20
Preassembled	Yes
Cable entry point	Yes
Weight & dimensions	
Size (imperial)	48.3 cm (19")
Width	820 mm
Depth	1050 mm
Height	2200 mm
Weight	127.7 kg
Packaging data	
Package width	820 mm
Package depth	1050 mm
Package height	2200 mm
Package weight	137 kg
Other features	
Dimensions (WxDxH)	800 x 1000 x 2053 mm
Matmenys ir svoris	
Svoris	1,00kg

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

› Atitikties deklaracija

Gamintojo ir saugos informacija

GAMINTOJAS

EET Group A/S

Bregnerødvej 133D, 3460 Birkerød, DK

eetgroup.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

› Atitikties deklaracija