

iiyama ProLite T2454MSC-B3AG kompiuterio monitorius 60,5 cm (23.8") 1920 x 1080 pikseliai „Full HD“ LED Lietimui jautrus ekranas Daugybė naudotojų Juoda

Gamintojas: **IIYAMA** · Modelis: **T2454MSC-B3AG** · EAN: **4948570125791** · Prekės kodas: **935814**



315,89 €

Kaina su PVM

Be PVM: **261,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 60,5 cm (23.8") Juoda
- ✓ Aukščio reguliavimas 11,1 cm Įmontuoti garsiakalbiai
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekranas: Plokščias
- ✓ Maksimalus atnaujinimo dažnis: 83 Hz Reakcijos laikas: 4 ms Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 1920 x 1080 pikseliai „Full HD“ Skydo tipas: IPS
- ✓ Energijos vartojimo efektyvumo klasė (SDR): E EPEAT, ErP, EPEAT Silver CE, EAC, REACH, RoHS, UKCA, WEEE





Aprašymas

Immersive interaction and elegant design - Discover the ProLite T2454MSC-B3AG, a vibrant 24" Full HD touchscreen monitor designed for exceptional interactive experiences. Featuring intuitive 10-point Touch technology (InCell PCAP), which ensures smooth and precise touch response. The vibrant colours of the IPS panel will captivate users with precise and natural interaction from any angle. Its sleek and stylish design and anti-glare surface offer durability and ease of cleaning, perfect for busy commercial environments, hospitality spaces, healthcare facilities and public areas. With adjustable ergonomics, neat cable management, built-in audio and seamless connectivity (HDMI, DisplayPort, USB 3.2 hub), it is an ideal choice for POS, self-service solutions and interactive signage.

Techninė specifikacija

Display	
Display diagonal	60.5 cm (23.8")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	4 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	83 Hz
Display number of colours	16.7 million colours
LED backlight	Yes
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	300 cd/m²
Display brightness	300 cd/m²
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes

Supported graphics resolutions	640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)
Contrast ratio (dynamic)	5000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.2745 x 0.2745 mm
Horizontal scan range	30 - 83 kHz
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Display diagonal (metric)	60.5 cm
Surface hardness	3H
Colour depth	8 bit
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Windows operating systems supported	Yes
Linux operating systems supported	Yes
OmniTaps Multitouch compatibility	Yes
Palm rejection	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Megapixel (approx.)	2.1 MP
Design	
Market positioning	Business
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes

USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of upstream ports	1
Number of downstream ports	2
USB Type-A downstream ports quantity	2
USB Touch port	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
HDCP	Yes

Ergonomics

VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable management	Yes
Cable lock slot type	Kensington
Adjustable height (max)	11.1 cm
Tilt adjustment	Yes
Tilt angle range	-5 - 90°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Portuguese, Russian
Number of OSD languages	10
Plug and Play	Yes

Power

Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	17 kWh
Power consumption (typical)	17 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Operational conditions

Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	540 mm
Depth (with stand)	241 mm
Height (with stand)	373 mm
Weight (with stand)	5.4 kg
Packaging data	
Package width	615 mm
Package depth	148 mm
Package height	420 mm
Package weight	7.1 kg
Packaging content	
Cables included	AC, USB, HDMI
Quick start guide	Yes
Sustainability	
Sustainability certificates	EPEAT, ErP, EPEAT Silver
Other features	
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Positional accuracy	2 mm
Placement supported	Horizontal/Vertical
Packaging content	Screwdriver
Active display area (W x H)	527.04 x 296.46 mm
USB ports quantity	2
Weight	5.4 kg
Height	373 mm
Width	540 mm
Depth	241 mm
Compliance certificates	CE, EAC, REACH, RoHS, UKCA, WEEE
Mean time between failures (MTBF)	50000 h
Certification	CE, TÜV-Bauart, VCCI-B, EAC, ErP, WEEE, REACH, CB

User controls	luminance (contrast, brightness, i-Style Color, adv. contrast, eco), Image settings (aspect ratio), Color settings (gamma, 6- axis, color temp), OSD (OSD horizontal position, OSD vertical position, OSD time, language), Extra (reset, DDC/CI, signal select, OverDrive, opening logo, information)
Touch method	finger, glove (latex), capacitive stylus
Control panel	Power, menu, +, -, Exit
Supplied AC adapter type	AC

Technical details

Native refresh rate	83 Hz
---------------------	-------


Logistics data

Harmonized System (HS) code	85285210
-----------------------------	----------

Matmenys ir svoris

Matmenys (I x P x A)	62,00cm x 15,00cm x 41,00cm
Svoris	5,40kg

Energijos efektyvumas ir ekologinis projektavimas



17 kWh/1000h



ETC/04/19/20

Energijos efektyvumo klasė **E** A-G

- > [Energijos etiketė](#)
- > [Gaminio informacijos lapas](#)
- > [EPREL duomenų bazė](#)

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)
- > [Vaizdo įrašas 1](#) objects.icecat.biz/objects/134659913_69139902.mp4
- > [Vaizdo įrašas 2](#) objects.icecat.biz/objects/134659913_69139905.mp4
- > [Vaizdo įrašas 3](#) objects.icecat.biz/objects/134659913_69139903.mp4
- > [Vaizdo įrašas 4](#) objects.icecat.biz/objects/134659913_69139904.mp4

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeerstraat 8, 2131 HA Hoofddorp, NL

[iiyama.com](https://www.iiyama.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt