

Thermaltake Toughpower PT 1200W power supply unit 24-pin ATX ATX Black

 Gamintojas: **THERMALTAKE** · Modelis: **PS-TPP-1200FNFAPE-1** · EAN: **4711658545305** · Prekės kodas: **936589**


176,90 €

Kaina su PVM

 Be PVM: **146,20 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt


Aprašymas

Package type: Box | Motherboard power cable length: 55 cm | Storage relative humidity (H-H): 5 - 95% | Peripheral (Molex) power cable length: 300 mm | Peripheral (Molex) power cable length: 750 | Max output current (-12V): 0.3 A | Cabling type: Fully-Modular | Peripheral (Molex) power cable length: 600 | Total power: 1200 W | Power protection features: Short circuit | Power protection features: Over voltage | Motherboard power connector: 24-pin ATX | Fan diameter: 13.5 cm | Power Good signal delay range: 100 - 150 ms | Power protection features: Over power | SATA power cable length: 600 | Combined power (-12V): 3.6 W | ATX version: 3.1 | PCI Express power connectors (6+2 pin): 5 | Number of SATA power connectors: 6 | PCI Express power connectors (12+4 pin): 2 | AC input voltage: 100 - 240 V | SATA power cable length: 450 | SATA power cable length: 750 | Operating temperature (T-T): 0 - 40 °C | Peripheral (Molex) power cable length: 450 | Power Factor Correction (PFC) type: Active | Number of fans: 1 fan(s) | Peripheral (Molex) power connectors (4-pin): 4 | Height: 86 mm | Power protection features: Under voltage | Power protection features: Over current | Depth: 140 mm | Efficiency: 92% | CPU power connector (4+4 pin): Yes | Product colour: Black | Power supply unit (PSU) form factor: ATX | Input current: 15 - 10 A | Mean time between failures (MTBF): 100000 h | Cooling type: Active | Combined power (+3.3V): 100 W | 80 PLUS certification: 80 PLUS Platinum | Combined power (+5V): 100 W | Combined power (+5Vsb): 15 W | Width: 150 mm | Max output

current (+5Vsb): 3 A | Combined power (+12V): 1200 W | Safety: CE/UKCA/FCC/ICES/CB/TUV/cTUVus/LVD/CCC/BSMI/ S-MARK/EAC/RCM | Max output current (+5V): 20 A | Purpose: PC | Hold time: 17 ms | Storage temperature (T-T): -20 - 70 °C | Max output current (+3.3V): 20 A | Max output current (+12V): 100 A | PCI Express power connectors (12+4 pin) cable length: 600 mm | Bearing technology: FDB | On/off switch: Yes | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 20 - 90% | CPU power cable length: 70 cm

Techninė specifikacija

Matmenys ir svoris	
Matmenys (l × P × A)	31,00cm × 12,00cm × 22,00cm
Svoris	3,51kg