

D-Link DNH-100 tinklo valdymo įrenginys 100 Mbit/ai Ethernet LAN jungtis

Gamintojas: **D-LINK** · Modelis: **DNH-100** · EAN: **790069451980** · Prekės kodas: **937433**



205,91 €

Kaina su PVM

Be PVM: **170,17 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Firewall per pardavimas: 100 Mbit/ai
- ✓ LAN prisijungimo taškų skaičius (maks.): 2
- ✓ Ethernet LAN jungtis IEEE 802.1Q, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x Web pagrįstas valdymas VLAN palaikymas
- ✓ Vielinis



Aprašymas

A Refreshing Take on Network Management

The D-Link DNH-100 Wireless Controller is a centralized wireless LAN manager developed specifically for our Nuclias Connect management solution and is suitable for small to medium-sized business (SMB) IT infrastructure. It comes preloaded with Nuclias Connect network management software, which is a key asset for businesses where IT skills are limited by financial or other constraints.

Tasks can be centralized and automated, meaning the DNH-100 is highly suited for remote deployment where either dedicated onsite staff are unavailable, or servers, PCs and other devices that can run the software might not be viable.

Better-Than-Expected Performance at a Smaller-Than-Expected Price

The DNH-100 is unbeatable value for money, delivering real value at a lower-than-expected price. Its backwards compatibility with a variety of legacy AP's means no need to unnecessarily replace older but still functioning hardware, better for your wallet and the planet.

With the ability to support up to 100 APs and a variety of business tools including Captive Portal, Payment Gateway Integration and Front Desk Ticket Management. Accordingly, all these top-notch capabilities can all be centralized thanks to the Nuclias Connect management software to reduce admin cost and fulfil most of SMBs networking and day-to-day demands.

Big Things Come in Small Packages

Despite its modest size, the DNH-100 offers the same Nuclias Connect management functionality of a larger device.

With a 1000Base-T Ethernet port, a USB 3.0 port, a Micro SD slot as well as support for IEEE 802.3ab/u/x, it's fully equipped for all occasions. Furthermore, manage up to 100 APs at one time, create and configure AP profiles, multiple SSID settings, access control, VLANs, time-based rules, bandwidth and performance. Control ranges from all-encompassing down to a single AP, so that fine-tuning your network via the connect software is effortlessly simple.

A Network That Can Look Out for Itself

The DNH-100 features self-organizing and self-optimizing capabilities such as interval-based radio scanning and analysis, self-management of radio frequency, as well as L2/L3 AP discovery and output power. Combined with other self-healing capabilities, it can maintain stability and continue operating at optimal levels even during peak usage times, so you can rest assured users are getting the best service possible.

An End to an Endless Number of Accounts

Nuclias Connect enables an extensive understanding of your network and its users through traffic analytics and status reports, which can be viewed at a glance. Insights derived from this data provide actionable intelligence which businesses can use to create business value. Traffic can be viewed across the entire network, down to the level of a single AP. Capacity and growth can be evaluated, as well as any irregularities that may arise, allowing for easier troubleshooting.

Real-Time Analytics & Reporting, All on an Intuitive Interface

Nuclias Connect enables an extensive understanding of your network and its users through traffic analytics and status reports, which can be viewed at a glance. Insights derived from this data provide actionable intelligence which businesses can use to create business value. Traffic can be viewed across the entire network, down to the level of a single AP. Capacity and growth can be evaluated, as well as any irregularities that may arise, allowing for easier troubleshooting.

Techninė specifikacija

Veikimo charakteristikos	
Firewall per pardavimas	100 Mbit/ai
LAN prisijungimo taškų skaičius (maks.)	2
Vienu metu veikiantys „IPSec“ tuneliai	0
Tinklas	
Tinklo standartai	IEEE 802.1Q, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x
Ethernet LAN jungtis	Taip
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Valdymo funkcijos	
Web pagrįstas valdymas	Taip

Reitingo apribotojimas	Taip
VLAN palaikymas	Taip
Saugumas	
Apsaugos algoritmų palaikymas	WPA2, WPA3
Ryšys	
Ryšio technologija	Vielinis
Ethernet LAN (RJ-45) portų kiekis	1
USB 2.0 portų kiekis	1
Energijos valdymas	
Maitinimas per Eternetą (PoE)	Ne
AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50 - 60 Hz
Energijos suvartojimas	6,5 W
Konstrukcija	
Produkto spalva	Balta
Maitinimo LED	Taip
LED indikatoriai	Energija
Sertifikavimas	FCC Class B, CE, C-Tick, VCCI, BSMI, cUL, CB, LVD (En60950-1)
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Darbo santykinės drėgmės diapazonas	5 - 95%
Sandėliavimo temperatūros norma (T-T)	-20 - 70 °C
Svoris ir matmenys	
Matmenys (WxDxH)	190 x 100 x 31 mm
Svoris	529 g
Plotis	190 mm
Ilgis	100 mm
Aukštis	31 mm
Pakuotės turinys	
Instrukcija	Taip
Naudojimo žinynas	Taip
Matmenys ir svoris	
Matmenys (l × P × A)	10,00cm × 19,00cm × 3,00cm
Svoris	1,22kg

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Greitos pradžios vadovas
- › Gaminio lankstinukas
- › Atitikties deklaracija

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- › Atitikties deklaracija