

D-Link DGS-1210-10MP Valdomas L2 Gigabit Ethernet (10/100/1000) Maitinimas per Eternetą (PoE) Juoda, Pilka

Gamintojas: **D-LINK** · Modelis: **DGS-1210-10MP/E** · EAN: **790069467714** · Prekės kodas: **937513**



221,90 €

Kaina su PVM

Be PVM: **183,39 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Valdomas L2 Web pagrįstas valdymas
- ✓ Paslaugos kokybės (QoS) palaikymas
- ✓ Pagrindinių perjungimo RJ-45 etherneto prievadų skaičius: 8
- ✓ Adreso lentelės dydis: 8000 įrašai Perjungimo pajėgumas: 20 Gbit/s
- ✓ AC Pridėtas maitinimo šaltinis Maitinimas per Eternetą (PoE)



Aprašymas

Static Routing

Route Layer 3 traffic between switches, even if they're segmented in VLANs.

Fibre Uplink Ports

Connect to other areas of your network at fibre-optic Gigabit speeds, and reach even further distances.

Surveillance Mode Interface

D-Link's exclusive, easy-to-use Surveillance Mode interface gives you a snapshot of your security topology in an instant.

PoE Capable

Up to 370 W PoE output per switch

VLANs

Segment your network into VLANs.

Dual Image

Risk-free configuration testing.

Smart Managed with a Plus

With increased PoE output, advanced Layer 2 management features, and Layer 3 static routing , D-Link's DGS-1210 Smart+ Managed Gigabit Switches provide a cost-efficient and flexible solution for expanding any business network.

Advanced Layer 2 Management with Layer 3 Static Routing

The DGS-1210 Smart+ family has advanced network management options, accessible via Compact CLI or the Web-based UI, that equip your business with network capabilities such as VLANs, multiple spanning tree protocol (MSTP), link aggregation (LACP), static routing, dual software images, and dual configuration files.

With powerful security features like IGMP snooping, access control lists, port security, and the unique D-Link Safeguard Engine that protects your network against malicious denial-of-service attacks from broadcast, multicast and unicast flooding, the DGS-1210 Smart+ family is a versatile solution for access-edge network environments.

Fibre Uplinks

Use fibre uplinks to connect across longer distances, like factory lines and university campuses, using lightweight, secure, and energy-efficient fibre optic cabling that's immune to interference and which has access to higher throughput to protect the future demands of your business network.

PoE and PoE+, with budgets up to 370W

The DGS-1210 Smart+ Series includes a range of high power budget PoE-enabled switches for businesses looking to power larger deployments of VoIP phones, wireless access points or network cameras.

This product is compatible with Nuclias Connect

Nuclias Connect is our free remote network management software designed with network scalability, privacy and customisation in mind. It can be used either as an on-premises software management platform, or as a cloud solution.

Free Network Design and Management Software

D-Link's free Network Assistant (DNA) displays all connected devices and speeds up the first time configuration. The free D-View 7 Network Management System comes with a license for 25 nodes and 2 probes and full access to the management tools. Optional upgrade licenses allow you to broaden your network and analysis.

Smart Energy-Saving Design

D-Link Green technology enables the DGS-1210 Smart+ series to save power without any sacrifices. The majority of the family utilises a fanless design, otherwise they feature a smart fan that powers on above a certain temperature. All come with advanced silicon technology which saves up to 73% of energy compared to a normal switch.

Surveillance Mode

Select Surveillance Mode in the Web UI to take advantage of easy-to-use surveillance features which enable you to manage your surveillance network effortlessly. It automatically detects your security devices and segments them into a dedicated Auto Surveillance VLAN to handle video surveillance traffic securely and efficiently.

Free Next-Business-Day Service

Enjoy our free Next Business Day service, as standard, to replace faulty equipment quickly.

Our rapid-response technical support is designed to ensure businesses get the best support for their unique environment. Our extended warranty and enhanced service packages increase the lengths of warranties and further minimises downtime. You can even opt for our Same Business Day Service which guarantees the delivery of the replacement product within 4 hours of confirmation of product failure.

Techninė specifikacija

Valdymo funkcijos	
Perjungimo tipas	Valdomas
Perjungimo sluoksnis	L2
Paslaugos kokybės (QoS) palaikymas	Taip
Web pagrįstas valdymas	Taip
Ryšys	
Pagrindinių perjungimo RJ-45 ethernet prievadų skaičius	8
Pagrindinių perjungimo RJ-45 ethernet prievadų tipas	Gigabit Ethernet (10/100/1000)
Įdiegtų SFP modulių kiekis	2
Įdiegtų SFP+ modulių kiekis	0
Tinklas	
Tinklo standartai	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G parama	Ne
Portų mirroring	Taip
Pilnai abipusis (duplex)	Taip
Pusiau dvipusis	Taip
Srauto kontrolės palaikymas	Taip
Nuorodų agregacija	Taip
Transliacijos audros valdymas	Taip
Auto MDI/MDI-X	Taip
Aprėpties medžio protokolas	Taip
Head-of-line (HOL) blokavimas	Taip
Ethernet LAN duomenų perdavimo norma	10,100,1000 Mbit/ai

VLAN palaikymas	Taip
VLANs skaičius	256
Duomenų perdavimas	
Adreso lentelės dydis	8000 įrašai
Perjungimo pajėgumas	20 Gbit/s
Persiuntimo dažnis	14,88 Mpps
Statinis maršrutas	Taip
Statinių maršrutų skaičius	256
Jumbo Frames palaikymas	Taip
„Jumbo“ kadrai	10000
Paketo buferio atmintis	4,1 MB
Saugumas	
IGMP tinklinio judėjimo sekimas	Taip
Apsauga nuo nesklaidaus ryšio	Taip
Konstrukcija	
Produkto spalva	Juoda, Pilka
LED indikatoriai	Taip
Veikimo charakteristikos	
Vidinė atmintis	128 MB
Flash atmintis	32 MB
Vidutinis laikas tarp trikčių (MTBF)	1274005 h
Energijos valdymas	
Maitinimo šaltinis	AC
Pridėtas maitinimo šaltinis	Taip
Maitinimo šaltinių skaičius	1
AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50/60 Hz
Galios suvartojimas (maks.)	9,4 W
„Power over Ethernet“ (PoE)	
Maitinimas per Eternetą (PoE)	Taip
Maitinimo per Eternetą (PoE) prievadų skaičius	8
Bendrosios galios per Eternetą (PoE) charakteriskos	130 W
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-5 - 50 °C

Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%
Šilumos sklaida	507,23 BTU/h
Svoris ir matmenys	
Plotis	330 mm
Ilgis	180 mm
Aukštis	44 mm
Svoris	1,77 kg
Sertifikatai	
Atitikties sertifikatai	BSMI, CB, CCC, cUL
Tvarumas	
Tvarumo reikalavimų laikymasis	Taip
Matmenys ir svoris	
Svoris	2,77kg

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
[dlink.com](https://www.dlink.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt