Cudy GS1024 network switch Unmanaged Gigabit Ethernet (10/100/1000) Black

Gamintojas: **CUDY** · Modelis: **GS1024** · EAN: **6971690791124** · Prekės kodas: **937963**



64.90€

Kaina su PVM

Be PVM: **53.64€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 24× GbE
- ✓ Default/VLAN/Extend Modes
- ✓ Extend for 250 meters Transmission
- ✓ VLAN for Clients Isolation
- ✓ Desktop, Rack-Mount
- ✓ 270×182×44 mm (10.63×7.17×1.73'')
- ✓ 617 g (21.76 oz.)





Aprašymas

Default/VLAN/Extend Multi-Mode

VLAN Mode

Protect clients from attack from client-side hacking. With VLAN mode, downlink ports 1-22 can only communicate with uplink ports.

Extend Mode

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Prolong the transmission distance of ports 1-22 to a maximum of 250 meters and simplify installation. (These ports' speed will be capped at 10 Mbps)

DSCP/802.1p QoS

Itentify the packets with DSCP headers and forward those with higher priority first.

IGMP Snooping

Identifies the multicast groups connected to the switch and sends data to the exact ports instead of broadcasting them.

Loop Prevention

Blocks the ports automatically when it detects a loop in the network, preventing downtime caused by misoperation.

Fanless Cooling

Low heat generation and fanless design cater to noise-sensitive enironments.

Installation and Dimension

Mounting Brackets Included
Standard 1U Rackmount

Versatile Scenarios

Office Network
Mall Wi-Fi
Surveillance
ISP FTTB

Techninė specifikacija

Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	24
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Cable types supported	Cat3, Cat5, Cat5e
Flow control support	Yes
VLAN support	Yes
Data transmission	

MAC address table	8192 entries
Switching capacity	48 Gbit/s
Forwarding rate	35.712 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	15000
Packet buffer memory	0.5 MB
Design	
Rack mounting	Yes
Product colour	Black
Power	
Power source	AC
Power supply included	Yes
AC input voltage	90 - 260 V
AC input frequency	50/60 Hz
Power consumption (max)	11 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	182 mm
Depth	270 mm
Height	44 mm
Weight	1.06 kg
Packaging content	
Cables included	AC
Manual	Yes
Packaging data	
Package width	367 mm
Package depth	245 mm
Package height	84 mm
Matmenys ir svoris	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Matmenys (I × P × A)	37.00cm × 9.00cm × 25.00cm
Svoris	1.77kg

Gamintojo ir saugos informacija

MANUFACTURER

Cudy

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt