

LevelOne RJ45 to SC Fast Ethernet Media Converter, Multi-Mode Fiber, 2km

Gamintojas: **LEVEL ONE** · Modelis: **FVT-2001** · EAN: **4015867225462** · Prekės kodas: **938148**



55,90 €

Kaina su PVM

Be PVM: **46,20 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 100 Mbit/s 2000 m 1310 nm
- ✓ Ethernet LAN (RJ-45) ports: 1 DC-in jack
- ✓ Multi-mode SC 50/125,62.5/125 μm
- ✓ Black



Aprašymas

The FVT-2001 MMF SC media converter is able to convert network signals between copper and fiber-optic based networks. The converter provides a 10/100Base-TX RJ-45 port, supports full duplex and half duplex switch connectivity and 10Base-T and 100Base-TX auto-sensing. Used in multi-mode with fibre-optic cabling, this can extend a network range up to 2km.

The device features built-in Dip switches for easy converter configuration, which function on the Smart LFP (Link Fault Pass-through), allowing the converter to monitor both the fiber and copper ports for signal loss, as well as converter transmission method, auto-negotiation mode for adjusting copper speed and full & half duplex mode.

The FVT-2001 is able to operate in temperatures from -10° up to 55° Celsius. The converter can be used as a standalone unit or as a slide-in module to the CHV-2000 19" Converter Chassis, which can accommodate up to 14 units for use in a central wiring closet.

Techninė specifikacija

Network	
Maximum data transfer rate	100 Mbit/s
Converter input interface	10Base-T, 100Base-TX
Converter output interface	100Base-FX
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Store-and-forward	Yes
Duplex system	Full, Half
Link Loss Carry Forward (LLCF) supported	Yes
Link Loss Return (LLR) supported	Yes
Performance	
Maximum transfer distance	2000 m
Wavelength	1310 nm
Fiber mode structure	Multi-mode
Fiber cable diameters supported (core/cladding)	50/125,62.5/125 µm
Features	
Internal	No
LED indicators	Activity, Link
Product colour	Black
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Power over Ethernet (PoE) ports quantity	1
DC-in jack	Yes
Power	
Input voltage	5 V
Input current	1 A
Weight & dimensions	

Width	94 mm
Depth	70 mm
Height	25 mm
Weight	420 g
Operational conditions	
Operating temperature (T-T)	40 - 75 °C
Storage temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	5 - 90%
Packaging content	
AC adapter included	Yes
Quick installation guide	Yes
Packaging data	
Package width	235 mm
Package depth	125 mm
Package height	55 mm
Package weight	494 g
Package type	Box
Certificates	
Compliance certificates	RoHS
Certification	FCC, CE
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990

Gamintojo ir saugos informacija

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbH
Im Defdahl 10 F, 44141 Dortmund, DE
level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt