

LevelOne 8-Port PS/2-USB VGA KVM Switch

Gamintojas: **LEVEL ONE** · Modelis: **KVM-3208** · EAN: **4015867229385** · Prekės kodas: **938179**



342,90 €

Kaina su PVM

Be PVM: **283,39 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports video resolutions up to 2048 x 1536
- ✓ Numerical LED display and LED indicators for easy bank/port status monitoring
- ✓ Autoscan period programmable 10 ~ 95 through OSD Menu option
- ✓ Control and manage 8 computers or up to 248 computers via daisy chain function
- ✓ Enhanced PS/2 mouse reset hotkeys for non-PnP OS such as Win NT 4.0 and Linux
- ✓ Buzzer sound for hotkey and port switching confirmation
- ✓ Password protection
- ✓ Active Sync Replication for DDC emulation
- ✓ Auto-logout timeout support



Aprašymas

The LevelOne KVM-3208 8-port combo KVM switch enables users to control and manage a server farm or computers connected to the KVM switch with either the local console or remote console port. Local ConsoleThe KVM-3208 Combo KVM Switch is easy to connect to a keyboard and mouse with a VGA monitor through the local console port. This enables a user to control systems connected to the KVM switch directly. Remote ConsoleIn order to make use of the remote control feature.

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	8
Keyboard port type	USB, PS/2
Mouse port type	USB, PS/2
Video port type	VGA
Console ports	PS/2, USB A, VGA (D-Sub)
VGA (D-Sub) ports quantity	8
Console USB ports quantity	2
PS/2 ports quantity	2
DC-in jack	Yes
Performance	
Maximum resolution	2048 x 1536 pixels
Scan interval	10,15,20,25,30,35,40,45,50,55,60,70,80,90 s
Auto scan delay (min)	10 s
Auto scan delay (max)	95 s
Daisy chain	Yes
Maximum operating distance	30 m
Design	
Rack mounting	Yes
Product colour	Black
Rack capacity	1U
Housing material	Metal
Cascadable	Yes
LED indicators	Power
Push button	Yes
Hot keys	Yes
Display	
Built-in display	No
On Screen Display (OSD)	Yes
Power	
Power source	DC
Input voltage	9 V
Input current	1 A

External power adapter	Yes
------------------------	-----

System requirements

Windows operating systems supported	Windows 2000, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 95, Windows 98, Windows 98SE, Windows ME, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
-------------------------------------	--

Linux operating systems supported	Yes
-----------------------------------	-----

Mac operating systems supported	Yes
---------------------------------	-----

Sustainability

Compliance certificates	CE, Federal Communications Commission (FCC), UKCA, WEEE
-------------------------	---

Sustainability compliance	Yes
---------------------------	-----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Storage temperature (T-T)	-10 - 70 °C
---------------------------	-------------

Operating relative humidity (H-H)	0 - 85%
-----------------------------------	---------

Storage relative humidity (H-H)	0 - 90%
---------------------------------	---------

Weight & dimensions

Width	410 mm
-------	--------

Depth	165 mm
-------	--------

Height	44.5 mm
--------	---------

Weight	1.84 kg
--------	---------

Packaging data

Package width	567 mm
---------------	--------

Package depth	245 mm
---------------	--------

Package height	106 mm
----------------	--------

Package weight	2.88 kg
----------------	---------

Package type	Box
--------------	-----

Packaging content

Manual	Yes
--------	-----

AC adapter included	Yes
---------------------	-----

Technical details

Pallet gross length	110 cm
Pallet gross width	120 cm
Pallet height (air)	11.5 cm

Logistics data

Master (outer) cases per pallet (air)	24 pc(s)
Master (outer) case width	585 mm
Master (outer) case length	270 mm
Master (outer) case height	545 mm
Master (outer) case gross weight	15.2 kg
Products per master (outer) case	5 pc(s)
Country of origin	Taiwan

Matmenys ir svoris

Svoris	2,86kg
--------	--------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [CE ženklimas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbH

Im Defdahl 10 F, 44141 Dortmund, DE

level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt**Saugos dokumentai**

- › [CE ženklimas](#)