Allied Telesis AT-MMC2000/SC-960 network media converter 1000 Mbit/s 850 nm Multi-mode Grey

Gamintojas: **ALLIED TELESIS** · Modelis: **AT-MMC2000/SC-960** · EAN: **767035218618** · Prekės kodas: **938544**

375,90 €

Kaina su PVM

Be PVM: **310,66 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Convert speed as well as media type
- ✓ 2K MAC address tables
- ✓ Store-and-forward switching mode
- ✓ Transparent to IEEE 802.1Q packets
- ✓ Auto Negotiation and Auto MDI/MDIX on copper port
- ✓ IEEE support on copper
- ✓ Far End Fault on Fiber
- ✓ 10K byte Jumbo packets
- ✓ Link/Activity LED per port
- ✓ Smart MissingLink

Aprašymas

Gigabit Ethernet to Fiber Mini Media and Rate Converter

This standalone mini media and rate converter features 10/100/1000T to 1000SX conversion with a multi-mode SC fiber connector and supports from 220 m to 500 m. It is compatible with the MMCR18 rack-mount chassis.

Copper to Fiber Mini Media and Rate Converters

Overview

The Allied Telesis MMC Series of mini media converters leverages its smaller size to not only help the environment with a small carbon footprint, but also to save space in its working environment. Despite its compact size, the MMC Series delivers all the power and functionality of standard size media converters.

Extend Networks

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

The MMC Series are available in 100Mbps or 1000Mbps models. Depending on the model chosen, the fiber-optic port has options for fixed SC, ST, LC or SFP connectors capable of multi-mode or single-mode fiber connectivity. The twisted-pair copper port has an RJ-45 connector supporting either 100Mbps or 1000Mbps, with a maximum operating distance of 100 meters (328 feet).

VLAN Support

Many new backbone switch products now support the industry-standard IEEE 802.1Q specification for Virtual LANs (VLANs) that send extra-long data packets on the network. The MMC Series are fully compatible with these long packets, enabling them to be used in modern networks. Media converters not supporting this feature discard these extra long packets, making them unsuitable for modern networks.

Small and Flexible

The smaller size and external power supply of the MMC Series allows them to be used almost anywhere.

Smart MissingLink (SML)

The Smart MissingLink™ (SML) feature monitors network connections and provides notification when network segments fail, allowing network managers to quickly identify the source and location of failed segments and minimize downtime.

Smart Link Restoration

Smart Link restoration allows the devices, in cases of power failure, link loss or other interrupted service, to automatically restore the link without the need to restart/reset them.

Power Saving

The MMC Series continues the Allied Telesis commitment to the environment with over 50% power savings. With just 1.7W of power usage, the MMC Series media converters are some of the most efficient in the market today.

Link Test

The link test is a fast and easy way for you to test the connections between the media converter ports and the connected end nodes. If a network problem occurs, you can perform a link test to determine which port is experiencing a problem, and focus your troubleshooting efforts on the right cable or end node.

Techninė specifikacija

Network	
Maximum data transfer rate	1000 Mbit/s
Converter input interface	10Base-T, 100Base-T, 1000Base-T
Converter output interface	1000Base-SX
Networking standards	IEEE 802.1Q
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Fiber ethernet cabling technology	1000BASE-SX
Jumbo frames support	Yes
VLAN support	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Duplex system	Full
Performance	
Maximum transfer distance	500 m
Wavelength	850 nm
Fiber mode structure	Multi-mode
Features	
Internal	No
Plug and Play	Yes
Product colour	Grey
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	2
Power	
Input voltage	12 V
Input current	0.14 A
Weight & dimensions	
Width	59 mm
Depth	101.6 mm
Height	21.8 mm
Weight	170 g
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-30 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3048 m
Packaging content	
User guide	Yes
Manual	Yes
Quick installation guide	Yes
Certificates	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Certification	CE, UL60950-1, EN60950-1, FCC Class A, EN55022 Class A, CISPR 22 Class A, C-TICK, VCCI
Logistics data	
Harmonized System (HS) code	85176990

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- Vaizdo įrašas youtube.com/watch?v=clecqflUuR4

Gamintojo ir saugos informacija

GAMINTOJAS

Allied Telesis

ATSAKINGAS ASMUO ES

Allied Telesis International B.V.
Karl-Hammerschmidt-Straße 34, 85609 Aschheim-Dornach, DE
alliedtelesis.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt