

D-Link DMS-107/E tinklo komutatorius Ne-valdomas Gigabit Ethernet (10/100/1000) Juoda

Gamintojas: **D-LINK** · Modelis: **DMS-107/E** · EAN: **790069470240** · Prekės kodas: **938558**



53,91 €

Kaina su PVM

Be PVM: **44,55 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Ne-valdomas
- ✓ Paslaugos kokybės (QoS) palaikymas
- ✓ Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 5
- ✓ 10BASE-T, 100BASE-T, 1000BASE-T, 2500BASE-T
- ✓ Adreso lentelės dydis: 2000 įrašai Perjungimo pajėgumas: 20 Gbit/s
- ✓ DC



Aprašymas

Experience multi-Gigabit Ethernet speeds.

The DMS-107 is a multi-Gigabit Ethernet plug-and-play switch that provides ultra-fast connectivity to your network core or network-attached storage (NAS) device. You can easily connect multiple computers within minutes, and start sharing an internet connection, files, music, and video across your small office or home network.

2.5 Gigabit Ethernet

Save time transferring large files and improve sharing and productivity

Effortless multi-Gigabit networking

Easily upgrade or extend your home or small business network

Compact Metal Housing

Sturdy, compact metal housing with fanless design for silent operation

Energy Efficient Design

Automatic power saving features to reduce power usage

Ready for Wi-Fi 6.

It comes with multi-Gigabit ports for maximum throughput and performance - ideal for enjoying unrestricted Wi-Fi 6 devices, high-end gaming computers and workstations. The multi-Gigabit ports eliminate potential bottlenecks with Wi-Fi 6 Access Points, allowing your network to take full advantage of the efficiency and speeds provided by Wi-Fi 6.

Effortless traffic optimisation.

With 2.5 Gigabit transfer speeds on uplink ports, you can rapidly transfer files between connected servers and network attached storage (NAS) to computers. The switch's 802.1p Quality of Service (QoS) functionality on Gigabit ports automatically organises and prioritises time-sensitive and critical data for efficient delivery, allowing for buffer-free video streaming as well as smooth video and voice calls.

Plug-and-pay convenience.

The DMS-107 is a plug-and-play device that requires no advanced technical configuration. Plug-and-play makes it easy to instantly create a network connected to the internet.

Designed for life, built to last.

The DMS-107 features a fanless design for silent operation, reduced energy consumption, and increased reliability by eliminating a common point of failure. Its sturdy compact metal housing ensures the product can withstand wider operating temperatures by helping to dissipate heat and reduce stress on internal components.

Energy Saving.

The compact, metal housing and fanless design mean the switches can be placed virtually anywhere and operate silently. The DMS-107 is designed with energy efficiency in mind. The switches automatically reduce power to ports that are inactive or not connected, and support the IEEE 802.3az Energy-Efficient Ethernet standard.

Techninė specifikacija

Valdymo funkcijos

Perjungimo tipas	Ne-valdomas
Paslaugos kokybės (QoS) palaikymas	Taip

Ryšys

Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius	5
Pagrindinių perjungimo RJ-45 eterneto prievadų tipas	Gigabit Ethernet (10/100/1000)
Įdiegtų SFP modulių kiekis	0
Įdiegtų SFP+ modulių kiekis	0
Gigabit Ethernet (varinis) portų kiekis	5

2,5 Gb ethernet (laidinių) lizdų skaičius	2
Tinklas	
Tinklo standartai	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x
10G parama	Ne
Varinių ethernet kabelių technologija	10BASE-T, 100BASE-T, 1000BASE-T, 2500BASE-T
Auto MDI/MDI-X	Taip
Ethernet LAN duomenų perdavimo norma	10,100,1000,2500 Mbit/ai
Palaikoma MAC adresų funkcija „Auto-learning“	Taip
Duomenų perdavimas	
Adreso lentelės dydis	2000 įrašai
Perjungimo pajėgumas	20 Gbit/s
Persiuntimo dažnis	14,88 Mpps
„Store-and-forward“ funkcija	Taip
Eilių skaičius	8
Paketo buferio atmintis	2 MB
Konstrukcija	
Produkto spalva	Juoda
Korpuso medžiaga	Metalas
LED indikatoriai	Aktyvumas, Jungtis, Energija
Veikimo charakteristikos	
Be ventiliatoriaus	Taip
Vidutinis laikas tarp trikčių (MTBF)	944277,78 h
Energijos valdymas	
Maitinimo šaltinis	DC
DC įėjimo įtampa	12 V
Įvesties srovė	0.5 A
Energijos suvartojimas	3,37 W
„Power over Ethernet“ (PoE)	
Maitinimas per Ethernetą (PoE)	Ne
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-10 - 70 °C
Darbo santykinės drėgmės diapazonas	10 - 90%

Sandėliavimo santykinis drėgmės diapazonas	5 - 90%
--	---------

Šilumos sklaida	14,28 BTU/h
-----------------	-------------

Svoris ir matmenys

Plotis	145 mm
--------	--------

Ilgis	28 mm
-------	-------

Aukštis	82 mm
---------	-------

Svoris	295,2 g
--------	---------

Sertifikatai

Atitikties sertifikatai	BSMI, CE, Žemos įtampos direktyva (LVD), RoHS
-------------------------	---

Tvarumas

Tvarumo reikalavimų laikymasis	Taip
--------------------------------	------

Matmenys ir svoris

Matmenys (I × P × A)	16,00cm × 10,00cm × 10,00cm
----------------------	-----------------------------

Svoris	0,47kg
--------	--------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [CE ženklimas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
[dlink.com](https://www.dlink.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- › [CE ženklimas](#)