

TERRA MINISERVER G6 E-2434/32/2x960/C/WS2025E

Gamintojas: **TERRA** · Modelis: **1100376** · EAN: **4039407083558** · Prekės kodas: **939218**



6 191,90 €

Kaina su PVM

Be PVM: **5 117,27 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Socket 1700
- ✓ Up to 64 GB DDR5 UB ECC RAM
- ✓ PCIe 5.0
- ✓ Remote Management module
- ✓ TPM module
- ✓ Acoustic level is in the range of a personal computer



Aprašymas

The TERRA MINISERVERS are perfect for small businesses or departments who appreciate central data administration and the shared use of information and resources.

Due to the compact construction the TERRA MINISERVER can be used in every office, in every environment.

Techninė specifikacija

Processor	
Processor family	Intel® Xeon®
Processor manufacturer	Intel
Processor model	E-2434
Processor frequency	3.4 GHz
Processor boost frequency	5 GHz
Performance cores	4
Processor cores	4
Processor cache	12 MB
Motherboard chipset	Intel C262
Memory channels supported by processor	Dual
Number of processors installed	1
Maximum number of SMP processors	1
Processor socket	LGA 1700
Intel® Optane™ Memory Ready	No
Memory	
Internal memory	32 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	64 GB
Memory slots	2x DIMM
ECC	Yes
Storage	
Total storage capacity	1.92 TB
RAID support	Yes
Optical drive type	No
Supported HDD sizes	2.5,3.5"
Number of SSDs installed	2
SSD capacity	960 GB
SSD interface	SATA III
Supported SSD sizes	2.5", 3.5"
RAID levels	1
Supported RAID controllers	Broadcom MegaRAID 9550-8i
Hot-swap	Yes

Internal drive bays	4x 3.5"/2.5" (HotSwap-fähig) ; 2x 2.5" (für Festeinbau von SSDs)
Graphics	
On-board graphics card	Yes
On-board graphics card family	Aspeed
On-board graphics card model	Aspeed AST2600
Maximum graphics card memory	64 MB
Network	
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet
Number of LAN controllers	2
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2
VGA (D-Sub) ports quantity	1
Total number of SATA connectors	6
Design	
Chassis type	Mini Tower
Cooling type	Active
Performance	
Remote administration	Ja
Trusted Platform Module (TPM)	Yes
Software	
Operating system installed	Windows Server 2025 Essentials
Compatible operating systems	Windows Server 2025 Windows Server 2022 Windows Server 2019
Operating system language	Multilingual
Power	
Redundant power supply (RPS) support	No
Power supply	450 W
Number of redundant power supplies supported	1
Number of redundant power supplies installed	1
Number of main power supplies	1
Power supply input voltage	100 - 240 V
Power supply input frequency	50/60 Hz

Operational conditions	
Operating temperature (T-T)	10 - 35 °C
Operating relative humidity (H-H)	10 - 75%
Certificates	
Certification	CE, production according to ISO9001 in Germany
Weight & dimensions	
Width	200 mm
Depth	340 mm
Height	270 mm
Technical details	
Compliance certificates	CE
Other features	
Memory type	2x DDR5 PC4800, UB ECC
Motherboard manufacturer	Asus P13R-I
Matmenys ir svoris	
Svoris	12,00kg

Gamintojo ir saugos informacija

GAMINTOJAS	PLATINTOJAS
WORTMANN AG	MB KOMPIUTERIŲ GURU
Bredenhop 20, 32609 Hüllhorst, DE	V. Nagevičiaus g. 3, LT-08237 Vilnius
wortmann.de	info@shopro.lt