StarTech.com 50ft (15m) Active HDMI 2.0 Cable, CMP, Plenum Rated, High Speed HDMI Cable, 4K 60Hz, HDR10/HDCP 2.2/ARC, CMP In Wall HDMI Cord

Gamintojas: **STARTECH** · Modelis: **HD2AP-15M-HDMI-CABLE** · EAN: **065030894265** · Prekės kodas: **939455**



179,90 €

Kaina su PVM

Be PVM: **148,68 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ DESIGNED FOR LONG RANGE: Active HDMI 2.0 Cable delivers 4K 60Hz beyond the length of passive copper cables; An integrated active chipset enables consistent performance without requiring an external booster or power source; Note: Cable is unidirectional
- ✓ PLENUM RATED: CMP-rated HDMI cable jacket is designed for safe installation in plenum spaces; Suitable for ceiling, conduit, and in-wall cable runs; For use in commercial environments where compliance with fire codes must be considered
- ✓ APPLICATIONS: Full-featured HDMI 2.0 enables Dynamic HDR10 w/10-bit processing for vibrant picture quality; Ideal for UHD/4K monitors/projectors/large displays, conference rooms, and video walls; 7.1 and 32-ch audio w/ARC; Compatible w/HDMI 1.4/1.2
- ✓ QUALITY CONSTRUCTION: Gold-plated connectors rated beyond 10,000 insertion cycles; Durable plenum jacket with robust strain reliefs; Tested beyond 1,000 bending cycles at -/+ 60° Embossed markings on connectors for Source and Display
- ✓ SPECS: Black; 15-meter (49.2-foot); Unidirectional; CMP (Plenum-Rated); High Speed HDMI 2.0; Supports HDR10/HDCP 2.2/7.1 & 32-ch audio; 18Gbps; 4K 60Hz; 9mm (0.35in) O.D.; Ideal for long cable runs








Aprašymas

Reliably connect high-bandwidth HDMI 2.0 devices through plenum spaces

Route this Active High Speed HDMI® 2.0 Cable through office plenum spaces for long distance transmission of 4K 60Hz video and high quality audio.

HDMI UHD Over Long Distances

The Active HDMI 2.0 cord is designed for long-distance reliability. Durable gold-plated connectors and 24/28AWG bare copper wire maintain optimal conductivity and low resistance, ensuring consistent performance across different environments. The integrated active chipset boosts the HDMI signal without requiring external power, facilitating 4K 60Hz video and full HDMI 2.0 capabilities. This enables the transmission of HDMI UHD video beyond passive cable lengths.

Full-Featured HDMI 2.0

The Active HDMI UHD Cable supports full HDMI 2.0 specifications:

• Up to 18Gbps bandwidth for 4K 60Hz video and higher refresh rates at lower resolutions (e.g. 1080p/1440p 120Hz)
• High Dynamic Range (HDR10) with 10-bit processing for higher contrast ratio and vibrant, cinematic picture quality
• Audio Return Channel (ARC) for 7.1 and 32-channel audio
• High-Bandwidth Digital Content Protection (HDCP 2.2) for a secure connection between source and display
• Dual Video Streams enable two independent video streams from a single source, allowing for picture-in-picture and other capabilities
• Variable Refresh Rate (VRR) synchronizes the refresh rate of the display with the output frame rate of the content, reducing screen tearing

Plenum-Rated Cabling

This HDMI 2.0 Cable features a Communications Multipurpose Plenum (CMP)-rated cable jacket with low-smoke characteristics. It is ideal for use in the plenum spaces of buildings (e.g., dropped ceilings and in-wall installations). The durable outer jacket is rated to withstand over 1,000 bending cycles at -/+60 degrees. This protects the cable from damage when routing through tight spaces that include multiple bends.

Note : This cable is unidirectional and must be installed in a specific direction. Refer to the embossed SOURCE and DISPLAY markings on the HDMI connectors to ensure that each end corresponds with the correct hardware.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Techninė specifikacija

Features	
Cable length	15 m
Connector 1	HDMI Type A (Standard)
Connector 2	HDMI Type A (Standard)
Connector 1 gender	Male

Connector 2 gender	Male
Product colour	Black
Connector contacts plating	Gold
Connector 1 form factor	Straight
Connector 2 form factor	Straight
HDMI version	2
Supported graphics resolutions	1920 x 1080 (HD 1080), 2560 x 1440, 3840 x 2160
Supported video modes	1080p, 1440p, 2560p
Audio Return Channel (ARC)	Yes
HDCP version	2.2
Data transfer rate	18 Gbit/s
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Supported digital audio channels (uncompressed)	7.1, 32
Unidirectional	Yes
Maximum refresh rate	120 Hz
AWG wire size	24/28
Cable material	Copper
Cable rating	CMP
Cable type	Round cable
Cable jacket material	Polyvinyl chloride (PVC)
Cable shielding	Aluminum mylar foil
Colour depth	10 bit
Operational conditions	
Operating temperature (T-T)	-20 - 70 °C
Storage temperature (T-T)	0 - 50 °C
Operating relative humidity (H-H)	0 - 95%
Certificates	
Compliance certificates	CE, RoHS
Weight & dimensions	
Cable diameter	9 mm
Packaging data	
Quantity per pack	1 pc(s)
Package width	264 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Package depth	253 mm
Package height	72 mm
Package weight	1.4 kg
Logistics data	
Master (outer) case width	405 mm
Master (outer) case length	312 mm
Master (outer) case height	314 mm
Products per master (outer) case	8 pc(s)
Sustainability	
Sustainability compliance	Yes

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.
Artisans Crescent 45, N5V 5E9 Ontario, London, CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited
Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt