

Cudy MC220 network media converter 1000 Mbit/s 1310 nm Single-mode Black

Gamintojas: **CUDY** · Modelis: **MC220** · EAN: **6971690790462** · Prekės kodas: **939530**



22,91 €

Kaina su PVM

Be PVM: **18,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Gigabit RJ45 Port to SFP Slot
- ✓ Hot-Swappable on RJ45 and SFP
- ✓ LFP and FEF for Troubleshooting
- ✓ Speed, Link, FDX, PWR LED



Aprašymas

Instant Network Monitoring with Built-in LED Indicators

With built-in LED indicators, you can easily check the working status of the device. The network status is instantly visible, making it simple to monitor and troubleshoot at a glance.

Reliable, High-Speed Transmission with No Speed Loss

The all-in-one module delivers exceptional optical and electrical performance, ensuring long-term data transmission stability.

Plug and Play, No Setup Required

Simply plug in the port, and it's ready to go—instant connection with no configuration needed. Easy to use, with fast and responsive performance.

Techninė specifikacija

Network	
Maximum data transfer rate	1000 Mbit/s
Converter input interface	1000Base-TX, 1000Base-FX
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Copper ethernet cabling technology	100BASE-TX, 100BASE-FX, 1000BASE-TX
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Cable types supported	Cat5, Cat5e
Performance	
Maximum transfer distance	20000 m
Wavelength	1310 nm
Fiber mode structure	Single-mode
Sensitivity	24 dBmW
Buffer size	9 KB
Mean time between failures (MTBF)	50000 h
Features	
Internal	No
Plug and Play	Yes
LED indicators	Yes
Product colour	Black
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Input voltage	90 - 240 V
AC input frequency	50 - 60 Hz

Output voltage	5 V
----------------	-----

Power consumption (typical)	4 W
-----------------------------	-----

Operational conditions

Operating temperature (T-T)	0 - 60 °C
-----------------------------	-----------

Operating relative humidity (H-H)	5 - 90%
-----------------------------------	---------

Matmenys ir svoris

Svoris	0,33kg
--------	--------

Dokumentai ir vaizdo įrašai

› [Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Cudy

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

› [Atitikties deklaracija](#)