ATEN CL5708MW rack console 43.9 cm (17.3") 1920 x 1080 pixels Metal, Plastic Black 1U

Gamintojas: **SECOMP** · Modelis: **CL5708MW D** · EAN: **4710469342462** · Prekės kodas: **939858**



1 262,90 €

Kaina su PVM

Be PVM: **1 043,72 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Exclusive LED illumination light – designed by ATEN to illuminate the keyboard and touchpad to allow visibility in lowlight conditions
- ✓ Integrated KVM console with 17”, 17.3”or 19“ LED-backlit LCD monitor in a Slideaway™ housing
- ✓ Available with or without fingerprint identification reader1
- ✓ Space saving technology – up to two consoles (one bus) control up to 8 or 16 computers
- ✓ Daisy-chain up to 31 additional units – controls up to 256 computers from a single console
- ✓ Dual interface – supports computers and console with PS/2 or USB keyboards and mice
- ✓ USB port allows each computer to access USB peripherals2 (inapplicable to CL5708MW)
- ✓ LCD module rotates up to 120 degrees for a more comfortable viewing angle
- ✓ Multiplatform support – Windows, Linux, Mac, and Sun
- ✓ Supports multimedia USB keyboards for PC, Mac and Sun






Aprašymas

The CL5708 Slideaway – LCD KVM Switch series is a control unit that allows access to multiple computers from a single PS/2 or USB KVM (keyboard, video, and mouse) console. A single CL5708 can control up to 8 or 16 computers. As many as 31 additional KVM switches can be daisy-chained to the CL5708, so that up to 256 computers can all be controlled from a single KVM console.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

The CL5708 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17", 17.3" or 19" LED-backlit LCD monitor, and touchpad in a 1U rack-mountable sliding housing. To enhance security, the CL5708 offers the option to use a fingerprint identification system for controlling access to both the CL5708 itself and the servers it commands.

The CL5708 is built on a modular design. The KVM section can be detached from the switch section for convenient maintenance and repair.

Techninė specifikacija

Display	
Display diagonal	43.9 cm (17.3")
Display resolution	1920 x 1080 pixels
Display	LCD
Display brightness	250 cd/m²
Contrast ratio (typical)	800:1
Viewing angle, horizontal	170°
Viewing angle, vertical	170°
On Screen Display (OSD)	Yes
Pixel pitch	0.1989 x 0.1989 mm
Response time	16 ms
Supported resolutions	1280 x 1024 @75 Hz; DDC2B, 1920 x 1200 @ 60 Hz
Technical details	
Rack capacity	1U
Material	Metal, Plastic
Product colour	Black
Hot-Plug support	Yes
Operating relative humidity (H-H)	0 - 85%
Built-in KVM switch	Yes
KVM switch ports quantity	8
Maximum resolution	1920 x 1200 pixels
Rack mounting	Yes
Console port	SPHD-18
Daisy chain	Yes
Number of computers controlled	256
On/off switch	Yes
LED indicators	Yes
Push button	Yes
Auto scan delay (min)	1 s

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Auto scan delay (max)	255 s
Compliance certificates	RoHS
Country of origin	China
Ports & interfaces	
VGA (D-Sub) ports quantity	8
Keyboard port type	USB, PS/2
Mouse port type	USB, PS/2
Video port type	VGA
Keyboard	
Built-in touchpad	Yes
Keyboard language	German
Keyboard layout	QWERTZ
Hot keys	Yes
Power	
Power consumption (typical)	15.4 W
AC adapter input voltage	100 - 240 V
AC adapter frequency	50/60 Hz
Input current	1 A
AC (power) in	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Weight & dimensions	
Width	689.2 mm
Height	44 mm
Depth	480 mm
Weight	13.4 kg
Packaging data	
Package weight	17.1 kg
Package width	668 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Package depth	833 mm
Package height	135 mm
Packaging content	
Cables included	AC, KVM
Quick installation guide	Yes
Manual	Yes
Rack mount kit	Yes
Logistics data	
Master (outer) case width	668 mm
Master (outer) case length	833 mm
Master (outer) case height	135 mm
Master (outer) case gross weight	17.1 kg

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Greitos pradžios vadovas
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.
Datung Road No.125, Sec. 2, 221 New Taipei City, TW
aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.