

StarTech.com 116E-USBC-DOCK knyginių kompiuterių dokas / jungčių replikatorius Vielinis USB 3.2 Gen 2 (3.1 Gen 2) Type-C Pilka, Sidabras

Gamintojas: **STARTECH** · Modelis: **116E-USBC-DOCK** · EAN: **065030900089** · Prekės kodas: **940429**



231,90 €

Kaina su PVM

Be PVM: **191,65 €**

Sandėlyje





Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ Priimančioji sąsaja: USB 3.2 Gen 2 (3.1 Gen 2) Type-C
- ✓ „USB Power Delivery“
- ✓ Ethernet LAN jungtis 10BASE-T, 100BASE-TX, 1000BASE-T Wake-on-LAN pasirengimas
- ✓ Kabelio spynos lizdas





Aprašymas

Seamlessly standardize across platforms with triple 4K display support

This USB-C Triple 4K Monitor Docking Station enables wide workstation flexibility, featuring compatibility with USB-C, or Thunderbolt 3/Thunderbolt 4 laptops, and supporting multiple combinations of Ultra HD 4K DisplayPort and HDMI monitors.

Enhance Productivity with Triple-4K Video

This triple-4K docking station uses a combination of its integrated DisplayLink® graphics controller and your computer's DP Alt Mode enabled USB-C port to provide three independent 4K displays.

Connect any combination of HDMI and/or DisplayPort monitors to Video Ports 1 and 2 (DisplayLink®); at resolutions up to 4K at 60Hz. Connect an HDMI monitor to Video Port 3 (DP Alt-Mode), at resolutions up to 4K at 30Hz. This high-resolution video performance is ideal for detailed graphics applications, enhancing your productivity by expanding the display capabilities of your laptop.

Full-Featured Docking Station

Connect the docking station to your computer's USB 3.2 Gen 2 (10Gbps) Type-C port to provide a wide range of port connectivity, options and features. The docking station features:

- 2x USB-A and 1x USB-C (USB 3.2 Gen 1 5Gbps) ports for USB peripheral devices.
- 1x USB-A and 1x USB-C (USB 3.2 Gen 2 10Gbps) port that supports BC 1.2 with 7.5W (1.5A) for charging tablets and smartphones.
- 1x Gigabit Ethernet port with WoL (Wake-on-LAN) for a wired Local Area Network (LAN) connection.
- 1x 3.5mm 4-position TRRS Audio Jack for a 3.5mm headset.

100W USB Power Delivery

The USB-C docking station supports 100W USB Power Delivery with the included power adapter. This allows you to charge the connected host device, as well as the devices connected to the BC 1.2 USB charging ports.

For added protection to connected USB devices, the BC 1.2 enabled USB charging ports feature Overcurrent Protection (OCP). OCP prevents USB peripherals from drawing more power than is safely allocated for the port.

Easy Deployment

Connect the dock to your host computer, using the included 3.3ft (1m) USB-C cable. The docking station supports all major operating systems, including Windows, macOS, ChromeOS, and Ubuntu. This dock was designed for seamless integration with any compatible USB-C equipped device within your organization, including Lenovo X1/Thinkpad P Series, Dell Latitudes/Precision/XPS 15, HP Envy, Surface Laptop 3, and M1 Pro/Max/M2 MacBooks. The dock features a side-facing K-Slot for added security in shared workspaces (e.g., BYOD hoteling/hot-desking).

Enhance Productivity and Device Management with the StarTech.com Connectivity Tools Application

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

- Advanced Windows Layout Utility : Setup and save custom windows layouts.

- Mac Address Pass-Through Utility : Improve network security.
- USB Event Monitoring Utility : Track and log connected USB devices.
- Wi-Fi Auto Switch Utility : Enable users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/Connectivity-Tools

This product is backed for 3-years by StarTech.com, including free lifetime 24/5 multi-lingual technical assistance.

Techninė specifikacija

Ryšys	
Ryšio technologija	Vielinis
Priimančioji sąsaja	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 2.0 portų kiekis	0
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	2
HDMI portų kiekis	3
Ausinių išvestys	1
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	1
USB 3.2 2 kart. (3.1 2 kart.) A tipo prievadų skaičius	1
USB 3.2 2 kart. (3.1 2 kart.) C tipo prievadų skaičius	1
„USB Power Delivery“	Taip
USB maitinimo šaltinio peržiūra	3.0
USB maitinimo tiekimas iki	100 W
HDMI versija	2.0
„DisplayPort“ kiekis	2
„DisplayPort“ versija	1.4
Jungtinis ausinių / mikrofono prievadas	Taip
Ausinių jungtis	3,5 mm
DC įėjimo lizdas	Taip
„USB Type C DisplayPort Alternate Mode“	Taip
Tinklas	
Ethernet LAN jungtis	Taip
Ethernet LAN (RJ-45) portų kiekis	1
Varinių eterreto kabelių technologija	10BASE-T, 100BASE-TX, 1000BASE-T
Wake-on-LAN pasirengimas	Taip
Tinklo standartai	IEEE 802.3ab
Veikimo charakteristikos	
Produkto spalva	Pilka, Sidabras

Integruotas kortelių skaitytuvas	Ne
Duomenų perdavimo sparta	10 Gbit/s
HD tipas	4K Ultra HD
Maksimali skaitmeninė raiška	4096 x 2160 pikseliai
Maksimalus atnaujinimo dažnis	60 Hz
Kabelio spynos lizdas	Taip
Laido spynos lizdo tipas	Kensington
LED indikatoriai	Energija
Korpuso medžiaga	Plastikas
Energijos valdymas	
AC įėjimo įtampa	100 - 240 V
Įvesties srovė	2.5 A
Išėjimo įtampa	24 V
Išėjimo srovė	5,41 A
Energijos suvartojimas	15 W
Kištuko tipas	M tipas
Belaidis įkrovimas	Ne
Programinė įranga	
Palaikomos „Windows“ operacinės sistemos	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Palaikomos MAC operacinės sistemos	Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos mobiliosios operacinės sistemos	Android
Kitos palaikomos operacinės sistemos	ChromeOS
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 70 °C
Sandėliavimo temperatūros norma (T-T)	-10 - 55 °C
Darbo santykinės drėgmės diapazonas	0 - 85%

Svoris ir matmenys

Plotis	85 mm
Ilgis	190 mm
Aukštis	30 mm
Svoris	350 g

Pakuotės duomenys

Pakuotės plotis	205 mm
Pakuotės gylis	250 mm
Pakuotės aukštis	50 mm
Paketo svoris	1,1 kg

Pakuotės turinys

Pridėti kabeliai	AC, Iš C tipo USB į C tipo USB
Kintamosios srovės adapteris	Taip
Greitos pradžios vadovas	Taip

Logistikos duomenys

Gaminių skaičius pagrindinėje (išorinėje) dėžėje	10 vnt
Pagrindinės (išorinės) dėžės plotis	280 mm
Pagrindinės (išorinės) dėžės ilgis	430 mm
Pagrindinės (išorinės) dėžės aukštis	290 mm

Kitos savybės

Lustų rinkinys	DisplayLink - DL-6950-N, VIA - VL817C0, Parade - PS176C0
----------------	--

Matmenys ir svoris

Svoris	1,03kg
--------	--------

Dokumentai ir vaizdo įrašai

- › Gaminio lankstinukas
- › Vaizdo įrašas 1 youtube.com/watch?v=V1e8gfpHE8s
- › Vaizdo įrašas 2 youtube.com/watch?v=0OUcYYrHpqs
- › Vaizdo įrašas 3 youtube.com/watch?v=pzZ6ygna0tk

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
startech.com

ATSAKINGAS ASMUIO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt