

StarTech.com DK31C3HDPDUE knyginių kompiuterių dokas / jungčių replikatorius Vielinis USB 3.2 Gen 2 (3.1 Gen 2) Type-C Juoda, Pilka

Gamintojas: **STARTECH** · Modelis: **DK31C3HDPDUE** · EAN: **065030881944** · Prekės kodas: **940431**



260,90 €

Kaina su PVM

Be PVM: **215,62 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ Priimančioji sąsaja: USB 3.2 Gen 2 (3.1 Gen 2) Type-C
- ✓ „USB Power Delivery“
- ✓ Ethernet LAN jungtis 10,100,1000 Mbit/ai
- ✓ Kabelio spynos lizdas





Aprašymas

USB-C & USB-A Dock | USB 3.2 Gen 2 10Gbps | 4K 60HZ HDMI | DisplayPort | 85W Power Delivery

This USB-C Gen 2 10Gbps docking station turns your USB-C ® or Thunderbolt™ 3 MacBook Pro, Windows laptop, and Chromebook into a powerful workstation. A USB 3.2 Gen 2 Type-C dock features everything you need, from triple HDMI or DisplayPort video outputs up to 4K 60 Hz to 10Gbps USB-C & USB-A downstream peripheral ports to 85W Power Delivery. Older USB-A laptops are supported through universal hybrid USB-C/USB-A cable included.

HDMI & DisplayPort for Triple Monitor Outputs

This USB-C Gen 2 docking station with DP 1.4 and HDMI 2.0 support, is a perfect choice for dual or triple monitor setup, supporting up to triple 4K 60Hz display output, with any combination of three DisplayPort or HDMI video interfaces, on USB-C Gen 2 (with DP 1.4 support) laptops, MacBooks and Windows-based Thunderbolt 3 laptops. Older USB-A laptops will only support dual monitor setup.

Host

Display Output

USB-C Gen 1 or 2 (with DP 1.4)

Triple Display - 3x 4K 60Hz

Thunderbolt 3 (DP 1.4 Supported)

Triple Display - 3x 4K 60Hz

USB-C Gen 1 (with DP 1.2)

Triple Display - 2x 4K 60Hz; 1x 4K 30Hz

USB-A or USB-C (No DP Alt Mode)

Dual Display - 2x 4K 60Hz

Power & Charge with 85W Power Delivery

Power and charge USB-C/Thunderbolt 3 workstation laptops & ultrabooks with 85 watt PD

Higher power delivery, MORE than other USB-C 10G Triple monitor docks. Charge smartphones and other devices with two downstream front-facing charging ports with BC 1.2 for USB-A and USB-C devices. Fast-charge ports support always-on charging so devices will charge whether or not a host laptop is connected.

Plenty of Downstream USB Ports

This USB-C Gen 2 docking station features 6 downstream USB ports in total to connect USB peripherals.

- 1x USB-C 3.2 Gen 2 (10 Gbps)
- 1x USB-A 3.2 Gen 2 (10 Gbps)
- 1x USB-C 3.2 Gen 1 (5 Gbps)
- 3x USB-A 3.2 Gen 1 (5 Gbps)

Also included, is a gigabit Ethernet port with PXE Boot and WoL support, as well as 4-position TRRS stereo audio headset/mic port.

Additional Security Features

This USB-C/USB-A docking station comes with plenty of security features such as a screw-lock host port which includes a USB-IF Certified 1m 2-in-1 USB-C/USB-A screw-lock cable, and a K-slot for a Kensington style laptop lock.

For added security, or flexibility where desk space is limited, this dock can be mounted to the wall, monitor, or underneath the desk with StarTech.com mounting brackets (SSPMSUDWM & SSPMSVESA). These mounting brackets (not included) are specifically designed for our docks and hubs to give you the customized setup you need.

Enhance Productivity and Device Management with the StarTech.com Connectivity Tools Application

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

-

Advanced Windows Layout Utility : To setup and save custom windows layouts.

-

Mac Address Pass-Through Utility : To improve network security.

-

USB Event Monitoring Utility : To track and log connected USB devices

-

Wi-Fi Auto Switch Utility : Enabling users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/Connectivity-Tools

The StarTech.com Advantage

Techninė specifikacija

Ryšys	
Ryšio technologija	Vielinis
Priimančioji sąsaja	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 2.0 portų kiekis	0
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	3
HDMI portų kiekis	3
Ausinių išvestys	1
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	1
USB 3.2 2 kart. (3.1 2 kart.) A tipo prievadų skaičius	1
USB 3.2 2 kart. (3.1 2 kart.) C tipo prievadų skaičius	1
„USB Power Delivery“	Taip
USB maitinimo tiekimas iki	85 W

HDMI versija	2.0
„DisplayPort“ kiekis	3
Jungtinis ausinių / mikrofono prievadas	Taip
DC įėjimo lizdas	Taip
Tinklas	
Ethernet LAN jungtis	Taip
Ethernet LAN (RJ-45) portų kiekis	1
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Veikimo charakteristikos	
Produkto spalva	Juoda, Pilka
Integruotas kortelių skaitytuvas	Ne
Duomenų perdavimo sparta	10 Gbit/s
Maksimali skaitmeninė raiška	3840 x 2160 pikseliai
Kabelio spynos lizdas	Taip
Laido spynos lizdo tipas	Kensington
Korpuso medžiaga	Aliuminis, Plastikąs
Sertifikavimas	CE, FCC
Energijos valdymas	
AC įėjimo įtampa	100 - 240 V
Įvesties srovė	2.5 A
Išėjimo įtampa	20 V
Išėjimo srovė	7,5 A
Kištuko tipas	M tipas
Suderinamų energijos šaltinio kištukinių lizdų tipai	EU, UK
Programinė įranga	
Palaikomos „Windows“ operacinės sistemos	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64
Palaikomos MAC operacinės sistemos	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 13.0 Ventura
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-20 - 70 °C

Darbo santykinės drėgmės diapazonas	0 - 95%
Svoris ir matmenys	
Plotis	84 mm
Ilgis	233 mm
Aukštis	37 mm
Svoris	365 g
Pakuotės duomenys	
Pakuotės plotis	172 mm
Pakuotės gylis	253 mm
Pakuotės aukštis	91 mm
Paketo svoris	1,7 kg
Pakuotės turinys	
Pridėti kabeliai	USB A tipo jungties adapteris USB C tipo jungtį
Kintamosios srovės adapteris	Taip
Greitos pradžios vadovas	Taip
Techninė informacija	
Atitikties sertifikatai	RoHS
Logistikos duomenys	
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	6 vnt
Pagrindinės (išorinės) dėžės plotis	315 mm
Pagrindinės (išorinės) dėžės ilgis	395 mm
Pagrindinės (išorinės) dėžės aukštis	300 mm
Darniosios sistemos (DS) kodas	84733020
Kitos savybės	
Kabelio ilgis	1 m
Lustų rinkinys	Realtek RTS5423, Realtek RTS5411, Realtek RTS5412, Realtek RTS5451, Realtek RTD2142, DisplayLink DL6950
Matmenys ir svoris	
Svoris	1,60kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas 1](#) youtube.com/watch?v=V1e8gfpHE8s
- › [Vaizdo įrašas 2](#) youtube.com/watch?v=0OUcYYrHpgs
- › [Vaizdo įrašas 3](#) youtube.com/watch?v=pzZ6ygna0tk

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt