

Allied Telesis AT-MMC200LX/SC-TAA-60 network media converter 100 Mbit/s 1310 nm Grey

Gamintojas: **ALLIED TELESIS** · Modelis: **AT-MMC200LX/SC-960** · EAN: **767035216416** · Prekės kodas: **940620**



310,90 €

Kaina su PVM

Be PVM: **256,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Convert speed as well as media type
- ✓ 2K MAC address tables
- ✓ Store-and-forward switching mode
- ✓ Transparent to IEEE 802.1Q packets
- ✓ Auto Negotiation and Auto MDI/MDIX on copper port
- ✓ IEEE support on copper
- ✓ Far End Fault on Fiber
- ✓ 10K byte Jumbo packets
- ✓ Link/Activity LED per port
- ✓ Smart MissingLink

Aprašymas

Copper to Fiber Mini Media and Rate Converters

Overview

The Allied Telesis MMC Series of mini media converters leverages its smaller size to not only help the environment with a small carbon footprint, but also to save space in its working environment. Despite its compact size, the MMC Series delivers all the power and functionality of standard size media converters.

Extend Networks

The MMC Series are available in 100Mbps or 1000Mbps models. Depending on the model chosen, the fiber-optic port has options for fixed SC, ST, LC or SFP connectors capable of multi-mode or single-mode fiber connectivity. The twisted-pair copper port has an RJ-45 connector supporting either 100Mbps or 1000Mbps, with a maximum operating distance of 100 meters (328 feet).

VLAN Support

Many new backbone switch products now support the industry-standard IEEE 802.1Q specification for Virtual LANs (VLANs) that send extra-long data packets on the network. The MMC Series are fully compatible with these long packets, enabling them to be used in modern networks. Media converters not supporting this feature discard these extra long packets, making them unsuitable for modern networks.

Small and Flexible

The smaller size and external power supply of the MMC Series allows them to be used almost anywhere.

Smart MissingLink (SML)

The Smart MissingLink™ (SML) feature monitors network connections and provides notification when network segments fail, allowing network managers to quickly identify the source and location of failed segments and minimize downtime.

Smart Link Restoration

Smart Link restoration allows the devices, in cases of power failure, link loss or other interrupted service, to automatically restore the link without the need to restart/reset them.

Power Saving

The MMC Series continues the Allied Telesis commitment to the environment with over 50% power savings. With just 1.7W of power usage, the MMC Series media converters are some of the most efficient in the market today.

Link Test

The link test is a fast and easy way for you to test the connections between the media converter ports and the connected end nodes. If a network problem occurs, you can perform a link test to determine which port is experiencing a problem, and focus your troubleshooting efforts on the right cable or end node.

Techninė specifikacija

Network	
Maximum data transfer rate	100 Mbit/s
Converter input interface	10Base-T, 100Base-T
Converter output interface	100Base-LX
Networking standards	IEEE 802.1Q
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Fiber ethernet cabling technology	100BASE-LX
Packet forwarding rate (10 Mbps)	14880 pps
Packet forwarding rate (100 Mbps)	148880 pps
Packet forwarding rate (1 Gbps)	1488000 pps
Jumbo frames support	Yes
Jumbo frames	10000
VLAN support	Yes

Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Store-and-forward	Yes
Duplex system	Full
Performance	
Maximum transfer distance	20000 m
Wavelength	1310 nm
Fiber cable diameters supported (core/cladding)	9/125 µm
Tx power (min)	-15 dBmW
Tx power (max)	-5 dBmW
Rx power (min)	-32 dBmW
Rx power (max)	-34 dBmW
Features	
Internal	No
LED indicators	Yes
Product colour	Grey
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	2
DC-in jack	Yes
Power	
Input voltage	12 V
Input current	0.14 A
Weight & dimensions	
Width	56 mm
Depth	101.6 mm
Height	21.8 mm
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-30 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Operating altitude 0 - 3048 m

Packaging content

AC adapter included Yes

Certificates

Safety UL60950-1, EN60950-1

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas](#) youtube.com/watch?v=clecqfIUuR4

Gamintojo ir saugos informacija

GAMINTOJAS

Allied Telesis

ATSAKINGAS ASMUO ES

Allied Telesis International B.V.

Karl-Hammerschmidt-Straße 34, 85609 Aschheim-
Dornach, DE
alliedtelesis.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt