

StarTech.com ST121HDBTE vaizdo ir garso signalų ilgintuvas AV siųstuvas ir imtuvas Juoda

Gamintojas: **SONSTIGE** · Modelis: **ST121HDBTE** · EAN: **065030851107** · Prekės kodas: **941498**



268,90 €

Kaina su PVM

Be PVM: **222,23 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ AV siųstuvas ir imtuvas 4096 x 2160 pikseliai Juoda
- ✓ Maksimalus perdavimo atstumas: 70 m
- ✓ 60 Hz
- ✓ 7.1 kanalai
- ✓ Vielinis DC įėjimo lizdas
- ✓ 3 W



Aprašymas

Extend HDMI® up to 230ft (70m) over a single CAT5e/6 cable with Power over Cable to Receiver

The StarTech.com HDBaseT extender kit, extends HDMI up to 230 feet (70 Meters) over a single CAT5e or CAT6 cable. The extender supports Ultra HD and Full HD resolutions (4K / 1080p) with support for 3D and the accompanying digital audio. For added versatility, both the transmitter and receiver can be powered by the same single power source using Power Over Cable (POC). The versatility of this video extender makes it an ideal solution for digital signage applications in large buildings such as commercial shopping centers, stadiums, schools, and hospitals.

What is HDBaseT?

HDBaseT is a standardized, zero latency, video distribution technology that's revolutionizing HDMI distribution. HDBaseT uses an advanced method of modulation that enables you to distribute uncompressed HDMI audio and video along with additional signals such as 100BaseT Ethernet, IR, RS-232 serial and power over cable.

Extend more with HDBaseT

The extender offers HDBaseT technology with HDMI and Power in a single extender kit, for complete end-to-end solution. Offering greater versatility than traditional HDMI extenders or HDMI cabling alone HDBaseT is the clear choice for every integrator and system designer. The added benefit of power over cable means you'll only need one power source at either side of your extension, great for extending video to areas where power outlets may be limited, such as industrial sites.

Astonishing 4K picture quality from an impressive distance

With the A/V industry quickly adopting 4K as the new high-resolution video standard, long range video distribution can be a challenge with standard HDMI cables beginning signal degradation at 30 feet.

With support for 4K you'll be amazed at how HDBaseT maintains your Ultra HD picture quality, four times the resolution of high-definition 1080p, even at 130 feet away from your video source. Plus, because the extender supports High-Definition 1080p and lower resolutions at 230 feet away, you can comfortably use this extender to make any video source look great.

Simplify your setup

This extender has been specially crafted for a smooth, tidy installation. HDBaseT technology allows for single cable installation, for seamless integration using existing CAT5e or CAT6 infrastructure, avoiding the hassle of running multiple Ethernet cables while, reducing potential failure points. Plus, the added benefit of power over cable means you'll only need one power source to power both your extender and receiver, great for extending to areas where power outlets may be limited. Mounting hardware is also included for both the extender and receiver for discrete, professional mounting.

The ST121HDBTE is TAA compliant and backed by a 2-year StarTech.com warranty with free lifetime technical support.

Techninė specifikacija

Savybės	
Tipas	AV siųstuvas ir imtuvas
Maksimali rezoliucija	4096 x 2160 pikseliai
Palaikomi laido tipai	Cat5e, Cat6
Maksimalus perdavimo atstumas	70 m
Maksimalus atnaujinimo dažnis	60 Hz
Audio sistema	Daugybė kanalų

Garso išvesties kanalai	7.1 kanalai
LED indikatoriai	Būsena
Palaikomi vaizdo režimai	720p, 1080p
Palaikomos grafikos rezoliucijos	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1600 (WQXGA), 4096 x 2160
Kabelio ilgis	0,1 m
Medžiaga	Aliuminis
Nuosekloji grandinė (Daisy Chain)	Ne
Vidutinis laikas tarp trikčių (MTBF)	52000 h
Produkto spalva	Juoda
Sertifikavimas	CE, FCC, HDBT, TAA

Ryšys

Ryšio technologija	Vielinis
RJ-45 įvesties prievadai	1
RJ-45 išvesties prievadai	1
HDMI įvestis	1
HDMI išvesčių skaičius	1
DC įėjimo lizdas	Taip

Energijos valdymas

AC įėjimo įtampa	110 - 240 V
Darbinė įtampa	12 V
Įvesties srovė	0.5 A
Išėjimo srovė	1,5 A
Energijos suvartojimas	3 W
Kištuko tipas	M tipas

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-10 - 60 °C
Darbo santykinės drėgmės diapazonas	0 - 80%

Svoris ir matmenys

Plotis	67 mm
Ilgis	80 mm
Aukštis	25 mm
Svoris	428 g

Pakuotės duomenys

Pakuotės plotis	158 mm
Pakuotės gylis	234 mm
Pakuotės aukštis	70 mm
Paketo svoris	1,1 kg

Pakuotės turinys

Kintamosios srovės adapteris	Taip
Pridėti kabeliai	LAN (RJ-45)
Priedamos maitinimo šakutės tipai	AU, EU, NA, UK
Instrukcija	Taip
Pridėti montavimo kronšteinai	Taip
Įžeminimo laidas	Taip

Techninė informacija

Atitikties sertifikatai	RoHS
Palaikomi garso įrašai	Taip

Logistikos duomenys

Pagrindinės (išorinės) dėžės plotis	322 mm
Pagrindinės (išorinės) dėžės ilgis	416 mm
Pagrindinės (išorinės) dėžės aukštis	264 mm
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	12 vnt

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas](#) youtube.com/watch?v=7uT6uFqbin8

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
[startech.com](https://www.startech.com)

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
[startech.com](https://www.startech.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt