

StarTech.com Dual Port PCI Express Gigabit Ethernet PCIe Network Card Adapter - PoE/PSE - TAA

Gamintojas: **STARTECH** · Modelis: **ST2000PEXPSE** · EAN: **065030849128** · Prekės kodas: **941568**



199,90 €

Kaina su PVM

Be PVM: **165,21 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dual 10/100/1000 Mbps PoE RJ45 ports
- ✓ Supports IEEE 802.3at (Type 1, 2) Power over Ethernet standard
- ✓ Power Sourcing Equipment (PSE) design, provides data and up to 25.5W of power on each port
- ✓ Built-in SATA and LP4 Molex power connector
- ✓ Unique surge protection design helps prevent system damage in the event of lightning strikes
- ✓ Jumbo Frame support
- ✓ On-chip 48 KB Big Transmit/Receive Buffer Support
- ✓ Fully Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, and supports IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
- ✓ Crossover Detection & Auto-Correction (Auto MDIX)
- ✓ Includes full and low profile/half-height installation brackets



Aprašymas

Add two Power-over-Ethernet Gigabit Ports to a PCI Express-enabled Computer

The ST2000PEXPSE Dual Port PoE NIC provides two 10/100/1000 Mbps PoE RJ45 ports that can provide up to 25.5W of power each, combining a network data connection and power on a single cable, for less clutter and convenient installations in remote locations.

This full/low profile Gigabit server adapter supports the IEEE 802.3at (Type 1 and 2) standard for a Power Sourcing Equipment (PSE) device, and can

deliver 48V DC power to compliant Powered Devices (PD). This eliminates the need for a separate power source and cable for remote networked devices such as IP cameras, IP phones and wireless access points.

Suitable for any PCI Express-enabled client, server or workstation, this versatile PoE network adapter supports features such as Jumbo Frames, VLAN tagging and Wake on LAN (WOL).

The ST2000PEXPSE PoE NIC is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Techninė specifikacija

Ports & interfaces	
Connectivity technology	Wired
Host interface	PCI Express
Interface	Ethernet
Ethernet LAN (RJ-45) ports	2
Power over Ethernet (PoE) ports quantity	2
Network	
Maximum data transfer rate	2000 Mbit/s
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
Ethernet LAN	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000BaseT(X)
Auto MDIX IEEE	Yes
Full duplex	Yes
Jumbo frames support	Yes
VLAN tagging	Yes
LAN controller	Realtek RTL8111E
Design	
Internal	Yes
Component for	PC
Chipset	Realtek - RTL8111E
LED indicators	Activity, Link, PoE
Mean time between failures (MTBF)	140981 h
Certification	CE, FCC, REACH
Power	
Output voltage	48 V
System requirements	

Windows operating systems supported	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 2000, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows ME, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Linux operating systems supported	Yes
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019

Operational conditions	
Operating temperature (T-T)	0 - 55 °C
Storage temperature (T-T)	-20 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	19 mm
Depth	195 mm
Height	68 mm
Weight	104 g
Packaging data	
Drivers included	Yes
Low-profile bracket	Yes
Package width	164 mm
Package depth	229 mm
Package height	44 mm
Package weight	246 g
Packaging content	
Manual	Yes
Technical details	
Compliance certificates	RoHS

Logistics data

Harmonized System (HS) code	85176990
Master (outer) case width	444 mm
Master (outer) case length	522 mm
Master (outer) case height	344 mm
Products per master (outer) case	40 pc(s)

Other features

Buffer size	48 KB
Flow control support	Yes

Matmenys ir svoris

Matmenys (l × P × A)	23,00cm × 17,00cm × 5,00cm
Svoris	0,25kg

Dokumentai ir vaizdo įrašai

[› Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA

startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt