

NETGEAR GS748PP Ne-valdomas Gigabit Ethernet (10/100/1000) Maitinimas per Eternetą (PoE) Pilka

Gamintojas: **NETGEAR** · Modelis: **GS748PP-100EUS** · EAN: **606449174915** · Prekės kodas: **943659**



525,90 €

Kaina su PVM

Be PVM: **434,63 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Ne-valdomas
- ✓ Paslaugos kokybės (QoS) palaikymas
- ✓ Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 48
- ✓ 10BASE-T
- ✓ Adreso lentelės dydis: 8000 įrašai
- ✓ Stovo montavimas
- ✓ AC/DC Maitinimas per Eternetą (PoE)



Aprašymas

POWER-OVER-ETHERNET

24 PoE+ ports delivering up to 30W per port with a 380W total power budget for wireless APs, IP Cameras, IP Phones and much more. Dynamic PoE maximizes usage of PoE budget.

PLUG-AND-PLAY

Simple set up with no software to install or configuration needed

NON-BLOCKING SWITCHING

Non-blocking switching architecture for maximum throughput at wire speed

DYNAMIC FANS

Optimal balance between noise and performance.

VERSATILE MOUNTING OPTIONS

Install your switch on your desktop or mount it to your rack with the hardware provided in the box

ENERGY EFFICIENT

Energy Efficient Ethernet (IEEE 802.3az) standard, which reduces energy consumption when there is light traffic on an active port or when there is no link or no activity detected

Techninė specifikacija

Management features

Switch type	Unmanaged
Quality of Service (QoS) support	Yes
MIB support	RFC 1213 MIB II, RFC 1643, RFC 1493

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)

Network

Networking standards	IEEE 802.1p, IEEE 802.3az
Copper ethernet cabling technology	10BASE-T
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Ethernet LAN data rates	1000 Mbit/s

Data transmission

MAC address table	8000 entries
Maximum data transfer rate	1 Gbit/s
Jumbo frames support	Yes
Jumbo frames	12.288
Packet buffer memory	1.5 MB
Design	
Rack mounting	Yes
Product colour	Grey
Redundant fans support	Yes
Number of fans	2 fan(s)
Safety	CE mark, cUL IEC950/EN60950
Performance	
Mean time between failures (MTBF)	570972 h
Power	
Power source	AC/DC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	8 A
Power consumption (max)	410 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	380 W
Other features	
Latency	2,900ns
Connectivity technology	Wired
Bandwidth	96 Gbit/s
Authentication method	802.1x
Warranty period	2 year(s)
I/O ports	48 x 10/100/1000 Mbps 4 x SFP
Electromagnetic emissions	CE mark, FCC Part 15 Class A, VCCI Class A, C-Tick
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C

Operating relative humidity (H-H)	10 - 90%
Operating altitude	0 - 3000 m
Heat dissipation	34.2 BTU/h

Weight & dimensions

Width	440 mm
Depth	310 mm
Height	43 mm
Weight	4.6 kg

Certificates

Compliance certificates	CB, CE, Federal Communications Commission (FCC), KC, Low Voltage Directive (LVD), RCM, UL, VCCI
-------------------------	---

Matmenys ir svoris

Matmenys (I × P × A)	53,00cm × 41,00cm × 11,00cm
----------------------	-----------------------------

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

NETGEAR

ATSAKINGAS ASMUO ES

NETGEAR Deutschland GmbH

Konrad-Zuse-Platz 1, 81829 München, DE

[netgear.com](https://www.netgear.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt