

D-Link 52-Port Gigabit Stackable Smart Managed Switch with 4 x 10G SFP+ Ports

Gamintojas: **D-LINK** · Modelis: **DGS-1530-52/E** · EAN: **790069474521** · Prekės kodas: **943660**



968,90 €

Kaina su PVM

Be PVM: **800,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2 Web-based management
- ✓ Quality of Service (QoS) support Configuring Location Settings (CLI)
- ✓ Basic switching RJ-45 Ethernet ports quantity: 48 Console port: RJ-45
- ✓ 10G support
- ✓ MAC address table: 16000 entries Switching capacity: 176 Gbit/s
- ✓ Access Control List (ACL)
- ✓ Rack mounting Stackable
- ✓ AC



Aprašymas

The DGS-1530 Series are part of the Layer 2 family of D-Link's Stackable Smart Switch product line that provides wired Gigabit speeds for Metro Ethernet and campus networks. They feature a variety of ports, including 10/100/1000BASE-T RJ-45 ports, 1G SFP ports, and 10G SFP+ ports for increased network bandwidth. Surge protection, advanced Layer 2 functions, and a suite of security and management tools make the DGS-1530 Series Stackable Smart Switch ideal for Metro Ethernet and campus applications.

Product Highlights

Comprehensive Security Solution Support for Access Control Lists (ACLs), multiple user authentication methods, and IP-MAC-Port Binding ensures a secure network environment

Superior Reliability

Per-port surge protection, Ethernet Ring Protection Switching (ERPS), and redundant power supply (RPS) features all help to maximize service availability

Scalability and High Availability

Physical stacking provides agile expansion and redundancy while reliability through fault tolerant topologies ensures rock-solid connectivity

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Traffic classification	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	4
USB Type-A ports quantity	1
Console port	RJ-45
USB 2.0 ports quantity	1
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3u, IEEE 802.3x
10G support	Yes
Port mirroring	Yes
Full duplex	Yes
Policy-based routing	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes

Spanning tree protocol	Yes
Ethernet LAN data rates	10,1000,100 Mbit/s
Auto-negotiation	Yes
VLAN support	Yes
Number of VLANs	4096
Data transmission	
MAC address table	16000 entries
Switching capacity	176 Gbit/s
Forwarding rate	130.95 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Packet buffer memory	1.5 MB
Security	
Access Control List (ACL)	Yes
Access Control List (ACL) egress	1000
Access Control List (ACL) ingress	2000
IGMP snooping	Yes
Security algorithms	SNMP, SNMPv2, SNMPv3
MAC address filtering	Yes
SSH/SSL support	Yes
Loop protection	Yes
Password protection	Yes
Authentication type	RADIUS, TACACS+
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Stackable	Yes
Product colour	Black
LED indicators	Yes
Number of fans	2 fan(s)
Performance	
Noise level	54.7 dB
Mean time between failures (MTBF)	330520 h

Power

Power source	AC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	44.1 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	-5 - 50 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Heat dissipation	150.38 BTU/h

Weight & dimensions

Width	440 mm
Depth	210 mm
Height	44 mm
Weight	3.2 kg

Dokumentai ir vaizdo įrašai[› Gaminio lankstinukas](#)**Gamintojo ir saugos informacija**

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link BeneluxPostbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt