Lindy 70m Cat.6 HDMI 4K60, USB and Audio KVM Extender

Gamintojas: **LINDY** · Modelis: **39383** · EAN: **4002888393836** · Prekės kodas: **944918**

218,90 €

Kaina su PVM

Be PVM: **180,91 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Extends HDMI and USB HID signals up to 70m using a single Cat.6 cable
- ✓ Supports HDMI resolutions up to 4K@60Hz 4:4:4 8bit with HDR
- ✓ EDID management and HDMI loop-out port to connect one additional display on the transmitter
- ✓ Supports PoC (Power over Cable), requiring a power supply connection from only one side of the installation
- ✓ 2 year warranty

Aprašymas

The Lindy Cat.6 HDMI 4K60, USB and Audio KVM Extender allow users to control a source device such as a PC from a single keyboard, mouse and display up to 70m using a Cat.6 RJ45 cable.

The following distance and resolution combinations are possible when using high quality Cat.6 or above U/UTP or F/UTP cable:70m: 1920x1080@60Hz 4:4:4 8bit40m: 3840x2160@60Hz 4:4:4 8bit

Support for HDMI 18G signals allows for the transmission of highly detailed 3840x2160@60Hz resolutions, perfect for detailed content in control rooms, medical setups or security installations. Ideal for KVM applications, the Extender consists of a transmitter and a receiver unit; the transmitter must be connected to a source such as a PC or KVM Switch, the console with display, keyboard and mouse must be connected to the receiver.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

The extender features an HDMI loop-through output on the transmitter which allows for simultaneous viewing using both the local and remote displays. With the EDID DIP-switch the user can copy EDID data from the display connected to the receiver or the loop-out port, or select from presets (4K60 and 1080p). Audio signal can be de-embedded from the 3.5mm output port on the receiver to connect speakers or headphones.

PoC (Power over Cable) functionality provides additional flexibility; this allows power to be supplied alongside data through Cat.6 network cable in a point-to-point connection between the two units, meaning only a single power supply is required at the transmitter or receiver unit. Ideal when power outlets are limited at the receiver end of the installation. In addition, the power supply is connected via a screw type DC jack, providing a more secure and reliable connection, perfect for professional installations where accidental disconnections could create a major issue.

This extender provides a simple plug and play installation with no additional drivers required, great for both professional and first time users.

Please note: This product is not designed to be used in conjunction with active network equipment and must only be used in a point to point connection.

Techninė specifikacija

Features	
Type	Transmitter & receiver
Connectivity technology	Wired
Maximum transfer distance	70 m
Cable types supported	Cat6
Maximum digital resolution	3840 x 2160 pixels
Maximum refresh rate	30 Hz
Product colour	Black
Material	Metal
LED indicators	Yes
Number of transmitters included	1
Transmitter	
Transmitter video port type	HDMI
Transmitter local video port	Yes
Transmitter local video port type	HDMI
Transmitter local keyboard/mouse port type	USB
RJ-45 ports quantity (transmitter)	1
Receiver	
Receiver local video port type	HDMI
Receiver local keyboard/mouse port type	USB
RJ-45 ports quantity (receiver)	1
Receiver local video ports quantity	1
Ports & interfaces	

USB port type	USB Type-A/USB Type-B
HDMI version	2
USB 1.1 ports quantity	3
Power	
Input current	1 A
DC-in jack	Yes
DC voltage	12 V
Weight & dimensions	
Transmitter width	9 cm
Transmitter depth	6.8 cm
Transmitter height	2.2 cm
Transmitter weight	560 g
Receiver width	9 cm
Receiver depth	6.8 cm
Receiver height	2.2 cm
Receiver weight	560 g
Packaging data	
Package width	215 mm
Package depth	135 mm
Package height	75 mm
Package weight	740 g
Packaging content	
AC adapter included	Yes
Cables included	USB
Manual	Yes
Mounting bracket(s) included	Yes
Included power plug types	AU, EU, UK, US
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	20 - 90%
Other features	
Supported video modes	2160p

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Bandwidth	18 Gbit/s
Compliance certificates	Federal Communications Commission (FCC), UKCA, CE, REACH, RoHS
Sustainability	
Sustainability compliance	Yes

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- Atitikties deklaracija

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.
Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB
lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH
Markircher Str. 22, 68229 Mannheim, DE
lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- Atitikties deklaracija