

StarTech.com VS222HD4K vaizdo signalo jungiklis HDMI

Gamintojas: **STARTECH** · Modelis: **VS222HD4K** · EAN: **065030862271** · Prekės kodas: **945262**



200,90 €

Kaina su PVM

Be PVM: **166,03 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vaizdo prievado tipas: HDMI
- ✓ Juoda
- ✓ 3840 x 2160 pikseliai



Aprašymas

Automatically switch between two 4K video sources on two displays, utilizing fast-switching technology

Save time and hassle by automatically switching between your HDMI audio/video sources. This 2x2 HDMI® matrix switcher provides the ultimate viewing experience, with support for Ultra HD 4K. It lets you connect two HDMI sources to two HDMI displays, with exceptional 4K resolution, while switching seamlessly between your video sources.

Impressive image quality with 4K support

The matrix switch supports Ultra HD 4K picture quality on two monitors while switching between content from HDMI source devices - including Blu-ray™ players or DVD players, computer systems, video game consoles, digital cable or satellite boxes, and A/V receivers.

4K support ensures a higher level of image clarity and visibility, delivering four times the resolution of 1080p - 8.29 million pixels versus 2.07 million pixels. It provides a more engaging visual experience for audiences in a wide range of venues including conference centers, boardrooms, educational facilities, and commercial settings. With its exceptional image quality, 4K resolution is also ideal for bringing your digital signage to life.

Fast and versatile switching options

Enjoy hassle-free operation with four different switching modes:

- Matrix switching: lets you route either HDMI source (Input 1 or Input 2) to either monitor (Output 1 and/or Output 2) - and independently switch two displays between two video sources.
- Fast auto-switching: ensures minimal time for switching between HDMI sources. The switch provides effortless operation with advanced auto-sensing - it detects the latest connected HDMI source and automatically switches both outputs to that device. It also ensures no downtime in a digital signage application if a source signal is accidentally powered off or fails.
- Priority switching: identifies the first port to have first priority for HDMI sources, which will be output on both displays.
- Manual switching: enables you to manually select your HDMI source with front-panel buttons that are easy to use.

An IR remote control is included in the box, enabling you to select your desired input source remotely. The RS-232 serial control interface ensures easy remote operation with serial control enabled devices.

Hassle-free setup with plug-and-play installation

The matrix switch is easy to install. EDID emulation saves you time during setup by ensuring all of your display settings, such as native resolution and refresh rate, are communicated between your display and video source devices. The built-in EDID copy feature maximizes compatibility with your 4K display, to ensure a convenient plug-and-play installation and the sharpest image quality.

The VS222HD4K is TAA compliant and backed by a 2-year StarTech.com warranty with free lifetime technical support.

Techninė specifikacija

Ryšys	
Vaizdo prievado tipas	HDMI
HDMI versija	1.4
HDMI įvestis	2
HDMI išvesčių skaičius	2
DC įėjimo lizdas	Taip
Savybės	
Produkto spalva	Juoda
HDCP	Taip
Palaikomi vaizdo režimai	1080p
LED indikatoriai	Aktyvumas, Energija
Maksimali rezoliucija	3840 x 2160 pikseliai
Nuotolinio valdymo tipas	IR
Garso išvesties kanalai	7.1 kanalai
Energijos valdymas	
AC adapterio įėjimo įtampa	100 - 240 V
AC adapterio įėjimo srovė	1,5 A
AC adapterio išėjimo įtampa	12 V

Sertifikatai

Sertifikavimas	CE, FCC
----------------	---------

Pakuotės duomenys

Pakuotės plotis	236 mm
Pakuotės gylis	158 mm
Pakuotės aukštis	67 mm
Paketo svoris	841 g

Pakuotės turinys

Greitos pradžios vadovas	Taip
Pridedamas nuotolinio valdymo pultelis	Taip
Pridėti kabeliai	Telefoninis (RJ-11)
Kintamosios srovės adapteris	Taip
Pridėti montavimo kronšteinai	Taip

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-20 - 70 °C
Darbo santykinės drėgmės diapazonas	0 - 80%

Techninė informacija

Atitikties sertifikatai	RoHS
Palaikomi garso įrašai	Taip

Logistikos duomenys

Darniosios sistemos (DS) kodas	85176990
Pagrindinės (išorinės) dėžės plotis	326 mm
Pagrindinės (išorinės) dėžės ilgis	408 mm
Pagrindinės (išorinės) dėžės aukštis	268 mm
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	12 vnt

Matmenys ir svoris

Matmenys (I × P × A)	24,00cm × 16,00cm × 6,00cm
Svoris	0,84kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA

startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL

startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt