

Intellinet 560559 tinklo komutatorius Valdomas Gigabit Ethernet (10/100/1000) Maitinimas per Eternetą (PoE) Juoda

Gamintojas: INTELLINET · Modelis: 560559 · EAN: 766623560559 · Prekės kodas: 945282



411,90 €

Kaina su PVM

Be PVM: 340,41 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Valdomas
- ✓ Paslaugos kokybės (QoS) palaikymas
- ✓ Pagrindinių perjungimo RJ-45 etherneto prievadų skaičius: 24
- ✓ Adreso lentelės dydis: 8000 įrašai Perjungimo pajėgumas: 52 Gbit/s
- ✓ Stovo montavimas
- ✓ AC Maitinimas per Eternetą (PoE)



Aprašymas

Save installation time and money with PoE. _x000D_

The Intellinet Network Solutions 24-Port Gigabit Ethernet PoE+ Web-Managed Switch with 2 SFP Ports (560559) is designed to pass both data and electrical power to a number of PoE-compatible devices via standard Cat5e or Cat6 network cables. Equipped with 24 Gigabit Ethernet ports, all of which support 802.3at/af Power over Ethernet (PoE/PoE+), this switch can power Wireless LAN access points and bridges, VoIP (Voice over Internet Protocol) telephones, IP surveillance cameras and more while delivering network speeds of up to 1000 Mbps. _x000D_

Power over Ethernet 802.3at. _x000D_

The Intellinet Network Solutions 24-Port Gigabit Ethernet PoE+ Web-Managed Switch with 2 SFP Ports supports the IEEE 802.3at protocol and is designed to inject up to 30 watts of power per port*. IEEE802.3af or IEEE802.3at compliant devices attached to the switch require no additional

power, thus eliminating the time and expense of electrical rewiring and minimising the unsightly clutter caused by power supplies and adapters in awkward places such as ceilings and walls. Any mix of PoE and non-PoE devices is supported, and thanks to its short circuit, overload and high-voltage protection function, your equipment is well-protected. For devices that are not 802.3at/af compliant (legacy wireless access points or network cameras), we suggest the use of an Intellinet Network Solutions PoE/PoE+ Splitter. _x000D_

x000D

x000D

Eliminate Bottlenecks with Gigabit Speeds_x000D_

x000D

Equipped with 24 auto-sensing 10/100/1000 Mbps RJ45 Gigabit Ethernet ports, the 24-Port Gigabit Ethernet PoE+ Web-Managed Switch with 2 SFP Ports offers plenty of performance for your computers, servers and other networking devices. In addition, two small form-factor pluggable GBIC module slots (SFP) provide fibre connectivity for greater distances. _x000D_

x000D

x000D

Web-Management_x000D_

x000D

This PoE switch is equipped with an impressive array of advanced management functions that allow you to be in full control over your network. The 24-Port Gigabit Ethernet PoE+ Web-Managed Switch with 2 SFP Ports supports VLAN, port aggregation, QoS, port mirroring, SNMP V1 and the popular SNMP V2c, just to name a few. _x000D_

x000D

x000D

* Total PoE budget for this switch is 240 watts. Per-port average power distribution is 10 watts; maximum per-port power usage cannot exceed 30 watts.

Techninė specifikacija

Valdymo funkcijos	
Perjungimo tipas	Valdomas
Paslaugos kokybės (QoS) palaikymas	Taip
Ryšys	
Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius	24
Pagrindinių perjungimo RJ-45 eterneto prievadų tipas	Gigabit Ethernet (10/100/1000)
Tinklas	
Tinklo standartai	IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
Srauto kontrolės palaikymas	Taip
Duomenų perdavimas	
Adreso lentelės dydis	8000 įrašai
Perjungimo pajėgumas	52 Gbit/s
Palaikomi duomenų perdavimo greičiai	10/100/1000
Persiuntimo dažnis	1,488 Mpps
Konstrukcija	
Stovo montavimas	Taip

Produkto spalva	Juoda
LED indikatoriai	Taip
Energijos valdymas	
Maitinimo šaltinis	AC
AC įėjimo įtampa	90 - 260 V
AC įėjimo dažnis	50 - 60 Hz
Galios suvartojimas (maks.)	260 W
„Power over Ethernet“ (PoE)	
Maitinimas per Eternetą (PoE)	Taip
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-20 - 70 °C
Darbo santykinės drėgmės diapazonas	10 - 90%
Svoris ir matmenys	
Plotis	440 mm
Ilgis	208 mm
Aukštis	44 mm
Svoris	3,55 kg
Pakuotės turinys	
Instrukcija	Taip
Sertifikatai	
Sertifikavimas	FCC Class A, CE
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85176990

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

[intellinetnetwork.eu](mailto:info@shopro.lt)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt