ATEN CL3116NX rack console 47 cm (18.5") 1366 x 768 pixels Metal, Plastic Black 1U

Gamintojas: **ATEN** · Modelis: **CL3116NX F** · EAN: **4710469343735** · Prekės kodas: **945285**



1 411,90 €

Kaina su PVM

Be PVM: **1 166,86 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Exclusive LED illumination light
- ✓ Integrated LCD KVM console with an 18.5'' LED-backlit widescreen LCD monitor in a single rail housing with top and bottom clearance for smooth operation in a 1U high system rack
- ✓ Cascade up to 2 levels – CL3116 controls up to 256 computers from a single console
- ✓ Keyboard and mouse emulation (PS/2 and USB) for smooth switching and simultaneously booting multiple computers even when the console focus is elsewhere





Aprašymas

The ATEN CL3116 LCD KVM Switch offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 18.5" LED-backlit LCD monitor, and a touchpad in a 1U rack-mountable sliding housing. The short-depth design maximizes space utility for equipping rack-mounting devices in narrow spaces. In addition, its exclusive LED illumination light provides users with proper visibility when working in low-light conditions.

The CL3116 can control up to 16 computers; when 16 additional KVM switches are cascaded, a single CL3116 LCD KVM Switch can control up to 256 computers. To achieve greater operational efficiency, the CL3116 offers Broadcast mode, which the console spreads out the commands to all computers to perform operations simultaneously. Besides, the Auto scan mode fulfills the needs for continuous monitoring a specific group of computers, and establishing a reliable working environment for users.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

To enhance information safety, the CL3116 provides two-level password security which restricts unauthorized users from viewing and controlling the computers. For added convenience, the CL3116 comes with an additional hot-pluggable USB mouse port that only supports HID device for keyboard and mouse.

As a feature-rich LCD KVM Switch, the CL3116 is aimed not just to achieve but exceed the requirements for space utility optimization, superior video quality, adaptive deployment, and operational versatility, and thus is ideal for control rooms with limited space in any industry.

Note: Optional rack mount kits are available. For more information, refer to Compatible Accessories below.

Techninė specifikacija

Display	
Display diagonal	47 cm (18.5")
Display resolution	1366 x 768 pixels
Display	LCD
Display brightness	450 cd/m²
Contrast ratio (typical)	1000:1
Viewing angle, horizontal	170°
Viewing angle, vertical	160°
On Screen Display (OSD)	Yes
Pixel pitch	0.3 x 0.3 mm
Display type	TFT
Response time	5 ms
Supported resolutions	up to 1920 x 1200 @ 60 Hz; 1366 x 768 @ 60 Hz, DDC2B
Technical details	
Rack capacity	1U
Material	Metal, Plastic
Product colour	Black
Hot-Plug support	Yes
Operating relative humidity (H-H)	0 - 80%
Built-in KVM switch	Yes
KVM switch ports quantity	16
Maximum resolution	1920 x 1200 pixels
Rack mounting	Yes
Number of computers controlled	256
On/off switch	Yes
LED indicators	Yes
Push button	Yes

Compliance certificates	RoHS
Ports & interfaces	
3.5 mm (1/8-inch) in	Yes
VGA (D-Sub) ports quantity	1
Keyboard port type	USB
Mouse port type	USB, PS/2
Video port type	VGA
USB 2.0 Type-A ports quantity	1
I/O ports	16x SPHD
Keyboard	
Built-in touchpad	Yes
Keyboard language	French
Keyboard layout	AZERTY
Hot keys	Yes
Power	
AC adapter input voltage	100 - 240 V
AC adapter frequency	50/60 Hz
Input current	1 A
AC (power) in	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Other operating systems supported	SunOS
Weight & dimensions	
Width	631 mm
Height	42.8 mm
Depth	480.6 mm
Weight	10.6 kg
Packaging content	
Cables included	AC, KVM

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Quick installation guide	Yes
Manual	Yes
AC adapter included	Yes
Rack mount kit	Yes
Package type	Box

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.
Datung Road No.125, Sec. 2, 221 New Taipei City, TW
aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt