

StarTech.com Fiber Media Converter Gigabit 1000Mbps MM Fibre LC 550m

 Gamintojas: **STARTECH** · Modelis: **ET91000LC2** · EAN: **065030846226** · Prekės kodas: **945438**


241,90 €

Kaina su PVM

 Be PVM: **199,92 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 2000 Mbit/s 550 m 850 nm
- ✓ Ethernet LAN (RJ-45) ports: 1 DC-in jack
- ✓ Multi-mode Fiber ports quantity: 1 LC
- ✓ Black



Aprašymas

Convert and extend a Gigabit Ethernet connection up to 550 m / 1804 ft over Multimode LC fiber

The ET91000LC2 1000 Mbps Gigabit Multimode Fiber Media Converter (LC, 550m) lets you extend a Gigabit Ethernet network over multimode fiber, at distances up to 550m (1804 ft).

A cost-effective solution for connecting a Gigabit Ethernet (1000Base-T) network to remote network segments over a (1000Base-LX/SX) fiber backbone, this GbE to MM fiber converter supports full Gigabit speeds for ideal network performance and scalability. Designed to offer a durable and convenient Ethernet-to-fiber solution, the Ethernet to LC Fiber converter features an all-steel chassis, and a simple plug-and-play installation with minimal configuration required.

For added versatility, this fiber media converter supports standalone operation, or installation into the 20 Slot, 2U Rackmount Chassis (ETCHS2U), as well as a replaceable SFP slot.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

The StarTech.com Advantage

- Link loss forwarding, remote status monitoring ensures maximum up-time

- Provides Ethernet to Fiber conversion as a standalone device, or can be installed into the ETCHS2U 20 slot chassis for added versatility
- Rugged steel casing for durability in harsh environments

Techninė specifikacija

Network		
Maximum data transfer rate		2000 Mbit/s
Converter input interface		1000Base-T
Converter output interface		1000Base-LX, 1000Base-SX
Ethernet interface type		Gigabit Ethernet
Ethernet LAN data rates		1000 Mbit/s
Auto MDI/MDI-X		Yes
Duplex system		Full, Half
Performance		
Maximum transfer distance		550 m
Wavelength		850 nm
Fiber mode structure		Multi-mode
Mean time between failures (MTBF)		65000 h
Features		
Internal		No
Plug and Play		Yes
Product colour		Black
Ports & interfaces		
Fiber optic connector		LC
Connectivity technology		Wired
Ethernet LAN (RJ-45) ports		1
Fiber ports quantity		1
DC-in jack		Yes
Power		
Output voltage		12 V
Output current		1 A
Power consumption (typical)		4 W

External power adapter	Yes
Weight & dimensions	
Weight	620 g
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Packaging content	
Manual	Yes
Packaging data	
Package width	206 mm
Package depth	138 mm
Package height	89 mm
Package weight	774 g
Certificates	
Compliance certificates	RoHS
Certification	CE, FCC
Logistics data	
Harmonized System (HS) code	85176990
Other features	
Dimensions (WxDxH)	95 x 160 x 20 mm
Full duplex	Yes

Gamintojo ir saugos informacija

GAMINTOJAS	ATSAKINGAS ASMUO ES	PLATINTOJAS
StarTech.com Ltd.	StarTech.com Limited	MB KOMPIUTERIŲ GURU
Artisans Crescent 45, N5V 5E9 Ontario, London, CA	Laarderhoogtweg 25, 1101 EB Amsterdam, NL	V. Nagevičiaus g. 3, LT-08237 Vilnius
startech.com	startech.com	info@shopro.lt