StarTech.com 4-Port HDMI Splitter - 4K 60Hz

Gamintojas: **STARTECH** · Modelis: **ST124HD202** · EAN: **065030880398** · Prekės kodas: **945449**

104,89 €

Kaina su PVM

Be PVM: **86,69 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4-PORT HDMI SPLITTER: Displays the same image with sound on 4 screens; Splits an HDMI video signal up to Ultra HD 4K 60Hz & 7.1 CH audio; 4:4:4 chroma subsampling support w/ bandwidth up to 18Gbps (HDMI 2.0b); HDR; HDCP 2.2 to HDCP 1.4 conversion
- ✓ EDID EMULATION: 1x4 HDMI splitter 4K automatically passes EDID between your video source and the display attached to port 1 ensuring native settings (such as resolution and refresh rate) are configured
- ✓ AUDIO SUPPORT: Audio output is supported on all ports simultaneously; Support for 7.1 surround sound audio including Dolby® True HD and DTS HD Master Audio
- ✓ LONG REACH: Reach up to 16.4ft (5m) with a passive HDMI cable; For longer distances, active HDMI cables or HDMI extenders are available (sold separately) to use with this HDMI splitter for 4x TVs/projectors/monitors/displays
- ✓ EASY SETUP: No drivers required for this 1-input 4-output UHD HDMI 2.0 splitter box; Simply connect cables and power with the EDID switch set to Auto to get started; Wide screen monitor formats supported; HDMI/DVI compatible







Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903



Aprašymas

1 In 4 Out Video Splitter | HDMI 2.0 | HDR | 2-Year Warranty

This 4-Port 4K HDMI splitter connects your HDMI video source to four HDMI displays at the same time, without distorting or degrading your video signal. For dependable performance, the splitter features a durable metal housing that provides passive cooling.

True 4K at 60Hz and HDR

With transmission bandwidth up to 18Gbps, this HDMI splitter is fully compatible with your HDMI 2.0 equipment, supporting UHD resolutions up to 4096x2160 (4K) at 60Hz. For smooth video and color transitions, the splitter offers 4:4:4 chroma subsampling, so every pixel gets its own unique color.

The splitter also supports High Dynamic Range (HDR) imaging, offering a greater luminosity than standard digital imaging.

Widely Compatible

The 4-way HDMI splitter supports HDCP 2.2 and is backward compatible with 4K 30Hz and 1080p displays. This ensures that it will work with almost any HDMI source, or destination device such as computers, Blu-ray players, monitors, TVs and projectors. Perfect for digital signage applications, where equipment may vary throughout your site.

Easy Installation

For hassle-free setup, the 1x4 HDMI splitter offers easy plug-and-play installation. The splitter also saves you setup time by automatically passing EDID between your video source and the display attached to port 1, ensuring settings like native resolution and refresh rate are configured properly.

ST124HD202 is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Techninė specifikacija

Ports & interfaces	
Video ports quantity	4
Video port type	HDMI
Video out	4x HDMI
HDMI version	2
Features	
Maximum resolution	3840 x 2160 pixels
Product colour	Black
Full HD	Yes
HD type	4K Ultra HD

Maximum refresh rate	60 Hz
HDCP	Yes
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1600 (WQXGA), 3840 x 2160
Power LED	Yes
Plug and Play	Yes
Supported video modes	720p, 1080p
LED indicators	Yes
Certification	CE, FCC, REACH
Power	
AC input voltage	100 - 240 V
Input current	1 A
Output voltage	5 V
Output current	0.2 A
Power consumption (typical)	5 W
Weight & dimensions	
Width	64 mm
Depth	165 mm
Height	65 mm
Weight	506 g
Packaging data	
Package width	151 mm
Package depth	216 mm
Package height	68 mm
Packaging content	
User guide	Yes
Included power plug types	AU, EU, NA, UK
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Technical details	
Maximum cable length	5 m
Supported audio channels	7.1
Compliance certificates	RoHS

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Logistics data	
Harmonized System (HS) code	85176990
Master (outer) case width	453 mm
Master (outer) case length	360 mm
Master (outer) case height	329 mm
Products per master (outer) case	20 pc(s)
Matmenys ir svoris	
Svoris	0,54kg

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- Vaizdo įrašas youtube.com/watch?v=gsEgk1YCL14

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.
Artisans Crescent 45, N5V 5E9 Ontario, London, CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited
Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.