

Intellinet Power over Ethernet (PoE) Injector, 1 Port, 48 V DC, IEEE 802.3af Compliant

Gamintojas: **INTELLINET** · Modelis: **524179** · EAN: **766623524179** · Prekės kodas: **945541**



36,91 €

Kaina su PVM

Be PVM: **30,50 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Ideal when AC power is not available
- ✓ Distance support: up to 100 m (328 ft.)
- ✓ Power output of up to 15.4 Watts
- ✓ Supports all IEEE 802.3af-compliant PoE devices (Wireless LAN access points and bridges, VoIP (Voice over Internet Protocol) telephones, IP surveillance cameras)
- ✓ Supports IEEE 802.3af detection and short circuit, overload and high-voltage protection
- ✓ Full-power Class 3 PoE design
- ✓ Fanless design ideal for silent operation
- ✓ Three-Year Warranty



Aprašymas

Reduce costs by using existing Cat5 cable to provide both power and data.

The INTELLINET NETWORK SOLUTIONS Power over Ethernet Injector allows you to connect your IEEE 802.3af-compliant products to a non-PoE LAN switch port. The injector can be used to connect a wireless access point, IP phone, network camera or any IEEE 802.3af powered device (PD) to a switch.

Reduce Wiring Costs

No need to run AC power lines for your wireless access point, network camera or IP phone. Simply connect the PoE Injector to the LAN switch port, and use the existing Cat5 cabling to deliver DC power as well as transfer data.

Preserve Existing Investments

Does your existing LAN switch not support the new IEEE 802.3af PoE standard? Well, don't let that stop you from realising the benefits of delivering DC power over the existing Cat5 Ethernet cabling. Use the Model 503389 PoE Injector until you are able to upgrade your LAN switch to a model that supports the IEEE 802.3af PoE standard.

Protect Your Equipment

Now that you are running DC power to your networked equipment through the Cat5 cabling, you need to be sure that the products are protected from power problems. The PoE Injector was designed to protect equipment from short circuits (short GRND), current overloads (over 450 mA) and high voltages (voltage exceeding 52 V).

Techninė specifikacija

Network	
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Power over Ethernet (PoE)	Yes
Networking standards	IEEE 802.3, IEEE 802.3af, IEEE 802.3u
Cable types supported	Cat5
Features	
Product colour	Black
LED indicators	No
Safety	SCP
Power protection features	Over voltage, Overload, Short circuit
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
Power	
Power over Ethernet (PoE) voltage	52 V
Power requirements	15.4 W

AC adapter frequency	50/60 Hz
Input voltage	100 - 240 V
Input frequency	50 - 60 Hz
Input current	0.45 A
AC adapter output voltage	48 V
Output current	0.35 A
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Certification	FCC Class B, Part 15, CE 89/336/EEC, UKCA, NDAA
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-20 - 85 °C
Weight & dimensions	
Size (imperial)	5.08 cm (2")
Width	50 mm
Depth	120 mm
Height	35 mm
Weight	140 g
Packaging content	
Number of products included	1 pc(s)
Manual	Yes
Logistics data	
Harmonized System (HS) code	85044095

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH
Löhbach Str. 7, D-58553 Halver, DE
[intellinetnetwork.eu](mailto:info@shopro.lt)

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt